

Characterization of Microring Filters for Differential Group Delay Applications

D. Doménech, P. Chamorro-Posada, F.J. Fraile-Pelaez, M.J. Erro, S. Tainta, M.A. Muriel, R. Baños, J. Bolten and H. Kleinjans

Index Terms—Integrated optics, couplers, optical filters, microring resonators, group delay.

Abstract—The longitudinal offset technique permits to improve the accuracy of the coupling coefficients of integrated directional couplers and provides designs that can be easily implemented with current fabrication tolerances. In this work, we address the additional degree of freedom offered by this technology in order to tailor the differential group delay in coupled-resonator optical filters. We present the characterization of several devices exploiting this feature and we discuss their potential applications.

I. INTRODUCTION

Microring devices have reached a prominent status as a key technology for the implementation of both linear [1], [2], [3], [4], [5], [6] and nonlinear [7], [8] photonic signal processing functionalities. In particular, due to their versatility, coupled resonator optical waveguides (CROW) [9] find many applications in the control of the group delay [10], [11].

At the top-level design, the coupling constants are fundamental parameters determined by the transversal separation between the coupler waveguides in the standard fabrication process of the structures. To meet the typically required accuracy levels, such separation must be set with a precision of around a few nanometers, bordering technological limits. To overcome this difficulty, an alternative approach was proposed in [12], [13], which consists in varying the coupling length rather than the inter-guide separation, by changing the longitudinal offset between the two parallel coupled straight waveguides of fixed length. Photolithographic production is then feasible as the resolution requirements are strongly relaxed.

As was highlighted in [14], there exists an asymmetry in the phase transmission characteristics of longitudinal offset structures that opens up new possibilities for the design

This work has been funded by MINECO, project numbers TEC2010-21303-C01, 02, 03 and 04.

D. Doménech is with VLC Photonics S.L., Camino de Vera s/n, 46022 Valencia, Spain.

P. Chamorro-Posada is with the Departamento de Teoría de la Señal y Comunicaciones e Ingeniería Telemática, Universidad de Valladolid, ETSI Telecomunicación, Paseo Belén 15, E-47011 Valladolid, Spain.

F.J. Fraile-Peláez is with Dept. Teoría de la Señal y Comunicaciones, Universidad de Vigo, ETSI Telecomunicación, Campus Universitario, E-36310 Vigo (Pontevedra), Spain.

M.J. Erro and S. Tainta are with Department of Electrical and Electronic Engineering, Universidad Pública de Navarra, 31006 Pamplona, Spain.

M.A. Muriel is with Department of Photonic Technology, Universidad Politécnica de Madrid, 28040 Madrid, Spain.

R. Baños is with Universitat Politècnica de Valencia, iTEAM, Camino de Vera s/n, 46022 Valencia, Spain.

J. Bolten and H. Kleinjans are with AMO GmbH, Otto-Blumenthal-Straße 25, 52074 Aachen, Germany.




Fig. 1. Geometry of a three-ring longitudinal offset CROW implementing two transfer functions with distinct group delays.

of photonic devices based on the control of the associated differential group delay. Several structures were proposed in [14] and their experimental demonstration is presented here.

II. TRANSMISSION PROPERTIES

The two sets of input/output ports available in a longitudinal offset CROW are respectively marked as *A* and *B* in Figure 1 for a three-ring system. The associated transmission paths for the fast and slow port sets are identified with dashed and solid arrows, respectively. The corresponding transfer functions are [14]

$$\begin{aligned} H_A(\omega) &= \exp(j\tau_{\text{off}}\omega)H(\omega) \\ H_B(\omega) &= \exp(-j\tau_{\text{off}}\omega)H(\omega). \end{aligned} \quad (1)$$

$H(\omega)$ is a common transmission term that can be evaluated [14] as $1/m_{11}$ in the expression

$$\begin{pmatrix} m_{11} & m_{12} \\ m_{21} & m_{22} \end{pmatrix} = \prod_{l=0}^N \frac{1}{(jt_l)} \begin{pmatrix} -\exp(j\beta L) & r_l \\ -r_l & \exp(-j\beta L) \end{pmatrix}, \quad (2)$$

where L is one half of the total ring length, which is assumed to be constant in the structure, β is the propagation constant, and r_l and t_l are, respectively, the bar and cross coupling coefficients for the optical field at coupler l .

The differential group delay parameter is defined as

$$\tau_{\text{off}} = n_g/c \sum_{l=0}^N L_{\text{off},l}, \quad (3)$$

where n_g is the group index in the optical waveguides, and $L_{\text{off},l}$ is the longitudinal offset for coupler l . τ_{off} can be identified in Figure 1 as the net propagation path difference due to the longitudinal offsets in the structure with no resonance enhancement. Therefore, this differential delay is limited by the ring size and the number of resonators. A given coupling coefficient can be typically obtained at different offset lengths, permitting to adjust the total differential group delay.

III. FABRICATION AND CHARACTERIZATION

The devices have been fabricated on an SOI substrate consisting of a $3\mu\text{m}$ thick buried oxide layer and a 220 nm thick Si layer by EBL and dry etching in a two-step process. First, using hydrogen silsesquioxane negative tone resist in combination with a high contrast development process [15] all device features are defined and fully etched to the buried oxide using an HBr-based ICP-RIE process [16]. In a second step, a positive tone ZEP resist mask is carefully aligned to those features, exposed and used to define the shallow etched parts of the devices using a C4F8/SF6-based dry etching process. For both process steps a multi pass exposure approach is used to further reduce the sidewall roughness of the photonic device, hence minimizing scattering losses. Special care is taken to guarantee accurate critical dimensions of all parts of the device by applying a very accurate proximity effect correction in combination with a well-balanced exposure dose [17].

The wire waveguides are 450 nm wide and 220 nm thick to ensure TE monomode propagation. The measured linear propagation loss in such photonic wires is $3 \pm 0.5\text{ dB/cm}$.

The resolution of the e-Beam lithography employed is below 10 nm thus leading to a very accurate control of the coupling gaps between rings. The coupling constant uncertainty can be controlled below 10%. The longitudinal offset technique has been applied in order to guarantee the uniformity between cavities since the gap is kept constant for all the rings.

All input/output waveguides in the chip have been provided with grating couplers [18]. The measurements have been normalized to the response of a straight waveguide in order to remove the spectral response of the grating coupler.

A. Three-port structures

We first consider the structure obtained when two ports in the reference structure of Figure 1 are combined using a Y-branch coupler. The resulting geometry is shown in Figure 2, where we have employed an MMI coupler.

This set-up permits to obtain two identically filtered replicas of the input with a relative delay

$$\Delta\tau = 2\tau_{\text{off}} = 2\frac{n_g}{c} \sum_{l=0}^N L_{\text{off},l} \quad (4)$$

that, in the case of equal $L_{\text{off},l} = L_{\text{off}}$, reads

$$\Delta\tau = 2(N+1)\frac{L_{\text{off}}n_g}{c}. \quad (5)$$




Fig. 2. SEM image of the fabricated structure producing two output replicas with a controlled relative group delay with five racetracks.

We have fabricated and characterized three structures with 3, 5 and 10 racetrack micro-rings, respectively. In all cases, the bend radius of the racetracks $R = 5\mu\text{m}$, the coupling gaps are $s = 0.2\mu\text{m}$, $L_{\text{off}} = 82.339\mu\text{m}$ and the total cavity length is $L_{\text{cav}} = 2L = 231.42\mu\text{m}$ with an associated free spectral range of $FSR = c/(L_{\text{cav}}) \simeq 285\text{ GHz}$. The coupling constant at a reference wavelength $\lambda = 1.55\mu\text{m}$ is $K = |t|^2 = 0.64$.

Using (5), the differential delay between outputs are 9.99 ps , 14.98 ps and 27.47 ps for 3, 5 and 10 rings structures, respectively. Figure 3 (a) compares the measured signals as transmitted in the fast and slow paths at four different values of the carrier frequency in the filter pass-bands. Ten measurements have been performed per wavelength to estimate the average and the standard deviation of the group delay. Figure 3 (b), shows the excellent agreement between experiment and theory.

This structure can be cascaded and could find application, for instance, in optical beam-forming networks [19] as discussed in [14]. Reversing the input and output ports, the structures can also be employed for simultaneously implementing a precise filtering operation through $H(\omega)$ and obtaining a time-domain multiplexed output signal from two input signals.

B. Two-port structures

New design possibilities are found when both the input and output ports are connected using Y couplers. If $\Delta\tau$ is greater than the pulse duration the addition of a phase control in one of the output paths, for instance, can be used [14] for the production and processing of time-bin encoded states for quantum information applications [20], [21], [22]. In this case we have a compact integrated set-up incorporating the precise waveform shaping provided by the filtering in the CROW.

The combination of ports, both at the input and output of the device in a Mach-Zehnder configuration, can also be used to double the FSR of a given structure without significantly affecting the bandwidth and introducing additional transmission nulls between resonances. If we assume the same input in Eqs. (1) and combine them into a single output, we obtain




Fig. 3. (a) Measured output pulse intensities at four different wavelengths for three (top) five (middle) and ten (bottom) rings. (b) Average group delay and its standard deviation for each structure.




Fig. 4. SEM image of the fabricated and characterized 3-ring MZ configuration devices with (top) and without (bottom) longitudinal offset couplers.

the transfer function

$$H_{MZ}(\omega) = \cos(\tau_{\text{off}}\omega)H(\omega). \quad (6)$$

To double the FSR, the position of a spectral null every other




Fig. 5. Measured transmission response of a three-ring Mach-Zehnder device configuration with and without longitudinally offset couplers and the corresponding calculated response for the case including longitudinal offsets.

transmission band of the CROW filter requires the fulfillment of the condition $\tau = 4\tau_{\text{off}}$ or, for constant $L_{\text{off},l} = L_{\text{off}}$,

$$L_{\text{off}} = \frac{L}{2(N+1)}. \quad (7)$$

The one-half resonator length is $L = L_a + L_{\text{off}} + \pi R$, where $L_s = L_a + L_{\text{off}}$ is the total length of the straight waveguide sections. Therefore, the above condition reads

$$L_{\text{off}} = \frac{L_a + \pi R}{2N + 1}. \quad (8)$$

The measured transmission responses of two MZ configurations with and without longitudinal offset differential group delay, as displayed in Figure 4, are compared in Figure 5 along with the transfer function computed using coupled mode theory. In this case $s = 0.3 \mu\text{m}$, $L_s = 88.233 \mu\text{m}$ and $L_{\text{off}} = 12.993 \mu\text{m}$. The measurements clearly show the expected FSR doubling in the structure. When comparing the results for the MZ configurations with and without differential group delay, it is important to bear in mind that the introduction of the longitudinal offset modifies the coupling constant in the structure.

If the design based on the condition (8) is too sensitive to fabrication tolerances, an alternative, more robust, design can be obtained for a limited bandwidth [14]. If $\tau = s\tau_{\text{off}}$, with s a rational number close to 4, the MZ and CROW resonance conditions will coincide in a particular band of the CROW periodic response, and an approximate cancellation will happen in a certain bandwidth that will depend on the value of s . In this case, the value of a constant offset for a given coupler length is given by the expression

$$L_{\text{off}} = \frac{2L_a + 2\pi R}{(N+1)s - 2}. \quad (9)$$

Figure 6 shows the experimental and simulated results for $s = 0.35 \mu\text{m}$, $L_s = 109.558 \mu\text{m}$, $L_{\text{off}} = 15.408 \mu\text{m}$, $n = 1000$ and $m = 246$. In this case, the FSR doubling has been achieved for a 20 nm bandwidth.




Fig. 6. Measured transmission response of a three-ring Mach-Zehnder device configuration with and without longitudinally offset couplers and the corresponding calculated response with longitudinal offsets.

IV. CONCLUSION

We have fabricated and characterized various structures exploiting the inherent differential group delay available in CROW chains realized by means of the longitudinal offset technique. Three port networks, obtained by combining either the input or output ports of the fast and slow channels, and two port networks, with port combination taking place both at the input and the output, have been demonstrated. Three port networks could find application, for instance, for combining filtering and time-domain multiplexation operations in integrated optical circuits applications or as building blocks for complex group delay networks that could be used in optical beam-forming antennas. The two port devices could be used for quantum information time-bin encoding applications for differential delays of the order of the pulse duration. We have demonstrated a more general set-up for FSR doubling in quasi-periodic filters. Simultaneous filtering and relative delaying operations can also be performed combining cascaded bandpass filters and waveguide delay pairs. In large integrated circuits with extensive use of this type of operations, our proposal permits to obtain more compact designs and a relevant reduction of the number of elements. In Quantum Information applications [22], the reduction of the complexity and the elimination of off-circuit filters has a direct impact on the photon loss, which is critical for the device operation, and avoids asymmetries that can also affect system performance.

REFERENCES

- [1] G. Lenz and C. K. Masden, "General optical all-pass filter structures for dispersion control in WDM systems," *J. Lightwave Technol.*, vol. 17, no. 7, pp. 1248–1254, Jul. 1999.
- [2] P. Chamorro-Posada, F.J. Fraile-Pelaez and F.J. Diaz-Otero, "Micro-ring chains with high-order resonances," *J. Lightwave Technol.*, vol. 29, no. 10, pp. 1514–1521, 2011.
- [3] C. K. Madsen, G. Lenz, A. J. Bruce, M. A. Cappuzzo, L. T. Gomez, and R. E. Scotti, "Integrated all-pass filters for tunable dispersion and dispersion slope compensation," *IEEE Photon. Technol. Lett.*, vol. 11, No. 12, pp. 1623–1625, Dec. 1999.

- [4] C. Y. Chao, W. Fung, and L. J. Guo, "Polymer microring resonators for biochemical sensing applications," *IEEE J. Sel. Top. Quantum Electron.*, vol. 12, no. 1, pp. 134–142, Jan./Feb. 2006.
- [5] R. W. Boyd, D. J. Gauthier, and A. L. Gaeta, "Applications of Slow Light in Telecommunications," *Opt. Photonics News*, vol. 17, no. 4, pp. 18–23, Apr. 2006.
- [6] P. Chamorro-Posada, and F. J. Fraile-Pelaez, "Fast and slow light in zigzag microring resonator chains," *Opt. Lett.*, vol. 34, no. 5, pp. 626–628, Mar. 2009.
- [7] R. Gómez-Alcalá, F. J. Fraile-Pelaez, P. Chamorro-Posada and F.J. Díaz-Otero, "Modeling of racetrack-resonator add-drop filters with arbitrary nonlinear directional couplers," *Opt. Lett.*, vol 37, no. 11, pp. 2097–2909, Jun. 2012.
- [8] V. Grigoriev and F. Biancalana, "Resonant self-pulsations in coupled nonlinear microcavities," *Phys. Rev. A*, vol. 80, p. 043816, Apr. 2011.
- [9] A. Yariv, Y. Xu, R.K.Lee and A. Scherer, "Coupled-resonator optical waveguide: a proposal and analysis," *Opt. Lett.*, vol. 24, no. 11, pp. 711–713, June 1999.
- [10] J. E. Heebner and R. W. Boyd, "Slow and fast light in resonator-coupled waveguides," *J. Mod. Opt.*, vol. 49, no. 14/15, pp. 2629–2636, Nov/Dec. 2002.
- [11] J. K. Poon, L. Zhu, G. A. DeRose, and A. Yariv, "Transmission and group delay of microring coupled-resonator optical waveguides," *Opt. Lett.*, vol. 31, no. 4, pp. 456–458, Feb. 2006.
- [12] J. D. Doménech, P. Muñoz, and J. Capmany, "The longitudinal offset technique for apodization of coupled resonator optical waveguide devices: concept and fabrication tolerance analysis," *Opt. Express*, vol. 17, no. 23, pp. 21050–21059, Nov. 2009.
- [13] J.D. Doménech, P. Muñoz, and J. Capmany, "Transmission and group-delay characterization of coupled resonator optical waveguides apodized through the longitudinal offset technique," *Opt. Lett.*, vol. 36, no. 2, pp. 136–138, Jan. 2011.
- [14] P. Chamorro-Posada and F.J. Fraile Peláez, "Group Delay Control in Longitudinal Offset Coupled Resonator Optical Waveguides," *J. Lightwave Technol.*, vol. 33, no. 9, pp. 1703–1707, Aug. 2014.
- [15] W. Henschel, Y.M. Georgiev and H. Kurz, "Study of a high contrast process for hydrogen silsesquioxane as a negative tone electron beam resist," *J. Vac. Sci. Technol. B*, vol. 21, no. 5, pp. 2018–2025, 2003.
- [16] M.C. Lemme, T. Mollenhauer, H.D.G. Gottlob, W. Henschel, J. Efavi, C. Welch and H. Kurz, "Highly selective HBr etch process for fabrication of Triple-Gate nano-scale SOI-MOSFETs," *Microelec. Eng.*, vol. 73, pp. 346–350. 2004.
- [17] J. Bolten, T. Wahlbrink, N. Koo, H. Kurz, S. Stammberger, U. Hofmann and N. Ünal, "Improved CD control and line edge roughness in E-beam lithography through combining proximity effect correction with gray scale techniques," *Microelec. Eng.*, vol. 8, pp. 10411043, 2010.
- [18] D. Taillaert, F. Van Laere, M. Ayre, W. Bogaerts, D. Van Thourhout, P. Bienstman and R. Baets, "Grating Couplers for Coupling between Optical Fibers and Nanophotonic Waveguides," *Japanese J. of Appl. Phys.*, vol. 45, pp. 6071–6077, 2006.
- [19] L. Zhuang, C.G.H. Roeloffzen, R.G. Heideman, A. Borreman, A. Meijerink, W. van Etten, "Single-chip ring resonator-based 1×8 Optical Beam Forming Network in CMOS-Compatible Waveguide Technology," *IEEE Photon. Technol. Lett.*, vol. 19, no. 15, pp. 1130–1132, Aug. 2007.
- [20] J. Brendel, N. Gisin, W. Tittel, and H. Zbinden, "Pulsed Energy-Time Entangled Twin-Photon Source for Quantum Communication," *Phys. Rev. Lett.*, vol. 83, no. 12, pp. 2594–2597, March 1999.
- [21] W. Tittel, J. Brendel, H. Zbinden, and N. Gisin, "Quantum Cryptography Using Entangled Photons in Energy-Time Bell States," *Phys. Rev. Lett.*, vol. 84, no. 20, pp. 4737–4740, May 2000.
- [22] C. Xiong, et al "Compact and reconfigurable silicon nitride time-bin entanglement circuit," *Optica*, vol. 2, no. 2, pp. 724–727, Aug. 2015,