



R news and tutorials contributed by (573) R bloggers

- [Home](#)
- [About](#)
- [RSS](#)
- [add your blog!](#)
- [R jobs](#) ♦♦♦
- [Contact us](#)

Welcome!

Follow

Here you will find daily **news and tutorials about R**, contributed by over 573 bloggers.

There are many ways to **follow us -**

[By e-mail:](#)

18204 readers

BY FEEDBURNER

[On Facebook:](#)



R blog...
26 391 Me gu...

Me gusta esta página

Sé el primero de tus amigos en indicar que te gusta esto.


If you are an R blogger yourself you are invited to [add your own R content feed to this site](#) (**Non-English** R bloggers should add themselves-[here](#))

[Jobs for R-users](#)

- [Product Analyst \(@ Pittsburgh \)](#)
- [Quantitative Developer/Data Scientist \(@ Mountain View\)](#)
- [Data Scientist AWF](#)
- [Network Link analysis Consultant \(@ London\)](#)
- [Seeking R](#)

[Programmers for
long term contract
role](#)

Search & Hit Enter

Popular Searches

- [heatmap](#)
- [web scraping](#)
- [maps](#)
- [undefined](#)
- [hadoop](#)
- [shiny](#)
- [twitter](#)
- [boxplot](#)
- [animation](#)
- [ggplot2](#)
- [trading](#)
- [finance](#)
- [time series](#)
- [latex](#)
- [excel](#)
- [ggplot](#)
- [pca](#)
- [quantmod](#)
- [googlevis](#)
- [eclipse](#)
- [market research](#)
- [rstudio](#)
- [how to import
image file to R](#)
- [tutorial](#)
- [knitr](#)
- [rattle](#)
- [coplot](#)
- [rcmdr](#)
- [gis](#)
- [sweave](#)

Recent Posts

- [Differences in the
network structure
of CRAN and
BioConductor](#)
- [SWMPPr 2.1.0 on
CRAN](#)
- [Visualizing bdsns
data using bdvis](#)
- [How Do Auction
Values Differ by the
Number of Teams
in Your League? A
Multilevel Model](#)
- [How do you know
if your data has
signal?](#)
- [Multilevel Models
and Political
Advertising](#)
- [JSM 2015 \[day
#2\]](#)

- [The Keep Function](#)
- [On radical manuscript openness](#)
- [How Do You Know if Your Data Has Signal?](#)
- [In case you missed it: July 2015 roundup](#)
- [Share your Shiny Apps with Docker and Kitematic!](#)
- [JSM 2015 \[day #1\]](#)
- [Curl 0.9.2: tweaks and proxies for windows](#)
- [Turning your R \(or Python\) models into APIs](#)

Other sites

- [Jobs for R-users](#)
- [Statistics of Israel](#)
- [SAS blogs](#)

Using apply, sapply, lapply in R

December 18, 2012

By [Pete](#)

Like Share  77

(This article was first published on [Shifting sands](#), and kindly contributed to [R-bloggers](#))

This is an introductory post about using apply, sapply and lapply, best suited for people relatively new to R or unfamiliar with these functions. There is a part 2 coming that will look at [density plots with ggplot](#), but first I thought I would go on a tangent to give some examples of the apply family, as they come up a lot working with R.

I have been comparing three methods on a data set. A sample from the data set was generated, and three different methods were applied to that subset. I wanted to see how their results differed from one another.

I would run my test harness which returned a matrix. The columns values were the metric used for evaluation of each method, and the rows were the results for a given subset. We have three columns, one for each method, and lets say 30 rows, representing 30 different subsets that the three methods were applied to.

It looked a bit like this

```
      method1 method2 method3
[1,] 0.05517714 0.014054038 0.017260447
[2,] 0.08367678 0.003570883 0.004289079
[3,] 0.05274706 0.028629661 0.071323030
[4,] 0.06769936 0.048446559 0.057432519
[5,] 0.06875188 0.019782518 0.080564474
[6,] 0.04913779 0.100062929 0.102208706
```

We can simulate this data using `rnorm`, to create three sets of observations. The first has mean 0, second mean of 2, third of mean of 5, and with 30 rows.

```
m <- matrix(data=cbind(rnorm(30, 0), rnorm(30, 2), rnorm(30, 5)), nrow=30,
ncol=3)
```

Apply

When do we use apply? When we have some structured blob of data that we wish to perform operations on. Here structured means in some form of matrix. The operations may be informational, or perhaps transforming,

subsetting, whatever to the data.

As a commenter pointed out, if you are using a data frame the data types must all be the same otherwise they will be subjected to type conversion. This may or may not be what you want, if the data frame has string/character data as well as numeric data, the numeric data will be converted to strings/characters and numerical operations will probably not give what you expected.

Needless to say such circumstances arise quite frequently when working in R, so spending some time getting familiar with `apply` can be a great boon to our productivity.

Which actual `apply` function and which specific incantation is required depends on your data, the function you wish to use, and what you want the end result to look like. Hopefully the right choice should be a bit clearer by the end of these examples.

First I want to make sure I created that matrix correctly, three columns each with a mean 0, 2 and 5 respectively. We can use `apply` and the base `mean` function to check this.

We tell `apply` to traverse row wise or column wise by the second argument. In this case we expect to get three numbers at the end, the mean value for each column, so tell `apply` to work along columns by passing 2 as the second argument. But let's do it wrong for the point of illustration:

```
apply(m, 1, mean)
# [1] 2.408150 2.709325 1.718529 0.822519 2.693614 2.259044 1.849530 2.544685 2.957950
2.219874
#[11] 2.582011 2.471938 2.015625 2.101832 2.189781 2.319142 2.504821 2.203066 2.280550
2.401297
#[21] 2.312254 1.833903 1.900122 2.427002 2.426869 1.890895 2.515842 2.363085 3.049760
2.027570
```

Passing a 1 in the second argument, we get 30 values back, giving the mean of each row. Not the three numbers we were expecting, try again.

```
apply(m, 2, mean)
#[1] -0.02664418 1.95812458 4.86857792
```

Great. We can see the mean of each column is roughly 0, 2, and 5 as we expected.

Our own functions

Let's say I see that negative number and realise I wanted to only look at positive values. Let's see how many negative numbers each column has, using `apply` again:

```
apply(m, 2, function(x) length(x[x<0]))
#[1] 14 1 0
```

So 14 negative values in column one, 1 negative value in column two, and none in column three. More or less what we would expect for three normal distributions with the given means and sd of 1.

Here we have used a simple function we defined in the call to `apply`, rather than some built in function. Note we did not specify a return value for our function. R will magically return the last evaluated value. The actual function is using subsetting to extract all the elements in `x` that are less than 0, and then counting how many are left are using `length`.

The function takes one argument, which I have arbitrarily called `x`. In this case `x` will be a single column of the matrix. Is it a 1 column matrix or a just a vector? Let's have a look:

```
apply(m, 2, function(x) is.matrix(x))
#[1] FALSE FALSE FALSE
```

Not a matrix. Here the function definition is not required, we could instead just pass the `is.matrix` function, as it only takes one argument and has already been wrapped up in a function for us. Let's check they are vectors as we might expect.

```
apply(m, 2, is.vector)
#[1] TRUE TRUE TRUE
```

Why then did we need to wrap up our `length` function? When we want to define our own handling function for `apply`, we must at a minimum give a name to the incoming data, so we can use it in our function.

```
apply(m, 2, length(x[x<0]))
#Error in match.fun(FUN) : object 'x' not found
```

We are referring to some value `x` in the function, but R does not know where that is and so gives us an error. There are other forces at play here,

but for simplicity just remember to wrap any code up in a function. For example, let's look at the mean value of only the positive values:

```
apply(m, 2, function(x) mean(x[x>0]))
#[1] 0.4466368 2.0415736 4.8685779
```

Using sapply and lapply

These two functions work in a similar way, traversing over a set of data like a list or vector, and calling the specified function for each item.

Sometimes we require traversal of our data in a less than linear way. Say we wanted to compare the current observation with the value 5 periods before it. Use can probably use `rollapply` for this (via `quantmod`), but a quick and dirty way is to run `sapply` or `lapply` passing a set of index values.

Here we will use `sapply`, which works on a list or vector of data.

```
sapply(1:3, function(x) x^2)
#[1] 1 4 9
```

`lapply` is very similar, however it will return a list rather than a vector:

```
lapply(1:3, function(x) x^2)
#[[1]]
#[1] 1
#
#[[2]]
#[1] 4
#
#[[3]]
#[1] 9
```

Passing `simplify=FALSE` to `sapply` will also give you a list:

```
sapply(1:3, function(x) x^2, simplify=F)
#[[1]]
#[1] 1
#
#[[2]]
#[1] 4
#
#[[3]]
#[1] 9
```

And you can use `unlist` with `lapply` to get a vector.

```
unlist(lapply(1:3, function(x) x^2))
#[1] 1 4 9
```

However the behaviour is not as clean when things have names, so best to use `sapply` or `lapply` as makes sense for your data and what you want to receive back. If you want a list returned, use `lapply`. If you want a vector, use `sapply`.

Dirty Deeds

Anyway, a cheap trick is to pass `sapply` a vector of indexes and write your function making some assumptions about the structure of the underlying data. Let's look at our mean example again:

```
sapply(1:3, function(x) mean(m[,x]))
[1] -0.02664418 1.95812458 4.86857792
```

We pass the column indexes (1,2,3) to our function, which assumes some variable `m` has our data. Fine for quickies but not very nice, and will likely turn into a maintainability bomb down the line.

We can neaten things up a bit by passing our data in an argument to our function, and using the ... special argument which all the apply functions have for passing extra arguments:

```
sapply(1:3, function(x, y) mean(y[,x]), y=m)
#[1] -0.02664418 1.95812458 4.86857792
```

This time, our function has 2 arguments, `x` and `y`. The `x` variable will be as it was before, whatever `sapply` is currently going through. The `y` variable we will pass using the optional arguments to `sapply`.

In this case we have passed in `m`, explicitly naming the `y` argument in the `sapply` call. Not strictly necessary but it makes for easier to read & maintain code. The `y` value will be the same for each call `sapply` makes to our function.

I don't really recommend passing the index arguments like this, it is error prone and can be quite confusing to others reading your code.

I hope you found these examples helpful. Please check out part 2 where we create a density plot of the values in our matrix.

Related

Comments: 9 A brief introduction to "apply" in R In "R. bb ggs" "	Comments: 12 Quick guide to parallel R with new In "R. bb ggs" "	Add a Comment Apply Yourself! In "R. bb ggs" "
--	---	--

77

Like

Share

To leave a comment for the author, please follow the link and comment on his blog:

[Shifting sands.](#)

R-bloggers.com offers [daily e-mail updates](#) about R news and [tutorials](#) on topics such as: visualization ([ggplot2](#), [Boxplots](#), [maps](#), [animation](#)), programming ([RStudio](#), [Sweave](#), [LaTeX](#), [SQL](#), [Eclipse](#), [git](#), [hadoop](#), [Web Scraping](#)) statistics ([regression](#), [PCA](#), [time series](#), [trading](#)) and more...

If you got this far, why not **subscribe for updates** from the site?

Choose your flavor: [e-mail](#), [twitter](#), [RSS](#), or [facebook](#)...

Like Share

77

Comments are closed.

Top 3 Posts from the past 2 days

- [Scatterplots](#)
- [In-depth introduction to machine learning in 15 hours of expert videos](#)
- [Installing R packages](#)

Search & Hit Enter

Top 9 articles of the week

1. [In-depth introduction to machine learning in 15 hours of expert videos](#)
2. [Installing R packages](#)
3. [Scatterplots](#)
4. [Using apply, sapply, lapply in R](#)
5. [Turning your R \(or Python\) models into APIs](#)
6. [Basics of Histograms](#)
7. [Microsoft Launches Its First Free Online R Course on edX](#)
8. [Read Excel files from R](#)
9. [Adding a legend to a plot](#)

Sponsors



Highland Statistics Ltd

Zero Inflated Models & GLMM

Beginner's Guide to GAM

Beginner's Guide to GLM & GLMM

Beginner's Guide to GAMM



R training

R consulting

QUANTIDE
knowledge from data

R Studio
open source & enterprise ready
professional software for R

REVOLUTION
ANALYTICS

R for the Enterprise

www.revolutionanalytics.com

Werden Sie zum Expe[R]ten mit der
R-Akademie von



Beratung | Software
Training | Lösungen



plotly online R graphing

[Plotly: collaborative, publication-quality graphing](https://plot.ly)

STATISTICS
VIEWS

Bringing Statistics Together



NYC DATA SCIENCE
ACADEMY

Sep 21 - Dec 11 | FULL TIME PROGRAM

12 - WEEK DATA SCIENCE BOOTCAMP

Hands-on R, Python & Hadoop Training

Mentorship from Top Data Scientists

Job Placement at Our 300+ Hiring Firms

Scholarship & Financial Aid Available

DEADLINE FOR APPLICATION: August 21st



DataCamp
Learn R Interactively



#ODSC

SAN FRANCISCO

NOV. 14TH - 15TH

www.opendatascicon.com

LEARN MORE

Save **25%** on
R Books



Use
Promo
Code
CZP40

Plus Free
Shipping

**Data Analysis
Modeling**
Cloud Solution

dotplot

Free Sign Up!



STATWORX

Consulting
Schulung
Data Mining

Mehr erfahren



Try the **FASTEST ML**
for **R**

Click for a Free Trial



Become a
Certified Data Scientist

ENROLL NOW

simpl|learn



EARN YOUR MASTER'S IN
DATA SCIENCE **online.**

Berkeley
UNIVERSITY OF CALIFORNIA

LEARN MORE



Search & Hit Enter

[Full list of contributing R-bloggers](#)

[R-bloggers](#) was founded by [Tal Galili](#), with gratitude to the [R](#) community.

Is powered by [WordPress](#) using a [bavotasan.com](#) design.

Copyright © 2015 [R-bloggers](#). All Rights Reserved. [Terms and Conditions](#) for this website