



UNIVERSIDAD DE VALLADOLID

ESCUELA TÉCNICA SUPERIOR DE INGENIEROS DE TELECOMUNICACIÓN

TRABAJO FIN DE GRADO

GRADO EN INGENIERÍA DE TECNOLOGÍAS DE TELECOMUNICACIÓN

Estación meteorológica con Raspberry Pi Pico W

Autor: Mario Acevedo Eustaquio

Tutores: Jesús M. Hernández Mangas
Iván Santos Tejido

21 de julio de 2025

TÍTULO:	Estación meteorológica con Raspberry Pi Pico W
AUTOR:	Mario Acevedo Eustaquio
TUTORES:	Jesús M. Hernández Mangas e Iván Santos Tejido
DEPARTAMENTO:	Departamento de Electrónica

TRIBUNAL

PRESIDENTE:	Jesús M. Hernández Mangas
SECRETARIO:	Iván Santos Tejido
VOCAL:	Lourdes Pelaz Montes
SUPLENTE:	Jesús Arias Álvarez
SUPLENTE:	María Aboy Cebrián

FECHA:	21 de julio de 2025
CALIFICACIÓN:	

Resumen del proyecto

Este proyecto consiste en el diseño y construcción de una estación meteorológica basada en una Raspberry Pi Pico W, que es capaz de medir diversas variables ambientales como temperatura, presión, humedad, índice UV, precipitación, velocidad y dirección del viento. Estos datos se envían mediante el protocolo MQTT a una Raspberry Pi que actúa como servidor, con el objetivo de que luego sean procesados, almacenados y visualizados. La estación incluye tanto el diseño de hardware (PCB, sensores, carcasa 3D) como el desarrollo del software necesario para la captura y envío de los datos.

Palabra clave

Raspberry Pi Pico W, estación meteorológica, sensores, MQTT, Arduino.

Abstract

This project involves the design and construction of a weather station based on a Raspberry Pi Pico W, capable of measuring various environmental variables such as temperature, pressure, humidity, UV index, precipitation, wind speed, and wind direction. The collected data is sent via the MQTT protocol to a Raspberry Pi acting as a server,

with the goal of later being processed, stored, and visualized. The station includes both the hardware design (PCB, sensors, 3D-printed enclosure) and the development of the software required for data acquisition and transmission.

Keywords

Raspberry Pi Pico W, weather station, sensors, MQTT, Arduino.

Agradecimientos

A mis padres y mi hermana Sara por ser un apoyo fundamental durante todos estos años y enseñarme las cosas realmente importantes de la vida.

A mis tutores por toda la ayuda que me han aportado durante todo el proyecto y el interés que me han contagiado en ir un poco más allá.

A todos mis amigos que me han ido acompañando durante estos años, siendo los mejores compañeros de camino que podría tener.

Y por último, a mi abuelo Luis, por haberme transmitido la curiosidad por entender cómo funcionan las cosas, montando y desmontando en su pequeña mesa de herramientas.

Índice general

Índice general	v
Índice de figuras	ix
Índice de tablas	xi
1. Introducción	1
1.1. Motivación	1
1.2. Objetivos	1
1.3. Estructura	1
1.4. Metodología	2
2. Desarrollo Hardware	3
2.1. Vista general de funcionamiento	3
2.2. Selección de componentes	4
2.2.1. Raspberry Pi Pico W	4
2.2.2. Sesnsor de temperatura, humedad y presión atmosférica - BME280	5
2.2.3. Sensor de radiación ultravioleta - GUVA-S12SD	8
2.2.4. Sensor de dirección del viento - Veleta ZTS-3000-FXJT-V05-360 . .	12
2.2.5. Anemómetro y pluviómetro - Sensor Hall SS49E	14
2.2.6. Pantalla LCD16D2	17
2.3. Captura esquemática	19
2.3.1. Pantalla LCD16D2	19
2.3.2. Sensor BME280	20
2.3.3. Botón de Reset	21
2.3.4. Veleta	21
2.3.5. Sensor UV GUVA-S12SD	22
2.3.6. Anemómetro (sensor Hall)	22
2.3.7. Pluviómetro (sensor Hall)	23
2.4. Diseño PCB	23
2.5. Diseño de impresión 3D	25
2.5.1. Modelos reutilizados de fuentes externas	25
2.5.2. Diseños 3D propios del proyecto	26
2.5.3. Programa y equipo de impresión 3D	27
2.6. Disposición final	28

3. Desarrollo Software	31
3.1. Plataforma de desarrollo	31
3.2. Descripción de componentes individuales	32
3.2.1. Sensor BME280	32
3.2.2. Sensor GUVA-S12SD	34
3.2.3. Veleta	35
3.2.4. Anemómetro	37
3.2.5. Pluviómetro	39
3.2.6. Pantalla LCD	41
3.3. Conectividad y transmisión de datos	43
3.3.1. Configuración de red WiFi	43
3.3.2. Formato del mensaje transmitido	43
3.3.3. Protocolo de comunicación: MQTT	44
3.3.4. Uso de Mosquitto	45
3.3.5. Funcionamiento general	45
3.4. Estructura del código principal	45
4. Presupuesto	47
5. Conclusiones	51
5.1. Resultado del proyecto	51
5.2. Líneas de futuro	51
Bibliografía	53
A. Hojas de datos	57
A.1. Hoja de datos Rasperry Pi Pico W	57
A.2. Hoja de datos sensor BME280	87
A.3. Hoja de datos sensor GUVA-S12SD	149
A.4. Hoja de datos veleta RS-FXJT-N01	153
A.5. Hoja de datos sensor SS49E	167
A.6. Hoja de datos pantalla LCD16D2	179
A.7. Hoja de datos potenciómetro 3296Y1102	207
B. Esquemático	211
C. PCB	213
C.1. Pistas de cobre de la cara superior	213
C.2. Pistas de cobre de la cara inferior	215
C.3. Serigrafía	217
C.4. Contorno de la PCB	219
D. Códigos Arduino IDE	221
D.1. Sensor BME280	221
D.2. Sensor GUVA-S12SD	223
D.3. Veleta	225
D.4. Anemómetro	227
D.5. Pluviómetro	229
D.6. Pantalla LCD	231

D.7. Código completo	233
E. Listado de materiales	241

Índice de figuras

2.1. Esquema del proyecto.	4
2.2. Raspberry Pi Pico W.	5
2.3. Sensor BME280 encapsulado.	7
2.4. Módulo BME280: frontal y trasero.	7
2.5. Sensor GUVVA-S12SD sin encapsulado de módulo.	9
2.6. Módulo GUVVA-S12SD: vista frontal y trasera.	9
2.7. Esquema de conexiones del módulo GUVVA-S12SD [25].	10
2.8. Esquema de conexiones del módulo GUVVA-S12SD modificado [25].	11
2.9. Curva que relaciona el voltaje de salida con el Índice UV.	12
2.10. Veleta ZTS-3000-FXJT-V05-360.	13
2.11. Módulo convertidor NDUB22TA.	13
2.12. Esquema conexiones veleta ZTS-3000-FXJT-V05-360.	14
2.13. Esquema funcionamiento anemómetro [14].	15
2.14. Esquema funcionamiento pluviómetro [29].	15
2.15. Variación del voltaje de salida del sensor SS49E en relación al campo mag- netico proporcionado [30].	16
2.16. Sensor SS49E.	17
2.17. Pantalla LCD16D2.	18
2.18. Potenciómetro 3296Y1102.	18
2.19. Esquema de conexiones de la Raspberry Pi Pico W.	19
2.20. Esquema de conexiones de la pantalla LCD16D2.	20
2.21. Esquema de conexiones del sensor BME280.	20
2.22. Esquema de conexiones del botón de Reset.	21
2.23. Esquema de conexiones de la veleta.	22
2.24. Esquema de conexiones del sensor GUVVA-S12SD.	22
2.25. Esquema de conexiones del sensor Hall del anemómetro.	23
2.26. Esquema de conexiones del sensor Hall del pluviómetro.	23
2.27. Diseño de la PCB.	24
2.28. PCB real.	24
2.29. Diseño 3D y montaje del anemómetro.	25
2.30. Diseño 3D y montaje del pluviómetro.	26
2.31. Soportes: veleta y anemómetro.	26
2.32. Primer diseño de la caja para el alojamiento de la PCB.	27
2.33. Diseo definitivo de la caja para el alojamiento de la PCB.	27
2.34. Esquema de la disposición final.	28
2.35. Estación meteorológica real.	29

Índice de tablas

2.1. Comparativa de sensores de temperatura, humedad y presión atmosférica en relación a su precio y proveedor en mayo de 2025.	6
2.2. Comparativa de sensores de radiación UV según proveedor y precio en mayo de 2025.	8
2.3. Comparativa entre índice UV proporcionado por la AEMET y la tensión medida en la primera etapa del sensor el 27 de junio de 2025.	11
2.4. Comparativa entre índice UV proporcionado por la AEMET y la tensión de salida del módulo medida en diferentes condiciones el 2 de julio de 2025.	12
4.1. Coste de materiales por unidad.	48
4.2. Coste de desarrollo del dispositivo.	48
4.3. Coste material por unidad en función del volumen	49
4.4. Coste total por unidad en función del volumen	49

Índice de listados

3.1. Importación de librerías.	32
3.2. Definición de pines I2C.	33
3.3. Inicialización del sensor BME280.	33
3.4. Lectura y visualización de datos del sensor.	33
3.5. Definición del pin de entrada y factor de conversión.	34
3.6. Inicialización del puerto serie.	34
3.7. Lectura del sensor UV y determinación de riesgo.	34
3.8. Definición del pin de lectura de la veleta.	36
3.9. Inicialización del puerto serie.	36
3.10. Lectura de dirección del viento y conversión a grados.	36
3.11. Definición de pines y variables del anemómetro.	37
3.12. Inicialización y configuración de interrupción.	37
3.13. Cálculo de velocidad del viento.	38
3.14. Rutina de interrupción del sensor Hall.	38
3.15. Definición de pines y variables del pluviómetro.	39
3.16. Inicialización del pluviómetro.	39
3.17. Cálculo de caudal de lluvia.	40
3.18. Rutina de interrupción del sensor Hall.	40
3.19. Variables de la pantalla LCD y definición de pines.	41
3.20. Inicialización de pantalla LCD y mensaje de bienvenida.	41
3.21. Visualización rotativa de datos.	42
3.22. Credenciales WiFi.	43
3.23. Configuración WiFi.	43
3.24. Publicación de los datos.	44
D.1. Código sensor BME280.	221
D.2. Código sensor GUVVA-S12SD.	223
D.3. Código veleta.	225
D.4. Código anemómetro.	227
D.5. Código pluviómetro.	229
D.6. Código pantalla LCD.	231
D.7. Código completo.	233

Capítulo 1

Introducción

1.1 Motivación

En la actualidad, el cambio climático es una realidad cada vez más presente en nuestra vida cotidiana. Por ello, la recopilación de datos meteorológicos se vuelve fundamental para su posterior análisis, con el objetivo de identificar zonas con condiciones extremas o anómalas —como las denominadas “islas de calor”— y, de este modo, facilitar la toma de decisiones y la implementación de medidas correctivas o preventivas.

1.2 Objetivos

El objetivo de este proyecto es la medición de diferentes variables meteorológicas —como la temperatura, la humedad, la presión atmosférica, la presión, el índice UV y la velocidad y dirección del viento— mediante una serie de sensores conectados a una Raspberry Pi Pico W, programada a través del entorno de desarrollo Arduino IDE.

Una vez recopilados y procesados localmente, los datos serán enviados a un servidor remoto mediante el protocolo MQTT, donde podrán ser almacenados, analizados y visualizados.

El proyecto contempla tanto el diseño del hardware de la estación meteorológica como el desarrollo del software necesario para la adquisición, procesamiento y transmisión de los datos.

Cabe destacar que este proyecto se implementa con otro, que desarrolla un sistema para la recepción, almacenamiento y visualización de datos meteorológicos en tiempo real. Procesa la información automáticamente y queda registrada con marcas temporales, permitiendo su consulta desde un panel gráfico accesible a través de la red local. Además, el sistema puede ser accedido de forma remota, lo que facilita su consulta desde ubicaciones externas. Está diseñado para ser robusto, seguro y fácilmente replicable en otros entornos.

1.3 Estructura

Este trabajo está organizado en varios capítulos que abordan de forma progresiva el desarrollo del proyecto. En primer lugar, se presenta la introducción, donde se detallan la motivación, los objetivos y la metodología empleada.

A continuación, el capítulo 2 se centra en el desarrollo del hardware, describiendo el análisis para la selección de componentes, esquemas eléctricos realizados, diseño de la PCB e impresiones 3D.

El capítulo 3 aborda el desarrollo del software, explicando la plataforma de programación, la implementación del código para la lectura de sensores, el tratamiento de datos y su transmisión mediante MQTT.

Posteriormente, el capítulo 4 incluye un presupuesto detallado, y finalmente, el capítulo 5 recoge las conclusiones y las posibles líneas futuras del proyecto.

1.4 Metodología

La metodología empleada en este proyecto se basa en un enfoque iterativo y por fases, que permite validar cada componente antes de integrar el sistema completo.

En primer lugar, se llevó a cabo una fase de análisis con el objetivo de identificar los requerimientos de la estación meteorológica y definir las variables climáticas que se deseaban medir. A partir de esta información, se realizó un estudio comparativo de distintos sensores disponibles en el mercado, evaluando su relación calidad-precio y su adecuación a las necesidades del proyecto. Asimismo, se analizó la viabilidad de fabricar algunos componentes en lugar de adquirirlos, teniendo en cuenta tanto los recursos disponibles como la complejidad de la implementación.

Posteriormente, se procedió a la prueba individual de cada sensor para verificar su correcto funcionamiento. Esta etapa se llevó a cabo en paralelo con el desarrollo del hardware, que incluyó el diseño de la placa PCB y la fabricación de soportes y carcasas mediante impresión 3D.

Una vez completado el hardware y validados todos los sensores de forma independiente, se integraron los diferentes códigos en un único programa, al cual se añadió la funcionalidad de conexión mediante el protocolo MQTT para el envío de los datos a un servidor remoto.

Finalmente, se elaboró un presupuesto detallado del proyecto y se extrajeron las conclusiones finales en base a los resultados obtenidos y al funcionamiento general del sistema.

Capítulo 2

Desarrollo Hardware

Este capítulo describe el diseño e implementación del sistema físico del proyecto. Se comienza con una vista general del funcionamiento, donde se explica cómo funciona el sistema para la comprensión de las conexiones de los sensores.

En la sección de selección de componentes, se justifica el uso de los sensores empleados y el análisis realizado para ello.

El capítulo continúa con el diseño y fabricación de las partes impresas en 3D.

A continuación, se presentan los esquemáticos eléctricos, donde se detallan las conexiones entre los sensores y el microcontrolador.

Finalmente, se explica el diseño de la placa PCB, incluyendo aspectos clave como el posicionamiento de componentes, rutado de pistas, planos de masa y diseño de la serigrafía.

2.1 Vista general de funcionamiento

El sistema está compuesto por cinco sensores encargados de medir diferentes variables ambientales: temperatura, humedad, presión atmosférica, índice UV, precipitación y velocidad y dirección del viento.

Además de los sensores, el sistema cuenta con una Raspberry Pi Pico W, que actúa como microcontrolador. Esta se encarga tanto de alimentar los sensores como de recibir y procesar los datos obtenidos por ellos, para su posterior envío al servidor del sistema, encargado del almacenamiento y procesamiento de estos datos finales.

Por último, se incluyen otros elementos complementarios: una pantalla LCD para visualizar los datos directamente en la estación, un potenciómetro para ajustar el brillo de la pantalla, un conversor de voltaje para alimentar la veleta, y un botón de reinicio para reconfigurar la Raspberry Pi Pico W cuando sea necesario.

La figura 2.1 muestra un esquema del funcionamiento general del sistema.




Figura 2.1: Esquema del proyecto.

2.2 Selección de componentes

La estación meteorológica, como se ha visto en el esquema anterior, funciona con un microcontrolador al cual se conectan todos los sensores y este procesa los datos enviados por los sensores para, a su vez, enviarlos a través de MQTT a un servidor. Este microcontrolador es la Raspberry Pi Pico W, una buena opción para lo que se quería lograr, ya que esta tiene alimentación relativamente baja, 26 pines GPIO (entrada/salida digital), varios pines convertidores de analógico a digital y conectividad WiFi para la integración de MQTT.

Para la selección de los sensores se realizó un estudio comparativo con el objetivo de identificar los más adecuados para las mediciones requeridas. En dicho análisis se evaluaron aspectos como la calidad, el precio, la cobertura de necesidades específicas y la disponibilidad en distintos proveedores.

Por último, aparte de la Raspberry y los sensores, la estación meteorológica cuenta con una pantalla LCD para la visualización en tiempo real de las mediciones recogidas.

2.2.1. Raspberry Pi Pico W

El elemento principal de la estación es una Raspberry Pi Pico W [11], una placa de desarrollo de bajo coste basada en el microcontrolador RP2040, desarrollada por la Fundación Raspberry Pi. A diferencia del modelo original (Pico), esta versión incorpora conectividad inalámbrica Wi-Fi, lo que permite su uso en aplicaciones relacionadas con el Internet de las Cosas (IoT), sensores remotos y sistemas conectados a la red.




Figura 2.2: Raspberry Pi Pico W.

Se puede consultar su hoja de datos y su diagrama de pines en el Anexo A.1. Entre sus características principales se encuentran:

- Microcontrolador RP2040 de doble núcleo ARM Cortex-M0+ a 133 MHz.
- 264 KB de memoria RAM.
- 2 MB de memoria flash interna.
- Conectividad Wi-Fi 802.11n integrada, imprescindible para la conexión con el protocolo MQTT.
- 26 pines GPIO con soporte para I2C, SPI, UART, PWM y entradas analógicas (ADC), necesarios para la interacción con los sensores.
- Alimentación entre 1.8 V y 5.5 V mediante USB o pin VIN.
- Programación en C/C++ o MicroPython.

Gracias a su bajo consumo (alrededor de 100–150 mW en reposo), tamaño compacto y capacidad de conexión inalámbrica, es una opción adecuada para el proyecto que se ha desarrollado.

2.2.2. Sesnsor de temperatura, humedad y presión atmosférica - BME280

En el análisis de las mediciones que se deseaban realizar con este proyecto, se concluyó que era necesario medir, entre otras variables, la temperatura, la humedad y la presión atmosférica. Durante este estudio, se identificó que existen sensores en el mercado capaces de medir simultáneamente estas tres magnitudes.

Como primer paso, se llevó a cabo un análisis comparativo de precios y proveedores, cuyos resultados se recogen en la siguiente tabla:

Sensor	Distribuidor	Precio (€)
BME280	Aliexpress	0.85
	Amazon	10.34
BME680	Aliexpress	5.99
	Amazon	9.99
DHT22	Aliexpress	0.71
	Amazon, Farnell, DigiKey	9.99

Tabla 2.1: Comparativa de sensores de temperatura, humedad y presión atmosférica en relación a su precio y proveedor en mayo de 2025.

Además de analizar precios y tiempos de llegadas de los diferentes proveedores, también se hizo una investigación sobre las diferentes funcionalidades que ofrece cada sensor.

El BME280 es un sensor que permite medir simultáneamente temperatura, humedad y presión atmosférica [2]. Ofrece buena precisión, bajo consumo de energía y tamaño compacto, lo que lo hace ideal para sistemas embebidos. Además, cuenta con una amplia documentación y soporte en librerías, lo que facilita su integración en proyectos. Su principal desventaja es que no incluye medición de calidad del aire, a diferencia de modelos más avanzados. En cuanto al precio, puede encontrarse a bajo coste en distribuidores como AliExpress, aunque en otros como Amazon su precio es considerablemente mayor.

El BME680 es una evolución del BME280 [3]. Añade la capacidad de medir gases (como compuestos orgánicos volátiles), lo que permite evaluar la calidad del aire además de las tres variables anteriores. Esta mejora lo convierte en un sensor muy completo para proyectos medioambientales. Sin embargo, su precio es más elevado, y la medición de gases requiere una calibración más cuidadosa y una implementación algo más compleja. Aun así, mantiene las ventajas del BME280 en cuanto a tamaño y consumo.

Por otro lado, el DHT22 es una alternativa muy económica que permite medir temperatura y humedad, pero no mide presión atmosférica [4]. Aunque es fácil de utilizar y tiene un amplio rango de medición, su precisión y estabilidad son inferiores a las de los sensores BME. Además, presenta una menor durabilidad en condiciones ambientales adversas y una respuesta más lenta.

Tras el análisis, se concluyó que la mejor opción para este proyecto es el **BME280**, ya que ofrece un equilibrio óptimo entre funcionalidad, precisión, facilidad de integración y coste. Si bien el BME680 proporciona datos más completos, en este caso su complejidad y coste adicional no se consideran justificados, aunque se podría tener en cuenta para futuras mejoras de la estación. Por el contrario, el DHT22 quedó descartado por no cumplir con todos los requisitos de medición definidos.

El sensor BME280 y el módulo integrado

El sensor BME280 es un dispositivo que integra en un solo chip tres sensores: de presión atmosférica, temperatura y humedad relativa. Está basado en tecnología piezo-resistiva desarrollada por BOSCH, que garantiza alta precisión, robustez electromagnética (EMC) y estabilidad a largo plazo. El sensor puede comunicarse con un microcontrolador a través de interfaces I2C o SPI, facilitando su integración en sistemas embebidos.

A continuación se muestra una imagen del sensor BME280 en su encapsulado original:



Figura 2.3: Sensor BME280 encapsulado.

Para más detalles técnicos, se puede consultar su hoja de datos en el Anexo A.2 .

Generalmente, el sensor viene integrado en un módulo que incluye componentes adicionales para facilitar su uso, tales como reguladores de voltaje, filtros y conectores para la interfaz de comunicación. Este módulo cuenta con un tamaño compacto y permite su conexión directa a placas de desarrollo.

A continuación se muestran imágenes del módulo BME280 adquirido [5] por su cara frontal y trasera:



Figura 2.4: Módulo BME280: frontal y trasero.

Especificaciones técnicas del módulo BME280

- Voltaje de operación: 1.71 V a 3.6 V.
- Interfaz de comunicación: I2C o SPI (1.2 V a 3.6 V).
- Rango de presión: 300 a 1100 hPa (0.3 - 1.1 bar).
- Resolución de presión: 0.16 Pa.
- Precisión absoluta de presión: ± 1 hPa (± 0.001 bar).

- Rango de temperatura: -40°C a 85°C.
- Resolución de temperatura: 0.01°C.
- Precisión de temperatura: $\pm 1^\circ\text{C}$.
- Rango de humedad relativa: 0-100 % RH.
- Precisión de humedad relativa: $\pm 3\%$ RH.
- Rango de altura medible: 0 - 9100 metros.
- Ultra bajo consumo energético.
- Completamente calibrado de fábrica.
- Frecuencia máxima de muestreo: 157 Hz.

Este módulo es ampliamente utilizado en aplicaciones de monitoreo ambiental, sistemas de domótica, drones para cálculo de altitud, Internet de las Cosas (IoT), y dispositivos de salud y fitness, gracias a su precisión y bajo consumo.

2.2.3. Sensor de radiación ultravioleta - GUVA-S12SD

Durante la planificación del sistema de sensado, se consideró la necesidad de medir la radiación ultravioleta (UV), dado su impacto en la salud y su utilidad para aplicaciones de monitoreo ambiental y meteorología urbana. Para ello, se llevó a cabo una comparación entre distintos sensores de radiación UV disponibles en el mercado.

Sensor	Distribuidor	Precio (€)
GUVA-S12SD	Aliexpress	1.90
	Amazon	9.80
	Adafruit	6.50
SI1145	Adafruit	9.95
UVM-30A	Aliexpress	6.79
	Arduiner	13.95
	Amazon	18.99
ML8511	Aliexpress	11.19
	Amazon	29.00

Tabla 2.2: Comparativa de sensores de radiación UV según proveedor y precio en mayo de 2025.

Además del precio, se evaluaron aspectos técnicos como rango espectral, facilidad de integración y disponibilidad de documentación. Entre las opciones analizadas, el sensor GUVA-S12SD destaca por su bajo coste, su bajo consumo energético y su buena sensibilidad dentro del rango UV-A y UV-B. Este sensor ofrece una salida analógica que varía en función de la intensidad de la radiación UV incidente, lo que lo hace fácilmente integrable con microcontroladores mediante un conversor analógico-digital (ADC).

En comparación, sensores como el SI1145 o el ML8511 ofrecen interfaces digitales o mayor precisión, pero a costa de una mayor complejidad y precio. El UVM-30A, por su parte, tiene un rango de operación similar al GUV A-S12SD, pero presenta menor linealidad y una mayor variabilidad entre unidades. En función de estos factores, el **GUVA-S12SD** se consideró la opción más adecuada para el proyecto, al ofrecer una buena relación coste/prestaciones y una integración sencilla.

El sensor GUV A-S12SD y el módulo integrado

El sensor GUV A-S12SD detecta radiación UV en el rango de longitud de onda entre 240 y 370 nm, cubriendo los espectros UV-B y UV-A. Su salida es una corriente eléctrica proporcional a la intensidad de la radiación recibida, la cual puede ser amplificada y convertida a un voltaje para su lectura.



Figura 2.5: Sensor GUV A-S12SD sin encapsulado de módulo.

Para más detalles técnicos, se puede consultar su hoja de datos en el Anexo A.3.

Generalmente, este sensor se encuentra integrado en un módulo que incorpora un amplificador operacional doble tipo LM358, encargado de transformar la corriente generada por el fotodiodo en una señal de voltaje. Esta señal es posteriormente amplificada.

A continuación se muestran imágenes del módulo GUV A-S12SD por su cara frontal y trasera:



Figura 2.6: Módulo GUV A-S12SD: vista frontal y trasera.

Especificaciones técnicas del módulo GUV A-S12SD

- Voltaje de alimentación: 2.7 V a 5.5 V DC.
- Longitud de onda detectada: 240 a 370 nm.
- Salida analógica proporcional a intensidad UV.
- Bajo consumo de energía.
- Dimensiones: 28 mm x 11 mm.
- Peso: 2 gramos.

Este módulo es ideal para proyectos de monitoreo ambiental, cuidado de la salud (protección solar), aplicaciones meteorológicas y estaciones de medición urbana, gracias a su simplicidad, fiabilidad y bajo coste. Su esquema eléctrico se muestra en la figura 2.7.

La primera etapa del circuito amplificador produce una señal de salida cuyo voltaje es proporcional a la fotocorriente del sensor, multiplicada por un factor de 43. Por ejemplo, si la corriente generada es de $0,1 \mu\text{A}$ (lo que representa aproximadamente $0,09 \text{ mW/cm}^2$ de intensidad UV, o 3.84 UVI según la hoja de especificaciones del fabricante), la salida será de 4,3 V.

Esta señal pasa luego a una segunda etapa de amplificación, con una ganancia adicional de 6,1. En este caso, el voltaje final a la salida sería de aproximadamente 26,23 V ($4,3 \text{ V} \times 6,1$).




Figura 2.7: Esquema de conexiones del módulo GUV A-S12SD [25].

Debido a que los valores obtenidos en la segunda etapa eran demasiado altos y no coincidían con los que deberían resultar según la hoja de especificaciones, se procedió a realizar un muestreo de los datos obtenidos cuando el sol impacta directamente sobre el sensor a lo largo de un día. Para ello, se recopilaron datos de salida de la primera etapa y se compararon con los valores proporcionados por la AEMET (Agencia Estatal de Meteorología).

Los datos obtenidos se organizaron en la tabla 2.3, que recoge la hora de medición, el índice UV registrado por la AEMET a esa hora y la tensión medida en la primera etapa del circuito:

Hora local (Valladolid)	Índice UV (AEMET)	Tensión 1ª etapa (V)
8:00	0	0.39
9:00	1	1.20
10:00	3	2.47
11:00	5	3.03
12:00	7	3.60
13:00	9	3.89
14:00	10	3.93
15:00	10	3.94
16:00	9	3.82
17:00	7	3.42
18:00	4	2.94
19:00	2	2.44
20:00	1	1.21
21:00	0	0.02

Tabla 2.3: Comparativa entre índice UV proporcionado por la AEMET y la tensión medida en la primera etapa del sensor el 27 de junio de 2025.

A partir de este análisis, se observó que, si el sensor era alimentado posteriormente con 3.3 V, al aplicar la ganancia de la segunda etapa, todos los valores resultaban saturados. Esto impedía determinar con precisión el valor real proporcionado por el sensor.

Ante esta situación, se estudiaron dos posibles soluciones. La primera consistía en eliminar la amplificación de la segunda etapa, retirando la resistencia de 1 k Ω y cortocircuitando la de 5,1 k Ω . La segunda opción consistía en sustituir la resistencia de 10 M Ω de la primera etapa por una de 1 M Ω , de forma que la ganancia pasara de 43 a 4.3.

Se concluyó que la segunda opción era la más adecuada, ya que, aunque se eliminara la segunda etapa, algunos valores seguían saturando cuando el sistema era alimentado con 3.3 V.




Figura 2.8: Esquema de conexiones del módulo GUVA-S12SD modificado [25].

Una vez realizada la modificación de la resistencia en la primera etapa, se procedió a efectuar mediciones de la señal de salida proporcionada por el módulo en función del índice UV recibido, considerando diferentes condiciones experimentales. Entre ellas, se incluyeron la exposición directa al sol, la presencia de un “filtro” producido por el metacrilato de la tapa de la caja, así como la posición del sensor en la propia caja.

Hora local	Hora solar	Índice UV (AEMET)	V directo	V tapa	V caja
9:47	7:24	1.69	0.88	0.71	0.41
10:32	8:09	3.14	1.16	0.92	0.72
11:29	9:06	5.24	1.58	1.29	1.09
12:30	10:07	7.42	1.78	1.45	1.20
13:31	11:08	8.97	1.91	1.54	1.33

Tabla 2.4: Comparativa entre índice UV proporcionado por la AEMET y la tensión de salida del módulo medida en diferentes condiciones el 2 de julio de 2025.

A partir de estos datos, fue posible determinar una curva de calibración que permite obtener el índice UV en función de la tensión de salida del módulo, y que se usó posteriormente en el software del proyecto.




Figura 2.9: Curva que relaciona el voltaje de salida con el Índice UV.

$$UVI = 7,6399 \cdot V_{\text{módulo}} - 1,9659 \quad \text{con } UVI \geq 0 \quad (2.1)$$

2.2.4. Sensor de dirección del viento - Veleta ZTS-3000-FXJT-V05-360

Para la medición de la dirección del viento, en una primera propuesta se planteó construir la veleta de forma manual, utilizando un potenciómetro junto con una brújula

para su calibración, o bien un sensor de ángulo como el módulo AS5600 [12]. Sin embargo, esta opción fue descartada, ya que presentaba una complejidad considerable y no parecía garantizar los objetivos planteados.

Por ello, se realizó una búsqueda de veletas ya construidas o completamente ensambladas, y se encontró la veleta **ZTS-3000-FXJT-V05-360** [13], la cual resultó ser una opción bastante económica que cumplía con los requisitos establecidos. La mayoría del resto de veletas disponibles en el mercado presentaban precios significativamente más elevados, por lo que fueron descartadas.



Figura 2.10: Veleta ZTS-3000-FXJT-V05-360.

Para comprender el funcionamiento de la veleta, se recurrió a la hoja de datos de otro modelo similar, el RS-FXJT-N01, dado que el modelo empleado no cuenta con una hoja de datos propia. Este modelo alternativo presentaba características similares y su hoja de datos está disponible en el Anexo A.4.

Sin embargo, al probar la veleta, se observó que su comportamiento difería considerablemente de lo que indicaba dicha hoja de datos. Esto llevó a realizar varias pruebas para entender mejor su funcionamiento real y detectar posibles inconvenientes. Durante estas pruebas, se identificó un problema no previsto en el momento de la compra: este modelo requiere una alimentación eléctrica entre 10 y 30 voltios, mientras que la Raspberry Pi Pico W solo puede suministrar un máximo de 5 voltios. Para resolver esta incompatibilidad, fue necesario adquirir un convertidor de tensión que eleva de 3.3 V a 10 V.

El módulo convertidor utilizado es el NDUB22TA, que recibe una tensión de entrada de 3.3 V y proporciona una salida estable de 10 V, permitiendo así alimentar correctamente la veleta y asegurar su correcto funcionamiento.




Figura 2.11: Módulo convertidor NDUB22TA.

Además de adaptar la tensión de entrada de la veleta, se elaboró un esquema para definir correctamente sus conexiones. Esto fue necesario debido a que la salida proporcionada por la veleta no es una señal de tensión, sino de corriente, que varía linealmente según el giro de la veleta (de 0 a 360°). Por esta razón, se añadió una resistencia de 270 Ω entre la salida del sensor y tierra (GND), con el objetivo de transformar la corriente de salida (0–9,5 mA) en una señal de voltaje compatible con la entrada analógica de la Raspberry Pi Pico W (0–2,58 V).




Figura 2.12: Esquema conexiones veleta ZTS-3000-FXJT-V05-360.

La conversión de corriente a voltaje se realiza aplicando la Ley de Ohm:

$$V = I \times R$$

Donde:

- V : tensión generada (voltios),
- I : corriente de salida del sensor (amperios),
- R : resistencia conectada (ohmios).

En este caso particular:

$$V = 9,5 \times 10^{-3} \text{ A} \times 270 \text{ } \Omega = 2,565 \text{ V}$$

Este voltaje es adecuado para ser leído directamente por el ADC de la Raspberry Pi Pico W, cuyo rango de entrada es de 0 a 3,3 V.

2.2.5. Anemómetro y pluviómetro - Sensor Hall SS49E

La medición de la velocidad del viento requiere el uso de un anemómetro. Para su construcción, se investigaron diversas alternativas, resaltando una basada en un sensor de efecto Hall y un imán. Se identificó la viabilidad de fabricar la estructura exterior del anemómetro mediante impresión 3D, gracias a la existencia de proyectos previos que proporcionan diseños de hardware adaptados para este método [19]. Estos diseños combinan piezas impresas en 3D con un sensor Hall y un imán para registrar las rotaciones del anemómetro, permitiendo así calcular la velocidad de giro y, por tanto, la velocidad del viento.




Figura 2.13: Esquema funcionamiento anemómetro [14].

Por otro lado, la precipitación se mide mediante un pluviómetro, un instrumento que, generalmente, consta de un embudo que canaliza el agua hacia un balancín. Este balancín bascula al recibir una cantidad determinada de agua, generando un conteo de los vuelcos, que permite calcular la cantidad de precipitación acumulada.




Figura 2.14: Esquema funcionamiento pluviómetro [29].

Al igual que con el anemómetro, existen proyectos que ofrecen diseños en 3D del pluviómetro, integrando también sensores de efecto Hall e imanes para el registro de los datos.

En ambos casos, existe la posibilidad de adquirir módulos comerciales ya fabricados, como el medidor de lluvia WH-SP-RG [31] para el caso del pluviómetro, o el anemómetro RS485 [32]. Sin embargo, en este proyecto se descartó esta opción, ya que estos dispositivos incrementan el coste total. Además, se consideró más apropiado optar por el diseño y la fabricación propia de los módulos, lo cual no solo reduce el presupuesto, sino que también permite una mayor comprensión del funcionamiento de cada componente.

El sensor de efecto Hall SS49E

El sensor de efecto Hall SS49E permite detectar campos magnéticos y su funcionamiento se basa en el efecto Hall, descubierto por Edwin Hall en 1879. Este fenómeno establece que, cuando una corriente eléctrica circula por un conductor o semiconductor y se aplica un campo magnético perpendicular a la dirección de la corriente, se genera una diferencia de potencial transversal (tensión Hall) en el material.

El SS49E es un sensor lineal que proporciona una salida analógica proporcional a la intensidad del campo magnético que detecta. Su comportamiento básico es el siguiente:

- En ausencia de campo magnético, el sensor entrega una señal de salida cercana a la mitad del voltaje de alimentación (por ejemplo, 2.5V si se alimenta con 5V).
- Si se acerca un imán con el polo norte hacia el sensor, el voltaje de salida aumenta.
- Si se acerca un imán con el polo sur, el voltaje de salida disminuye.




Figura 2.15: Variación del voltaje de salida del sensor SS49E en relación al campo magnético proporcionado [30].

En este proyecto, el sensor se utiliza como parte de un anemómetro. Para ello, se fija un imán en una parte giratoria del dispositivo. Cada vez que el imán pasa frente al sensor, se produce una variación en el campo magnético detectado, lo que genera un pulso eléctrico. Estos pulsos permiten contar las revoluciones del anemómetro y, con ello, calcular la velocidad del viento.

De manera similar, el pluviómetro funciona mediante un mecanismo de balancín que se inclina cada vez que se acumula una cierta cantidad de agua. Cada movimiento del balancín activa el sensor, generando también un pulso. Al contar estos pulsos, es posible determinar la cantidad total de precipitación.




Figura 2.16: Sensor SS49E.

La hoja de datos del sensor SS49E está disponible en el Anexo A.5.

2.2.6. Pantalla LCD16D2

La pantalla LCD (Liquid Crystal Display) es un dispositivo ampliamente utilizado para mostrar información en forma de caracteres, símbolos o gráficos sencillos. Su funcionamiento está controlado por un microcontrolador que gestiona el envío de instrucciones y datos. En este proyecto se utiliza un LCD de 16x2, lo que significa que dispone de dos filas con capacidad para mostrar hasta 16 caracteres cada una.

El funcionamiento de estos módulos se basa en el control de una matriz de píxeles organizada por caracteres, cuyo formato interno varía ligeramente según el fabricante. Son especialmente útiles para mostrar datos como temperaturas, lecturas de sensores, mensajes de estado o menús de usuario.

La pantalla LCD 16x2 cuenta con una serie de pines agrupados por funciones: alimentación (Vss a GND, Vdd a 5V y Vo para ajustar el contraste mediante un potenciómetro), control (RS para seleccionar entre instrucciones o datos, RW para elegir entre lectura o escritura —aunque normalmente se conecta a GND—, y E para habilitar la lectura del dato), y un bus de datos bidireccional (D0 a D7), que puede usarse en modo de 8 bits o en el más habitual modo de 4 bits utilizando solo D4 a D7. Además, este modelo incluye dos pines para la retroiluminación (ánodo y cátodo), que permiten controlar la luz de fondo de la pantalla. Se puede consultar la hoja de datos de la pantalla en el Anexo A.6.



Figura 2.17: Pantalla LCD16D2.

El potenciómetro 3296Y1102

Para el control del contraste de la pantalla se ha hecho uso de un potenciómetro 3296Y1102 de 2 k Ω .




Figura 2.18: Potenciómetro 3296Y1102.

El potenciómetro es un resistor variable ajustable que permite controlar la resistencia eléctrica de manera manual. Funciona mediante un sistema de tres terminales: dos terminales fijos conectados a los extremos de una pista resistiva y un terminal móvil (wiper) que se desplaza al girar el eje, variando así la resistencia entre el wiper y cada extremo. Su valor nominal es de 2 k Ω con una tolerancia estándar de $\pm 10\%$, y ofrece una resolución precisa gracias a su diseño multivuelta (25 vueltas nominales). Este modelo, de la serie 3296, está diseñado para aplicaciones industriales, soporta una tensión máxima de 300 V y una potencia de 0.5 W a 70 °C. Es ideal para ajustes finos en circuitos electrónicos, como divisores de tensión o calibración de sensores.

Para más información sobre el potenciómetro se puede consultar su hoja de datos en el Anexo A.7.

2.3 Captura esquemática

En una primera fase del diseño, se seleccionaron los símbolos de los componentes, extrayéndolos de la librería de SnapEDA. Sin embargo, algunos de ellos no se encontraban disponibles, por lo que fue necesario crearlos manualmente, asegurando una representación precisa de sus pines. Una vez definidos todos los símbolos, se procedió a realizar el esquema completo de conexiones.

Para el diseño del circuito de la estación meteorológica, se realizó un esquemático donde todos los sensores y módulos están conectados a una Raspberry Pi Pico W.




Figura 2.19: Esquema de conexiones de la Raspberry Pi Pico W.

A continuación, se describen las conexiones de cada uno de los componentes del circuito. También se dispone del esquemático completo en el Anexo B.

2.3.1. Pantalla LCD16D2

La pantalla LCD 1602A se conecta mediante una interfaz paralela de 4 bits. Sus conexiones son las siguientes:




Figura 2.20: Esquema de conexiones de la pantalla LCD16D2.

- **VSS, VDD, V0:** alimentación y control de contraste. El pin V0 está conectado a un potenciómetro para ajustar el contraste.
- **RS (GP1), E (GP0):** líneas de control conectadas a la Raspberry Pi Pico W.
- **D4–D7 (GP2–GP5):** líneas de datos.
- **A, K:** alimentación de retroiluminación mediante una resistencia limitadora (R4).

2.3.2. Sensor BME280

El sensor BME280 se comunica mediante el protocolo I2C. Sus conexiones son las siguientes:




Figura 2.21: Esquema de conexiones del sensor BME280.

- **VCC** a 3.3V.

- **GND** a masa.
- **SDA (GP6)** y **SCL (GP7)** conectados al bus I2C de la Raspberry Pi Pico W.

El sensor BME280 posee resistencias internas *pull-up* de 10 k Ω en SDA y SCL.

2.3.3. Botón de Reset

Un pulsador conectado al pin **RUN** de la Raspberry, utilizado para reiniciar el sistema. Dispone de una resistencia *pull-down* de 10 k Ω (R3) para evitar activaciones falsas.




Figura 2.22: Esquema de conexiones del botón de Reset.

2.3.4. Veleta

La veleta requiere una alimentación mínima de 10V para su correcto funcionamiento. Dado que la Raspberry Pi Pico W únicamente proporciona salidas de 3.3V o 5V, se incorpora un convertidor de voltaje que eleva dicha tensión hasta los 10V necesarios. Además, la veleta entrega una señal de salida en forma de tensión variable, por lo que se añade la resistencia R1 como parte del circuito de adaptación para obtener un voltaje compatible con la entrada analógica de la Raspberry. Esta señal, de tipo analógico, se conecta al pin ADC1 (GP27) del microcontrolador para su lectura y procesamiento.




Figura 2.23: Esquema de conexiones de la veleta.

2.3.5. Sensor UV GUVA-S12SD

La salida del sensor es analógica y se conecta al pin ADC2 (GP28) de la Raspberry Pi Pico W.




Figura 2.24: Esquema de conexiones del sensor GUVA-S12SD.

- Alimentado a 3.3V.
- La luz entra a través de una tapa con cristal transparente en la caja impresa en 3D.

2.3.6. Anemómetro (sensor Hall)

Este sensor entrega pulsos digitales proporcionales a la velocidad del viento.




Figura 2.25: Esquema de conexiones del sensor Hall del anemómetro.

- VCC a 3.3V.
- GND a masa.
- OUT a GP20 de la Raspberry.

2.3.7. Pluviómetro (sensor Hall)

Igual que el anemoemtro este sensor entrega pulsos digitales para calcular la precipitación.




Figura 2.26: Esquema de conexiones del sensor Hall del pluviómetro.

- VCC a 3.3V.
- GND a masa.
- OUT a GP21 de la Raspberry.

2.4 Diseño PCB

El diseño de la PCB, ha seguido un proceso muy parecido al del esquemático. En una primera fase se crearon todas las huellas de los componentes, importando de SnapEDA las huellas ya existentes y creando de cero las huellas que no existían.

Una vez creadas las huellas de los componentes, se procedió a su colocación sobre el área definida para la PCB, la cual tiene unas dimensiones de 10×10cm. Durante esta fase se tuvo en cuenta una serie de consideraciones funcionales y de diseño. Por un lado, el conector de alimentación de la Raspberry Pi Pico W debía situarse en uno de los laterales para facilitar el acceso al cable. De igual forma, las bornas destinadas a la conexión de la veleta, el anemómetro y el pluviómetro también se posicionaron en un lateral para simplificar el cableado hacia el exterior. Por otro lado, el botón de Reset se colocó próximo a la Raspberry para garantizar un acceso cómodo durante su uso.

Una vez posicionadas todas las huellas sobre la placa, se procedió al rutado de las conexiones entre los componentes. Para ello, se utilizó la herramienta de rutado automático que ofrece Proteus, la cual permite generar de forma rápida el trazado de las pistas. Tras este proceso automático, se realizaron ajustes manuales para corregir pequeños errores y optimizar el diseño, garantizando así la funcionalidad eléctrica y una disposición clara y ordenada del circuito.

Por último, se añadieron serigrafías informativas sobre la superficie de la PCB, como el título del proyecto, el nombre del autor y otros textos explicativos. También se realizaron varios agujeros mecánicos destinados a la fijación de la placa dentro de la carcasa, permitiendo así su correcta integración en el montaje final del sistema.

Con todo esto el diseño final de la PCB es el siguiente:




Figura 2.27: Diseño de la PCB.




Figura 2.28: PCB real.

Se adjuntan en el Anexo C, los enrutados tanto superior como inferior, la serigrafía y el contorno de la placa.

2.5 Diseño de impresión 3D

2.5.1. Modelos reutilizados de fuentes externas

Para la fabricación del anemómetro y el pluviómetro, se ha hecho uso de diseños ya existentes de fuentes externas [19].

Anemómetro

El anemómetro utilizado está formado por tres piezas impresas en 3D: el cuerpo inferior, el cuerpo superior y tres cazoletas.




Figura 2.29: Diseño 3D y montaje del anemómetro.

Las tres cazoletas se fijan a la parte superior del cuerpo mediante tres tornillos, uno por cada cazoleta. En esta misma parte se coloca un imán, que posteriormente pasa frente al sensor. La parte superior se une a la base inferior mediante una varilla que actúa como eje y un rozamiento que permite el giro, manteniéndose fijo a la base (que también estará fija). En esta base inferior se aloja el sensor de efecto Hall, colocado en el hueco previsto para ello. De este modo, al girar la parte superior impulsada por el viento, el imán pasa repetidamente frente al sensor, generando pulsos que permiten calcular las revoluciones por minuto (RPM) y, por tanto, estimar la velocidad del viento.

Pluviómetro

El pluviómetro empleado también está compuesto por tres piezas impresas en 3D: la caja exterior, el embudo superior y el balancín.




Figura 2.30: Diseño 3D y montaje del pluviómetro.

El embudo se encaja en la parte superior de la caja con una serie de varillas, perfiles y tuercas y dirige el agua hacia el balancín, que se encuentra alojado en el interior de la caja, situado con una varilla y una serie de tuercas. Este balancín bascula hacia un lado u otro cada vez que acumula una cantidad determinada de agua, vaciando uno de sus compartimentos y generando un pulso gracias a un imán fijado en él, que pasa frente a un sensor de efecto Hall instalado en un lateral de la caja. De esta forma, contando el número de pulsos generados por el movimiento del balancín, es posible calcular la cantidad de precipitación acumulada en un intervalo de tiempo.

2.5.2. Diseños 3D propios del proyecto

Para la instalación del anemómetro y la veleta en la estación final, se consideró oportuno diseñar un soporte individual para cada uno. Dichos soportes permiten la calibración mediante el uso de un nivelador de burbuja y tres tornillos dispuestos en forma de trípedo para facilitar el nivelado de los instrumentos.



Figura 2.31: Soportes: veleta y anemómetro.

Además de los soportes, también se consideró necesario el diseño de una caja para la disposición final de la PCB. Para su diseño, se tuvo en cuenta que debía ser una caja cerrada, pero no hermética, ya que era necesario permitir la entrada y salida de cables, así como la entrada de humedad y temperatura para su correcta medición. Asimismo, debía permitir el paso de luz para posibilitar la medición del índice UV.

En una primera fase del diseño, se realizó una caja con rejillas. Sin embargo, este diseño fue descartado tras su impresión, debido a la dificultad para retirar los soportes generados durante el proceso de impresión 3D en las zonas de las rejillas, además de que la altura de la caja resultó insuficiente para alojar adecuadamente la pantalla LCD.




Figura 2.32: Primer diseño de la caja para el alojamiento de la PCB.

En una segunda fase del diseño, se eliminaron las rejillas y se sustituyeron por pequeños huecos en forma de rombos (los cuales no requerían soportes durante la impresión 3D) y se aumentó la altura de la caja para permitir la correcta instalación de la pantalla LCD. También se diseñó una tapa que incorpora un metacrilato transparente, con el objetivo de permitir la entrada de luz necesaria para la medición del índice UV.




Figura 2.33: Diseo definitivo de la caja para el alojamiento de la PCB.

2.5.3. Programa y equipo de impresión 3D

Para el diseño 3D de los componentes se ha utilizado la herramienta en línea Tinkercad, una plataforma intuitiva basada en la unión y modificación de formas geométricas básicas. Esta herramienta permite realizar diseños de manera rápida y sencilla, lo cual resulta ideal para prototipos funcionales como los utilizados en este proyecto. Gracias a su interfaz amigable, fue posible modelar tanto los soportes como la caja de la PCB sin necesidad de conocimientos avanzados en diseño asistido por ordenador (CAD).

Una vez finalizado el diseño, se exportaron los modelos en formato .stl, estándar para impresión 3D. Posteriormente, estos archivos fueron procesados mediante el software Ulti-

Maker Cura, una aplicación que permite preparar y ajustar los parámetros de impresión, como la altura de capa, el relleno, la temperatura o la generación de soportes. Este paso fue esencial para adaptar correctamente los modelos a las características de la impresora utilizada y garantizar una impresión correcta.

La impresora empleada en este proyecto fue una Anycubic i3 Mega, presente en el laboratorio del departamento de Electricidad y Electrónica de la E.T.S.I.T., utilizando como material de impresión filamento PLA genérico. Este tipo de filamento fue elegido por su facilidad de uso, buena adherencia a la cama de impresión y propiedades adecuadas para componentes que no estarán sometidos a esfuerzos extremos y que estarán en ambientes exteriores.

2.6 Disposición final

La disposición final de los distintos componentes de la estación meteorológica se diseñó considerando criterios de funcionalidad, accesibilidad y eficiencia en la recogida de datos. Todo el conjunto está montado sobre una base de plancha de policarbonato de 40×40cm que actúa como soporte estructural.

La PCB, que contiene todos los elementos electrónicos del sistema, se encuentra alojada en el interior de una caja impresa en 3D. Esta caja cuenta con una tapa superior que incorpora una ventana de cristal transparente, permitiendo así la entrada de luz necesaria para el sensor de radiación UV.

Encima de la caja, se montó la veleta mediante un soporte calibrable, con el objetivo de garantizar su correcta exposición al viento y su funcionamiento sin interferencias. A la izquierda de la caja se situó el anemómetro, fijado mediante otro soporte calibrable que permite su nivelación precisa. En una de las esquinas de la base se posicionó el pluviómetro.

Para facilitar el montaje y la comprensión de la disposición, se elaboró un esquema ilustrativo de la posición relativa de todos los elementos.




Figura 2.34: Esquema de la disposición final.

A continuación, se muestra una imagen de la estación meteorológica en su versión final, completamente ensamblada.




Figura 2.35: Estación meteorológica real.

Capítulo 3

Desarrollo Software

Este capítulo describe la implementación del software que controla el funcionamiento de la estación meteorológica. Se abordan las herramientas utilizadas para el desarrollo, la estructura lógica del programa principal, la integración de los sensores y dispositivos periféricos, así como los mecanismos empleados para la conectividad y transmisión de datos hacia la red.

En primer lugar, en la plataforma de desarrollo, se detallan los entornos y lenguajes utilizados, como el IDE de Arduino, junto con las principales bibliotecas que permiten la comunicación con sensores, la visualización de datos y la conectividad de red mediante WiFi y protocolo MQTT.

Posteriormente, se presenta la estructura del código principal, organizada en funciones clave como **setup()** y **loop()**, además de rutinas específicas como **setupwifi()** para la conexión a Internet, **reconnect()** para mantener activa la comunicación con el servidor MQTT, e interrupciones que capturan eventos desde el anemómetro y el pluviómetro.

A continuación, se expone una descripción de los componentes individuales que conforman el sistema, incluyendo sensores ambientales, meteorológicos y elementos de salida como la pantalla LCD. Se detalla su conexión física, configuración de lectura y procesamiento de datos, así como los factores de calibración empleados.

Finalmente, en la sección de conectividad y transmisión de datos, se especifica la configuración de red, el formato de los mensajes en JSON, y la lógica de publicación periódica de datos a través del protocolo MQTT, utilizando un tópico identificado como `/teleco/estacion1`. Esto permite la integración del sistema en una arquitectura IoT para monitoreo remoto en tiempo real.

Cabe destacar que todo el código desarrollado se carga y ejecuta directamente en una Raspberry Pi Pico W, que actúa como unidad central de control. Esta placa microcontroladora se encarga tanto de la lectura de sensores como del procesamiento de los datos y su posterior envío mediante WiFi. Gracias a su bajo consumo, tamaño reducido y compatibilidad con el entorno Arduino, la Raspberry Pi Pico W constituye una solución eficiente y robusta para el control de la estación meteorológica.

3.1 Plataforma de desarrollo

El desarrollo del sistema se realizó utilizando la aplicación de software Arduino IDE, una plataforma que proporciona un entorno de programación eficiente, con acceso a bibliotecas especializadas que facilitan la interacción con sensores y módulos de comunicación.

El lenguaje de programación utilizado fue C++, debido a su eficiencia y compatibilidad con microcontroladores de recursos limitados.

Para la implementación del sistema, se emplearon las siguientes bibliotecas:

- **Wire.h**: para comunicación mediante el protocolo I2C, fundamental para la conexión con varios sensores como el BME280. Viene integrada con Arduino IDE.
- **Adafruit_Sensor.h**: interfaz estándar para sensores de Adafruit, utilizada como capa base en la obtención de datos físicos. Se puede encontrar en el administrador de librerías como Adafruit Unified Sensor by Adafruit.
- **Adafruit_BME280.h**: específica para el sensor ambiental BME280 (temperatura, humedad y presión). También se encuentra en el administrador de librerías como Adafruit BME280 Library by Adafruit.
- **LiquidCrystal.h**: permite controlar pantallas LCD en modo de 4 bits. Esta librería viene integrada por defecto con Arduino IDE.
- **WiFi.h**: utilizada para establecer conexión a redes WiFi con microcontroladores compatibles. Forma parte del paquete "Arduino Mbed OS RP2040 Boards", instalado para la configuración de la placa Raspberry Pi Pico W.
- **PubSubClient.h**: facilita la implementación del protocolo MQTT para la transmisión de datos a un servidor o broker. Se encuentra en el administrador de librerías como PubSubClient by Nick O'Leary.

```
1 #include <Wire.h>    //viene integrada con arduino IDE
2 #include <Adafruit_Sensor.h> //Adafruit Unified Sensor by Adafruit
3 #include <Adafruit_BME280.h> //Adafruit BME280 Library by Adafruit
4 #include <LiquidCrystal.h>    //viene integrada con arduino IDE
5 #include <WiFi.h>    //se instala desde board manager Arduino Mbed OS
   RP2040 Boards
6 #include <PubSubClient.h>    //PubSubClient by Nick O'Leary
```

Listing 3.1: Importación de librerías.

Estas herramientas y librerías conforman la base del entorno de desarrollo del sistema, facilitando una integración de hardware y una transmisión de datos eficiente a través de Internet.

3.2 Descripción de componentes individuales

Antes de desarrollar un código general que integrara el funcionamiento de todos los sensores, se elaboraron programas individuales para cada uno con el objetivo de verificar su correcto funcionamiento.

3.2.1. Sensor BME280

El siguiente código permite la lectura de los valores de temperatura, humedad relativa y presión atmosférica mediante el sensor BME280, conectado a una Raspberry Pi Pico W a través del bus I2C.

Las conexiones físicas entre el sensor y la Raspberry Pi Pico W son las siguientes: SDA al pin 11 (GPIO 8), SCL al pin 12 (GPIO 9), VCC y CSB al pin 36 (3.3V), y GND y SDO al pin 38 (GND). Para ellos se definen los pines I2C de la siguiente forma:

```
13 #define I2C_SDA 8 // GP8 - PIN 11
14 #define I2C_SCL 9 // GP9 - PIN 12
```

Listing 3.2: Definición de pines I2C.

En la función `setup()`, se configura el puerto serie para depuración, se establecen los pines personalizados para el bus I2C y se inicializa el sensor en la dirección `0x76`, que es la más común para este modelo. Si el sensor no se detecta correctamente, el programa se detiene:

```
18 void setup() {
19     Serial.begin(115200);
20     Wire.setSDA(I2C_SDA);
21     Wire.setSCL(I2C_SCL);
22     Wire.begin();
23
24     if (!bme.begin(0x76)) {
25         Serial.println("Error: No se encontr el BME280.");
26         while (1);
27     }
28
29     Serial.println("BME280 detectado correctamente.");
30 }
```

Listing 3.3: Inicialización del sensor BME280.

En la función `loop()`, que se ejecuta de forma continua, se realizan lecturas periódicas de temperatura, humedad y presión, y se imprimen por el monitor serie. La presión se convierte de Pascales a hectoPascales (dividiendo entre 100), que es la unidad estándar utilizada en meteorología. Además, se introduce una pausa de 2 segundos entre mediciones para facilitar la visualización de los datos.

```
32 void loop() {
33     Serial.print("Temperatura: ");
34     Serial.print(bme.readTemperature());
35     Serial.println(" C ");
36
37     Serial.print("Humedad: ");
38     Serial.print(bme.readHumidity());
39     Serial.println(" %");
40
41     Serial.print("Presi n: ");
42     Serial.print(bme.readPressure() / 100.0F);
43     Serial.println(" hPa");
44
45     Serial.println("_____");
46     delay(2000);
47 }
```

Listing 3.4: Lectura y visualización de datos del sensor.

Este código permite comprobar el correcto funcionamiento del sensor y obtener una lectura en tiempo real de las condiciones ambientales. La salida por el monitor serie es la siguiente:

```
BME280 detectado correctamente.
```

```
-----
Temperatura: 22.45 °C
Humedad: 47.30 %
Presión: 1013.85 hPa
-----
```

3.2.2. Sensor GUVVA-S12SD

Este código permite la medición del índice ultravioleta (UV) mediante el sensor GUVVA-S12SD, el cual proporciona una salida analógica proporcional a la intensidad de radiación UV. El sensor se conecta directamente a una entrada analógica (ADC) de la Raspberry Pi Pico W.

Las conexiones físicas entre el sensor y la Raspberry Pi Pico W son las siguientes: SIG al pin 31 (GPIO26 / ADC0), VCC al pin 36 (3.3V), y GND al pin 38 (GND). La lectura se realiza sobre el pin analógico 26, definido del siguiente modo:

```
7 #define UV_SENSOR_PIN 26 // GPIO26 = ADC0
8 #define FACTOR_CONVERSION 7.64 // Curva hallada (falta restar 1.97)
```

Listing 3.5: Definición del pin de entrada y factor de conversión.

En la función `setup()`, se inicializa la comunicación serie a 115200 baudios para la salida de depuración:

```
10 void setup() {
11     Serial.begin(115200);
12 }
```

Listing 3.6: Inicialización del puerto serie.

En la función `loop()`, se realiza la lectura del valor analógico generado por el sensor con la función `analogRead()`. Esta lectura (de 0 a 1023) se convierte a milivoltios, y luego se calcula el índice UV con la ecuación hallada en la calibración del sensor. En función del valor obtenido, se clasifica el nivel de riesgo de exposición según las categorías establecidas por la OMS:

```
14 void loop() {
15     int uv_raw = analogRead(UV_SENSOR_PIN);
16     uv = (uv_raw / 1023) * 3.3 * FACTOR_CONVERSION - 1.97;
17     String riesgo_uv;
18     if (uv < 3) {
19         riesgo_uv = "Bajo";
20     } else if (uv >= 3 && uv < 6) {
21         riesgo_uv = "Moderado";
22     } else if (uv >= 6 && uv < 8) {
23         riesgo_uv = "Alto";
24     } else if (uv >= 8 && uv < 11) {
```

```

25     riesgo_uv = "Muy Alto";
26 } else {
27     riesgo_uv = "Extremo";
28 }
29
30 Serial.print("Lectura ADC: ");
31 Serial.print(uv_raw);
32 Serial.println(" V ");
33
34 Serial.print(" Índice UV: ");
35 Serial.print(uv);
36 Serial.println(" UVI");
37
38 Serial.print(" Riesgo ");
39 Serial.println(riesgo_uv);
40
41 Serial.println("_____");
42
43 delay(1000);
44 }

```

Listing 3.7: Lectura del sensor UV y determinación de riesgo.

Este código permite visualizar en tiempo real el nivel de radiación ultravioleta y su clasificación de riesgo. Un ejemplo típico de salida por el monitor serie sería:

```

-----
Lectura ADC: 625
Índice UV: 3.56 UVI
Riesgo Moderado
-----

```

3.2.3. Veleta

El siguiente código permite la lectura de la dirección del viento mediante una veleta modelo ZTS-3000-FXJT-V05-360, conectada a la Raspberry Pi Pico W a través de una entrada analógica. Este sensor proporciona una señal analógica proporcional a la dirección del viento, con un rango que varía desde 0 hasta aproximadamente 800 unidades ADC.

Es importante destacar que la veleta debe instalarse con una marca, que dispone la veleta, apuntando al norte para una correcta interpretación de los valores.

Las conexiones físicas se realizan a través de un conversor de voltaje a 10V con las siguientes conexiones:

- GND IN del conversor: pin 38 (GND de la Raspberry Pi Pico W)
- VIN del conversor: pin 36 (3.3V)
- GND OUT: se conecta al cable negro y amarillo de la veleta, y a una resistencia de 270 Ω
- VOUT: se conecta al cable marrón de la veleta
- El cable azul de la veleta se conecta al pin 32 (GPIO 27 / ADC1) y a la otra patilla de la resistencia

La lectura se realiza sobre el pin analógico 27, definido como sigue:

```
17 const int pinVeleta = 27; // GP27 es ADC1
```

Listing 3.8: Definición del pin de lectura de la veleta.

En la función `setup()`, se inicializa la comunicación serie para depuración:

```
19 void setup() {
20     Serial.begin(115200);
21 }
```

Listing 3.9: Inicialización del puerto serie.

En la función `loop()`, se realiza la lectura del valor analógico. Se asume un rango máximo de 800 en lugar de 4095 (valor estándar del ADC), lo cual puede depender del conversor utilizado. A partir del valor analógico se calcula el voltaje y se transforma linealmente en grados (0° a 360°):

```
23 void loop() {
24     int lectura = analogRead(pinVeleta); // Leer se al anal gica
        (0-800 en Pico) 0/800 norte 0 , 200 estes 90 , 400 sur 180 , 600
        oeste 270 ETIQUETA APUNTA AL NORTE!!!
25     float voltaje = lectura * (3.3 / 800.0); // Convertir a voltaje no
        se muy bien si es 800 o 4095
26
27
28     // Convertimos a grados
29     float grados = lectura * (360.0 / 800.0);
30
31
32     Serial.print("Valor ADC: ");
33     Serial.print(lectura);
34     Serial.print(" - Voltaje: ");
35     Serial.print(voltaje);
36     Serial.print(" - Grados: ");
37     Serial.println(grados);
38
39     if (grados > 350 || grados < 10) Serial.print("NORTE");
40     if (grados > 80 && grados < 100) Serial.print("ESTE");
41     if (grados > 170 && grados < 190) Serial.print("SUR");
42     if (grados > 260 && grados < 280) Serial.print("OESTE");
43
44     delay(500); // Leer cada medio segundo
45 }
```

Listing 3.10: Lectura de dirección del viento y conversión a grados.

Este código permite obtener una lectura aproximada de la dirección del viento y mostrar en el monitor serie tanto el valor analógico como la conversión a voltaje y grados. También identifica las cuatro direcciones principales (N, S, E, O) mediante rangos de tolerancia definidos.

Un ejemplo de salida del monitor serie sería:

```
-----
Valor ADC: 23 - Voltaje: 0.10 - Grados: 9.35
NORTE
-----
```


3.2.4. Anemómetro

El siguiente código permite medir la velocidad de giro del anemómetro basado en un sensor de efecto Hall modelo SS49E. Este sensor genera un pulso cada vez que un imán pasa frente a él, lo que permite calcular la velocidad de giro.

Para calcular la velocidad del viento, habría que utilizar la siguiente fórmula:

$$V_{viento} = A * V_{giro} + B$$

Donde A y B representan factores de calibración cuya determinación implica un proceso más complejo, tanto en términos de cálculos como de condiciones experimentales. Para su obtención precisa, sería necesario el uso de un túnel de viento, recurso del que no se dispone en el proyecto.

Las conexiones físicas entre el sensor y la Raspberry Pi Pico W son las siguientes:

- VCC (pin 1 del sensor) al pin 36 (3.3V)
- GND (pin 2) al pin 38 (GND)
- VOUT (pin 3) al pin 20 (GPIO)

La constante de calibración usada se basa en el radio del rotor ($r = 0,1\text{ m}$) y permite convertir las revoluciones por minuto a km/h.

```

9 const int pinAnemometro = 20; // Pin GPIO para el sensor Hall
10 const float CALIBRATION_FACTOR_ANEMOMETRO = 0.0377; // Factor de
    calibración 2*pi*r*60/1000 (r=0.1)
11 const unsigned long REPORT_INTERVAL = 3000; // Intervalo de reporte en
    ms
12
13 // Variables para interrupciones
14 volatile unsigned long pulseCountAnem = 0;
15 volatile unsigned long lastPulseTimeAnem = 0;
16 float rpm = 0.0;
17 float windSpeedKmh = 0.0;
```

Listing 3.11: Definición de pines y variables del anemómetro.

En la función `setup()`, se configura el pin del sensor como entrada con resistencia pull-up, se inicializa la comunicación serie y se asocia una interrupción al flanco de subida para contar los pulsos generados por el sensor.

```

22 void setup() {
23     Serial.begin(115200);
24     while (!Serial); // Esperar inicialización serial
25
26     pinMode(pinAnemometro, INPUT_PULLUP);
27     attachInterrupt(digitalPinToInterrupt(pinAnemometro), hallSensorISR,
        RISING); // FALLING o RISING
28
29     Serial.println("Anemómetro inicializado - Mediciones continuas");
30 }
```

Listing 3.12: Inicialización y configuración de interrupción.

La función `loop()`, calcula cada 3 segundos el número de pulsos detectados y se transforma en revoluciones por minuto (RPM), para luego convertirlo en velocidad del viento en km/h y m/s.

```

32 void loop() {
33     static unsigned long lastReportTime = 0;
34     unsigned long currentTime = millis();
35
36     if (currentTime - lastReportTime >= REPORTINTERVAL) {
37         noInterrupts();
38         unsigned long pulses = pulseCountAnem;
39         unsigned long lastTime = lastPulseTimeAnem;
40         pulseCountAnem = 0;
41         interrupts();
42
43         if (pulses > 0 && lastTime > 0) {
44             float measurementTime = (currentTime - lastReportTime) / 1000.0;
45             rpm = (pulses / measurementTime) * 60.0;
46             windSpeedKmh = rpm * CALIBRATIONFACTORANEMOMETRO;
47         } else {
48             rpm = 0.0;
49             windSpeedKmh = 0.0;
50         }
51
52         Serial.print("RPM: ");
53         Serial.print(rpm);
54         Serial.print(" | Velocidad: ");
55         Serial.print(windSpeedKmh);
56         Serial.print(" km/h | ");
57         Serial.print(windSpeedKmh / 3.6);
58         Serial.println(" m/s");
59
60         lastReportTime = currentTime;
61     }
62 }

```

Listing 3.13: Cálculo de velocidad del viento.

La rutina de interrupción se ejecuta cada vez que se detecta un flanco de subida, incrementando el conteo de pulsos y registrando el tiempo del último pulso:

```

65 void hallSensorISR() {
66     pulseCountAnem++;
67     lastPulseTimeAnem = micros();
68     Serial.println(" + uno");
69 }

```

Listing 3.14: Rutina de interrupción del sensor Hall.

La salida en el monitor serie tendrá un formato similar al siguiente:

```

-----
+ uno
+ uno
RPM: 180.00 | Velocidad: 6.79 km/h | 1.88 m/s
-----

```

3.2.5. Pluviómetro

El siguiente código permite medir la cantidad de lluvia mediante un pluviómetro con un sensor de efecto Hall SS49E. Este sensor detecta cada basculación del balancín del pluviómetro, que contiene un pequeño imán. Cada pulso corresponde a un volumen conocido de agua. El código devuelve la precipitación acumulada desde el último reporte, es decir, envía la precipitación registrada en los últimos 3 segundos.

Las conexiones físicas entre el sensor y la Raspberry Pi Pico W son las siguientes:

- VCC (pin 1 del sensor) al pin 36 (3.3V)
- GND (pin 2) al pin 38 (GND)
- VOUT (pin 3) al pin 21 (GPIO)

El factor de calibración se ajusta según el volumen recogido por cada basculación. El balancín se calibró con una jeringuilla, observando una capacidad de 3.7 ml.

```
9 const int HALL_SENSOR_PIN = 21; // Pin GPIO para el sensor Hall
10 const float CALIBRATION_FACTOR = 3.7; // Factor de calibración 3.7
    ml cada balanceo
11 const unsigned long REPORT_INTERVAL = 3000; // Intervalo de reporte en
    ms
12
13 // Variables para interrupciones
14 volatile unsigned long pulseCount = 0;
15 volatile unsigned long lastPulseTime = 0;
16 float contador_min = 0.0;
17 float cantidad_ml = 0.0;
```

Listing 3.15: Definición de pines y variables del pluviómetro.

En la función `setup()`, se configura la entrada digital con resistencia pull-up, se inicializa la comunicación serie y se vincula una interrupción al flanco de subida del sensor Hall:

```
22 void setup() {
23     Serial.begin(115200);
24     while (!Serial); // Esperar inicialización serial
25
26     pinMode(HALL_SENSOR_PIN, INPUT_PULLUP);
27     attachInterrupt(digitalPinToInterrupt(HALL_SENSOR_PIN),
        hallSensorISR, RISING); // FALLING o RISING
28
29     Serial.println("Pluviómetro inicializado - Mediciones continuas");
30 }
```

Listing 3.16: Inicialización del pluviómetro.

Cada 3 segundos, la función `loop()` calcula la cantidad de pulsos detectados y estima el caudal de lluvia en litros por metro cuadrado:

```

32 void loop() {
33     static unsigned long lastReportTime = 0;
34     unsigned long currentTime = millis();
35
36     if (currentTime - lastReportTime >= REPORTINTERVAL) {
37         noInterrupts();
38         unsigned long pulses = pulseCount;
39         unsigned long lastTime = lastPulseTime;
40         pulseCount = 0;
41         interrupts();
42
43         if (pulses > 0 && lastTime > 0) {
44             float measurementTime = (currentTime - lastReportTime) / 1000.0;
45             //pulses
46             cantidad_ml = pulses * CALIBRATIONFACTOR;
47         } else {
48
49             cantidad_ml = 0.0;
50         }
51
52         Serial.print("Contador desde la ltima interrupci n: ");
53         Serial.println(pulses);
54         Serial.print(" | Cantidad desde la ltima interrupci n: ");
55         Serial.print(cantidad_ml/0.000014725, 2); //9.5*15.5 cm Area del
embudo = 0.014725 m^2 / 1000 para pasar de ml a l
56         Serial.println(" l/m^2 | ");
57
58
59         lastReportTime = currentTime;
60     }
61 }

```

Listing 3.17: Cálculo de caudal de lluvia.

La rutina de interrupción se activa con cada flanco de subida y simplemente incrementa el contador de pulsos:

```

64 void hallSensorISR() {
65     pulseCount++;
66     lastPulseTime = micros();
67     Serial.println(" + uno");
68 }

```

Listing 3.18: Rutina de interrupción del sensor Hall.

La salida en el monitor serie se actualiza periódicamente con datos como:

```

-----
+ uno
+ uno
Contador desde última interrupción: 20.00
Cantidad desde última interrupción: 74.00 l/m^2
-----

```

3.2.6. Pantalla LCD

El siguiente código permite mostrar información en una pantalla LCD de 16 columnas por 2 filas (modelo HD44780 o compatible), utilizando la librería `LiquidCrystal` y una conexión en modo de 4 bits a la Raspberry Pi Pico W.

Las conexiones físicas entre la pantalla LCD y la Raspberry Pi Pico W son las siguientes:

- VSS al pin 38 (GND)
- VDD al pin 36 (3.3V)
- V0 al pin central de potenciómetro (para contraste)
- RS al pin 1 (GPIO 0)
- RW al pin 38 (GND)
- E al pin 2 (GPIO 1)
- D4 al pin 4 (GPIO 2)
- D5 al pin 5 (GPIO 3)
- D6 al pin 6 (GPIO 4)
- D7 al pin 7 (GPIO 5)
- A (anodo retroiluminación) al pin 40 (3.3V)
- K (cátodo retroiluminación) al pin 38 (GND)

```
17 #include <LiquidCrystal.h>
18
19 // Configura pines (RS, E, D4, D5, D6, D7)
20 LiquidCrystal lcd(0, 1, 2, 3, 4, 5); // Usando GP0, GP1, GP2, GP3,
    GP4, GP5
21
22 // Variables para el control del tiempo
23 unsigned long previousTime = 0;
24 const long interval = 3000; // Intervalo de 3 segundos (3000 ms)
25 int step = 0; // Paso actual del bucle
```

Listing 3.19: Variables de la pantalla LCD y definición de pines.

En la función `setup()`, se inicializa la pantalla LCD y se muestra un mensaje de inicio:

```
27 void setup() {
28     lcd.begin(16, 2); // Inicializa LCD (16 columnas, 2 filas)
29     lcd.print("Iniciando...");
30     delay(1000);
31     lcd.clear();
32 }
```

Listing 3.20: Inicialización de pantalla LCD y mensaje de bienvenida.

La función `loop()` actualiza la pantalla cada 3 segundos, mostrando de forma cíclica distintas variables meteorológicas (estos valores deben ser reemplazados por las lecturas reales de los sensores):

```

34 void loop() {
35     unsigned long currentTime = millis(); // Tiempo actual
36
37     // Cada 3 segundos, cambia el mensaje
38     if (currentTime - previousTime >= interval) {
39         previousTime = currentTime; // Reinicia el temporizador
40
41         lcd.clear(); // Limpia la pantalla
42
43         switch (step) {
44             case 0:
45                 lcd.setCursor(0, 0);
46                 lcd.print("Temperatura:");
47                 lcd.setCursor(0, 1);
48                 lcd.print("25.5 C"); // Reemplaza con tu sensor real
49                 break;
50             case 1:
51                 lcd.setCursor(0, 0);
52                 lcd.print("Humedad:");
53                 lcd.setCursor(0, 1);
54                 lcd.print("60%"); // Reemplaza con tu sensor real
55                 break;
56             case 2:
57                 lcd.setCursor(0, 0);
58                 lcd.print("Presi n:");
59                 lcd.setCursor(0, 1);
60                 lcd.print("1013 hPa"); // Reemplaza con tu sensor real
61                 break;
62             case 3:
63                 lcd.setCursor(0, 0);
64                 lcd.print("Indice UV:");
65                 lcd.setCursor(0, 1);
66                 lcd.print("Moderado"); // Reemplaza con tu sensor real
67                 break;
68         }
69
70         step++; // Avanza al siguiente paso
71         if (step > 3) step = 0; // Reinicia el bucle despu s del ndice
           UV
72     }
73 }
```

Listing 3.21: Visualización rotativa de datos.

Esta secuencia permite mostrar los parámetros atmosféricos medidos en tiempo real en una única pantalla LCD, ideal cuando no se dispone de una interfaz gráfica o monitor adicional.

El Anexo D. contiene todos los códigos completos utilizados para las pruebas individuales.

3.3 Conectividad y transmisión de datos

El sistema de la estación meteorológica implementa conectividad WiFi utilizando el protocolo de mensajería ligera MQTT para la transmisión de datos hacia un servidor local. Esta comunicación permite la monitorización remota de los parámetros atmosféricos capturados por los sensores.

3.3.1. Configuración de red WiFi

La conexión WiFi se establece utilizando el SSID de la red a la que se conecte la Raspberry Pi Pico W, y la contraseña de esta red.

En el código fuente, esta configuración se realiza mediante las siguientes líneas:

```
10 const char* ssid = "TU_SSID_WIFI";  
11 const char* password = "TU_CONTRSEA_WIFI";
```

Listing 3.22: Credenciales WiFi.

```
275 void setup_wifi() {  
276     delay(10);  
277     Serial.println("Conectando a WiFi...");  
278     WiFi.begin(ssid, password);  
279  
280     while (WiFi.status() != WL_CONNECTED) {  
281         delay(500);  
282         Serial.print("."); Serial.print(WiFi.status());  
283     }  
284  
285     Serial.println("\nWiFi conectado");  
286     Serial.print("IP: ");  
287     Serial.println(WiFi.localIP());  
288 }
```

Listing 3.23: Configuración WiFi.

Una vez conectado, el dispositivo muestra la dirección IP asignada por la red, lo cual permite su identificación dentro de la red local.

3.3.2. Formato del mensaje transmitido

Los datos de los sensores son formateados en un objeto JSON antes de ser enviados. Este formato permite estructurar la información de manera clara y fácilmente interpretable por aplicaciones de visualización o almacenamiento. Un ejemplo de mensaje transmitido es:

```
{  
  "t": 23.45,  
  "h": 56.78,  
  "pn": 1012.34,  
  "v": 180.00,  
  "a": 15.67,  
  "pl": 0.50,  
  "r": 5.12  
}
```

Donde:

- "t": Temperatura (°C)
- "h": Humedad relativa (%)
- "pn": Presión atmosférica (hPa)
- "v": Dirección del viento (°)
- .a": Velocidad del viento (km/h)
- "pl": Precipitación (mL min⁻¹)
- r": Índice UV (valor numérico)

3.3.3. Protocolo de comunicación: MQTT

Para la transmisión de datos, se utiliza el protocolo **MQTT (Message Queuing Telemetry Transport)**, ideal para aplicaciones IoT debido a su ligereza y eficiencia. En este caso, se emplea la biblioteca **PubSubClient** para la conexión y publicación.

El servidor MQTT está alojado localmente con la herramienta **Mosquitto**, configurado en la dirección IP:

- **Broker MQTT:** 192.168.1.105
- **Puerto:** 1883
- **Usuario:** xxxxxxxxxxxxxxxx
- **Contraseña:** xxxxxxxxxxxxxxxx

La publicación de datos se realiza periódicamente (cada 6 segundos) en el tópico `/teleco/estacion1`.

```

124  if ( millis() - lastMsg > 6000 ) {
125      lastMsg = millis();
126      String mensaje = "{";
127      mensaje += "\"t\":" + String(temp, 2) + ","; //comentario
128      mensaje += "\"h\":" + String(hum, 2) + ",";
129      mensaje += "\"pn\":" + String(pres, 2) + ",";
130      mensaje += "\"v\":" + String(grados, 2) + ",";
131      mensaje += "\"a\":" + String(windSpeedKmh, 2) + ",";
132      mensaje += "\"pl\":" + String(cantidad_ml, 2) + ",";
133      mensaje += "\"r\":" + String(uv, 2);
134      mensaje += "}";
135
136      char buffer[mensaje.length() + 1];
137      mensaje.toCharArray(buffer, sizeof(buffer));
138
139      client.publish("/teleco/estacion1", buffer);
140
141      Serial.println("Mensajes publicado");
142  }
```

Listing 3.24: Publicación de los datos.

3.3.4. Uso de Mosquitto

Mosquitto es un *broker* MQTT de código abierto que permite la comunicación entre dispositivos mediante el protocolo MQTT (Message Queuing Telemetry Transport), un sistema de mensajería ligero y eficiente basado en el modelo *publicador/suscriptor*. Este protocolo está especialmente diseñado para entornos con recursos limitados o redes inestables, como es habitual en proyectos de IoT (Internet of Things). Mosquitto gestiona los mensajes que se publican en distintos tópicos, permitiendo que otros dispositivos suscritos a dichos tópicos los reciban de forma eficiente y en tiempo real.

En el contexto de este trabajo, Mosquitto se utilizó como broker MQTT de forma local, instalado en el mismo ordenador empleado para la realización de pruebas de funcionamiento. Esta configuración permitió verificar el correcto funcionamiento de la conexión de red, la autenticación básica y la transmisión de mensajes en formato JSON desde la estación meteorológica al broker. Es importante destacar que el uso de Mosquitto en este proyecto tiene carácter provisional y experimental, ya que la implementación definitiva del sistema de mensajería y del broker MQTT forma parte de otro proyecto independiente que complementa esta estación meteorológica.

3.3.5. Funcionamiento general

El flujo de conectividad y transmisión puede resumirse de la siguiente manera:

1. La estación se conecta a la red WiFi local.
2. Establece conexión con el broker Mosquitto a través de MQTT.
3. Cada 6 segundos, los datos ambientales se leen, se empaquetan en formato JSON y se publican en el tópico `/teleco/estacion1`.
4. Cualquier cliente MQTT (por ejemplo, una aplicación en Python, Node-RED o una base de datos) que esté suscrito a dicho tópico puede recibir y procesar estos datos en tiempo real.

3.4 Estructura del código principal

Una vez realizadas con éxito todas las pruebas individuales, tanto de los sensores como de la conectividad WiFi y el envío por MQTT, se procedió a integrar todos los módulos en un único programa. Este código unificado se ejecuta en la Raspberry Pi Pico W y coordina el funcionamiento global de la estación meteorológica.

El programa se estructura en dos partes principales: la función `setup()` y el bucle `loop()`. En la fase de inicialización, `setup()` se encarga de:

- Configurar los pines y modos de funcionamiento de los sensores.
- Inicializar la pantalla LCD en modo 4 bits.
- Establecer la conexión con la red WiFi.
- Configurar el cliente MQTT.
- Iniciar el bus I2C y comprobar la presencia del sensor BME280.

- Activar las interrupciones para el anemómetro y el pluviómetro.

Una vez completada la inicialización, el bucle principal `loop()` entra en funcionamiento. Este se encarga de:

- Reconectar al broker MQTT en caso de desconexión.
- Realizar lecturas periódicas de todos los sensores (temperatura, humedad, presión, UV, dirección y velocidad del viento, precipitación).
- Procesar los datos provenientes de los sensores con pulsos (anemómetro y pluviómetro) mediante variables compartidas y temporizadas.
- Construir un mensaje en formato JSON y enviarlo al servidor MQTT.
- Mostrar cíclicamente los diferentes valores medidos en la pantalla LCD.

Además, se utilizan funciones auxiliares como `setup_wifi()` para establecer la conexión inalámbrica y `reconnect()` para mantener activa la comunicación con el servidor MQTT. Las interrupciones definidas (ISR) permiten registrar eventos de forma precisa sin interrumpir la ejecución general del programa.

Esta arquitectura modular facilita la integración eficiente de múltiples sensores, asegurando una operación continua, autónoma y sincronizada del sistema. El código completo que implementa la estación meteorológica se encuentra en el Anexo D.7.

Capítulo 4

Presupuesto

En este capítulo se presenta una estimación económica del coste total asociado al desarrollo y fabricación de la estación metereológica. El objetivo es conocer cuánto cuesta producir una unidad y cómo varía ese coste en función del volumen de producción.

Para ello, se han distinguido dos tipos de costes: los costes fijos y los costes variables.

Los costes fijos son aquellos que no dependen del número de unidades producidas. El principal en este proyecto es el tiempo dedicado al diseño por parte del ingeniero. Este coste se asume de forma inicial (tiempo dedicado al estudio, análisis y diseño de la estación), y se reparte entre todas las unidades fabricadas, por lo que su impacto por unidad disminuye cuanto mayor es el volumen de producción.

Por otro lado, los costes variables sí dependen directamente del número de unidades fabricadas. Aquí se incluyen principalmente los materiales necesarios para fabricar cada dispositivo. Estos costes se mantienen constantes por unidad y no se ven afectados por la escala de producción.

En la Tabla 4.1 se detalla el coste del material necesario para fabricar una unidad del dispositivo, así como el precio por hora de trabajo a la hora de montar la estación. En los componentes que requieren una compra mínima, se ha considerado el precio de la compra mínima.

Componente	Cantidad	Coste (€)
Resistencia R1	10	0,08
Resistencia R3	10	0,62
Resistencia R4	10	0,42
BME280	1	3,28
Conversor a 10V	1	6,58
Sensor Hall SS49E	5	2,00
Pantalla LCD	1	2,83
Potenciómetro	1	2,36
Raspberry Pi Pico W	1	6,39
Botón RESET	10	1,22
Veleta ZTS-3000-FXJT	1	19,65
PCB	5	5,73
PLA impresión 3D	1	12,95
Tornillería	1	6,15
Rodamiento	1	2,13
Plancha policarbonato	8	12,00
Imanes	5	1,29
Horas de montaje	5	60,00
Total		145,68

Tabla 4.1: Coste de materiales por unidad.

El coste de desarrollo se muestra en la Tabla 4.2. Se ha calculado en función del número estimado de horas necesarias para el análisis, estudio y diseño, y el precio por hora del trabajo técnico, calculado suponiendo un salario anual de 21.504 € y el convenio de ingenierías y oficinas técnicas de 1.792 horas anuales.

Horas dedicadas	Precio por hora (€/h)	Total (€)
145	12,00	1.740,00

Tabla 4.2: Coste de desarrollo del dispositivo.

La Tabla 4.3 muestra cómo varía el precio de algunos materiales en función de la cantidad de unidades producidas. Por su parte, la Tabla 4.4 detalla cómo se reparte el coste total de desarrollo según el número de unidades.

Componente	Coste 1 u. (€)	Coste 100 uds. (€)	Coste 1000 uds. (€)
R1	0,08	0,0074	0,0052
R3	0,62	0,0346	0,0202
R4	0,42	0,029	0,0241
Sensor Hall SS49E	2,00	0,40	0,40
Potenciómetro	2,36	1,70	1,70
Botón RESET	1,22	0,1027	0,0835
PCB	5,73	1,3587	0,89258
PLA impresión 3D	12,95	1,295	1,295
Plancha policarbonato	12,00	1,56	1,56
Imanes	1,29	0,259	0,258

Tabla 4.3: Coste material por unidad en función del volumen

Unidades.	Coste material (€)	Coste de desarrollo (€)	Coste total (€)
1	145,68	1740,00	1885,68
100	113,77	17,40	131,17
1000	113,25	1,74	114,99

Tabla 4.4: Coste total por unidad en función del volumen

Como se puede observar, a partir de las 10 unidades la variación del coste de material es muy reducida, notándose la variación total en el coste de desarrollo. A partir de las mil unidades, tanto el cambio del coste de desarrollo como del material es despreciable. Se adjunta la lista de materiales BOM (Bill of materials) en el Anexo E.

Capítulo 5

Conclusiones

5.1 Resultado del proyecto

El desarrollo de este Trabajo Fin de Grado ha culminado con éxito, alcanzando los objetivos planteados inicialmente. Se ha diseñado y construido una estación meteorológica completa, basada en la Raspberry Pi Pico W, capaz de medir diversas variables climáticas: temperatura, presión atmosférica, humedad relativa, índice de radiación ultravioleta (UV), cantidad de precipitación, velocidad y dirección del viento. Para ello, se han integrado diferentes sensores mediante una placa de circuito impreso (PCB) personalizada, y se ha desarrollado una carcasa protectora impresa en 3D que permite su uso en entornos exteriores.

En el plano del software, se ha programado un sistema robusto que no solo adquiere y procesa las mediciones locales, sino que también se encarga de enviarlas de forma periódica a un servidor remoto utilizando el protocolo de comunicación MQTT. Esta funcionalidad de conectividad ha sido posible gracias a la incorporación del módulo WiFi en la Raspberry Pi Pico W, lo que convierte el sistema en una solución de bajo consumo, bajo coste y adecuada para aplicaciones de Internet de las Cosas (IoT).

Durante el proceso de desarrollo, se han superado diversos retos técnicos, como la integración de sensores analógicos y digitales, la adaptación de tensiones incompatibles, la calibración de sensores de viento y precipitación, y el diseño físico de los componentes. Todo ello ha contribuido a una comprensión más profunda tanto del diseño electrónico como del desarrollo de software.

El sistema resultante ha mostrado un funcionamiento correcto y estable, lo que demuestra su viabilidad como herramienta para el monitoreo ambiental. Su diseño abierto y replicable permite que pueda ser implementado en entornos educativos, urbanos o rurales.

En definitiva, el proyecto ha cumplido satisfactoriamente sus objetivos, sentando las bases para desarrollos futuros que amplíen sus capacidades o faciliten su despliegue a mayor escala.

5.2 Líneas de futuro

A partir del desarrollo realizado en este Trabajo de Fin de Grado, se plantean varias líneas de mejora y ampliación que podrían abordarse en trabajos posteriores. Estas se enfocan en optimizar el funcionamiento del sistema y facilitar su reproducción por parte de otros usuarios.

En primer lugar, aunque el sistema actual proporciona datos funcionales en la medición del índice ultravioleta, sería recomendable incorporar sensores más precisos o implementar algoritmos de corrección que utilicen datos externos, como los ofrecidos por satélites o estaciones meteorológicas oficiales. Esto permitiría mejorar la fiabilidad y utilidad de las mediciones, especialmente en aplicaciones más exigentes.

Por otro lado, sería importante realizar una calibración adecuada del anemómetro. Actualmente, el sensor entrega valores de la velocidad de giro del anemómetro y no de la velocidad real del viento. Llevar a cabo una calibración en condiciones controladas, como en un túnel de viento o mediante comparación con instrumentos certificados, permitiría obtener datos más precisos de velocidad del viento y aumentar la calidad del sistema.

Por último, se considera muy útil la elaboración de un manual completo que detalle el proceso de fabricación, configuración y uso del dispositivo, ya que este proyecto se plantea como una iniciativa escalable que permita la implementación de múltiples estaciones meteorológicas similares en distintos centros educativos de una misma ciudad. El objetivo es crear una red de monitoreo ambiental distribuida que facilite la identificación de distintos factores ambientales, como pueden ser islas de calor, microclimas urbanos y corredores de viento.

Bibliografía

- [1] Naylamp Mechatronics. *Módulo Sensor de Luz Ultravioleta UV GUVAS12SD*. Disponible en: <https://naylampmechatronics.com/sensores-luz-y-sonido/1221-modulo-sensor-de-luz-ultravioleta-uv-guva-s12sd.html>
- [2] Naylamp Mechatronics. *Sensor BME280 Presión, Temperatura y Humedad*. Disponible en: <https://naylampmechatronics.com/sensores-posicion-inerciales-gps/357-sensor-bme280-presion-temperatura-y-humedad.html>
- [3] Naylamp Mechatronics. *Sensor BME680 Presión, Temperatura, Humedad y Gas*. Disponible en: <https://naylampmechatronics.com/sensores-posicion-inerciales-gps/650-sensor-bme680-presion-temperatura-humedad-y-gas.html>
- [4] Naylamp Mechatronics. *Sensor DHT22 Temperatura y Humedad relativa*. Disponible en: [https://naylampmechatronics.com/sensores-temperatura-y-humedad/58-sensor-de-temperatura-y-humedad-relativa-dht22-am2302.html#:~:text=El%20DHT22%20\(AM2302\)%20es%20un,\(no%20posee%20salida%20anal%C3%B3gica\).](https://naylampmechatronics.com/sensores-temperatura-y-humedad/58-sensor-de-temperatura-y-humedad-relativa-dht22-am2302.html#:~:text=El%20DHT22%20(AM2302)%20es%20un,(no%20posee%20salida%20anal%C3%B3gica).)
- [5] AliExpress. *BMP280-3.3V módulo Digital Sensor de presión barométrica de temperatura para Arduino BMP280*. Disponible en: https://es.aliexpress.com/item/1005004527984343.html?spm=a2g0o.order_list.order_list_main.46.6c8d194difteUu&gatewayAdapt=glo2esp
- [6] Leyendas Mirdalirs. *El anemómetro y el anemoscopio de Leonardo*. Disponible en: <https://leyendasmirdalirs.com/2015/05/26/el-anemometro-y-el-anemoscopio-de-leonardo/>
- [7] Naylamp Mechatronics. *Sensor de Efecto Hall SS49E*. Disponible en: <https://naylampmechatronics.com/sensores-proximidad/994-sensor-de-efecto-hall-ss49e.html>
- [8] Wikipedia. *Edwin Herbert Hall*. Disponible en: https://es.wikipedia.org/wiki/Edwin_Herbert_Hall
- [9] Wikipedia. *Sensor de efecto Hall*. Disponible en: https://es.wikipedia.org/wiki/Sensor_de_efecto_Hall
- [10] Universidad de Vigo. *Sensor de efecto Hall - Electromagnetismo*. Disponible en: https://dte_recursos.webs.uvigo.es/recursos/multimedia/inductivos/INDUCTIVOS/electromagnetismo/hall.htm

- [11] Raspberry Pi Foundation. *Pico Series Documentation*. Disponible en: <https://www.raspberrypi.com/documentation/microcontrollers/pico-series.html>
- [12] Mouser Electronics. *AS5600*. Disponible en: https://www.mouser.com/datasheet/2/588/AS5600_UG000254_2_00-1877354.pdf?srltid=AfmB0oq00hf4WzFiTc7tnkT-GZZRXg0A12YWTjMoLLihx6D0cwTHkSM9
- [13] AliExpress. *Sensor de dirección del viento de 360 °, transmisor de dirección del viento para estación meteorológica de ocho direcciones, RS485 4-20MA 0-5V 0-10V*. Disponible en: https://es.aliexpress.com/item/1005003040677398.html?spm=a2g0o.order_list.order_list_main.36.6c8d194difteUu&gatewayAdapt=glo2esp
- [14] Anemómetro electrónico . *Detalles del anemómetro electrónico* . Disponible en: <http://www.miajas.com/intercom/Anemometro/videoVeleta.htm>
- [15] IEEE Xplore. *MQTT-Based Adaptive Estimation Over Distributed Network Using Raspberry Pi Pico W*. Disponible en: <https://ieeexplore.ieee.org/abstract/document/10704725>
- [16] YouTube. *Funcionamiento y manejo de display LCD 16x2 en Arduino*. Disponible en: <https://www.youtube.com/watch?v=YqxyAM-NOBk>
- [17] TodoElectrodo. *LCD 16x2*. Disponible en: <https://todoelectrodo.blogspot.com/2013/02/lcd-16x2.html>
- [18] Cults 3D. *Wind Indication System*. Disponible en: <https://cults3d.com/es/modelo-3d/herramientas/wind-indication-system>
- [19] Instructables. *DIY Weather Station With ESP32*. Disponible en: <https://www.instructables.com/DIY-Weather-Station-With-ESP32/>
- [20] Hubor Proteus. *Creación de modelos en Proteus*. Disponible en: <https://www.hubor-proteus.com/documentos/Creacion%20de%20modelos%20en%20proteus.pdf>
- [21] Universidad de Valladolid. *TFG: Fabricación de placas de circuito impreso con Proteus* . Disponible en: <https://uvadoc.uva.es/bitstream/handle/10324/14625/TFG-P-312.pdf?sequence=1>
- [22] Hubor Proteus. *Utilización de las pilas de huellas*. Disponible en: <https://www.hubor-proteus.com/proteus-pcb/ares/318-utilizaci%C3%B3n-de-las-pilas-de-huellas.html>
- [23] CEAC. *¿Qué es el IDE de Arduino en robótica?*. Disponible en: <https://www.ceac.es/blog/que-es-el-ide-de-arduino-en-robotica>
- [24] Labcenter Electronics. *BOM Generator - Proteus*. Disponible en: <https://www.labcenter.com/bom/>
- [25] Proto Supplies. *GUVA-S12SD UV Light Sensor Module*. Disponible en: <https://protosupplies.com/product/guva-s12sd-uv-light-sensor-module/>

- [26] AEMET. *Índice de radiación ultravioleta (UVI) en Valladolid*. Disponible en: <https://www.aemet.es/es/eltiempo/observacion/radiacion/ultravioleta?l=valladolid>
- [27] Suelo Solar. *Hora solar en España*. Disponible en: <https://suelosolar.com/hora-solar>
- [28] Seeed studio. *Grove - UV Sensor*. Disponible en: https://wiki.seeedstudio.com/Grove-UV_Sensor/
- [29] ResearchGate. *Esquema del pluviógrafo de balancín*. Disponible en: https://www.researchgate.net/figure/Figura-1-Esquema-del-pluviografo-de-balancin_fig1_262662612
- [30] Aranacorp. *Uso de un sensor de efecto Hall con Arduino*. Disponible en: https://www.aranacorp.com/es/uso-de-un-sensor-de-efecto-hall-con-arduino/#google_vignette
- [31] Store Mectronica. *El sensor del pluviómetro mide el volumen de lluvia pulsada para estaciones meteorológicas y Arduino*. Disponible en: <https://store.mectronica.it/es/lluvia/1326-el-sensor-del-pluviometro-mide-el-volumen-de-lluvia-pulsada-para-estaciones.html>
- [32] DF Robot. *RS485 Wind Speed*. Disponible en: https://wiki.dfrobot.com/RS485_Wind_Speed_Transmitter_SKU_SEN0483
- [33] YouTube. *Creación de componentes en Proteus*. Disponible en: <https://www.youtube.com/watch?v=RKK3HvTaX8s>
- [34] YouTube. *Anemómetro casero 2*. Disponible en: <https://www.youtube.com/watch?v=EWfUigol30M>
- [35] YouTube. *Creación de símbolos en Proteus*. Disponible en: <https://www.youtube.com/watch?v=vq6Q-beyBkw>

Anexo A

Hojas de datos

A.1 Hoja de datos Raspberry Pi Pico W

RP2040 A microcontroller by Raspberry Pi

Raspberry Pi Pico W Datasheet

An RP2040-based microcontroller
board with wireless

Raspberry Pi Ltd

Colophon

© 2022-2024 Raspberry Pi Ltd

This documentation is licensed under a Creative Commons [Attribution-NoDerivatives 4.0 International](#) (CC BY-ND).

build-date: 2024-10-15

build-version: eec2b0c-clean

Legal disclaimer notice

TECHNICAL AND RELIABILITY DATA FOR RASPBERRY PI PRODUCTS (INCLUDING DATASHEETS) AS MODIFIED FROM TIME TO TIME ("RESOURCES") ARE PROVIDED BY RASPBERRY PI LTD ("RPL") "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW IN NO EVENT SHALL RPL BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THE RESOURCES, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

RPL reserves the right to make any enhancements, improvements, corrections or any other modifications to the RESOURCES or any products described in them at any time and without further notice.

The RESOURCES are intended for skilled users with suitable levels of design knowledge. Users are solely responsible for their selection and use of the RESOURCES and any application of the products described in them. User agrees to indemnify and hold RPL harmless against all liabilities, costs, damages or other losses arising out of their use of the RESOURCES.

RPL grants users permission to use the RESOURCES solely in conjunction with the Raspberry Pi products. All other use of the RESOURCES is prohibited. No licence is granted to any other RPL or other third party intellectual property right.

HIGH RISK ACTIVITIES. Raspberry Pi products are not designed, manufactured or intended for use in hazardous environments requiring fail safe performance, such as in the operation of nuclear facilities, aircraft navigation or communication systems, air traffic control, weapons systems or safety-critical applications (including life support systems and other medical devices), in which the failure of the products could lead directly to death, personal injury or severe physical or environmental damage ("High Risk Activities"). RPL specifically disclaims any express or implied warranty of fitness for High Risk Activities and accepts no liability for use or inclusions of Raspberry Pi products in High Risk Activities.

Raspberry Pi products are provided subject to RPL's [Standard Terms](#). RPL's provision of the RESOURCES does not expand or otherwise modify RPL's [Standard Terms](#) including but not limited to the disclaimers and warranties expressed in them.


Table of contents

Colophon	1
Legal disclaimer notice	1
1. About Raspberry Pi Pico W	3
1.1. Raspberry Pi Pico W design files	5
2. Mechanical specification	7
2.1. Pico W pinout	7
2.2. Surface-mount footprint	9
2.2.1. Keep-out area	12
2.3. Recommended operating conditions	14
3. Applications information	15
3.1. Programming the flash	15
3.2. General purpose I/O	15
3.3. Using the ADC	15
3.4. Powerchain	16
3.5. Powering Raspberry Pi Pico W	17
3.6. Using a battery charger	18
3.7. USB	19
3.8. Wireless interface	19
3.9. Debugging	20
Appendix A: Availability	21
Support	21
Ordering code	21
Appendix B: Pico W schematic	22
Appendix C: Pico W component locations	24
Documentation Release History	25
15 October 2024	25
02 May 2024	25
02 Feb 2024	25
14 Jun 2023	25
03 Mar 2023	25
01 Dec 2022	25
30 Jun 2022	26

Chapter 1. About Raspberry Pi Pico W

Raspberry Pi Pico W is a microcontroller board based on the Raspberry Pi RP2040 microcontroller chip.

Figure 1. The Raspberry Pi Pico W Rev3 board.



Raspberry Pi Pico W has been designed to be a low cost yet flexible development platform for RP2040, with a 2.4GHz wireless interface and the following key features:

- RP2040 microcontroller with 2MB of flash memory
- On-board single-band 2.4GHz wireless interfaces (802.11n, Bluetooth 5.2)
 - Support for Bluetooth LE Central and Peripheral roles
 - Support for Bluetooth Classic
- Micro USB B port for power and data (and for reprogramming the flash)
- 40-pin 21mm×51mm 'DIP' style 1mm thick PCB with 0.1" through-hole pins also with edge castellations
 - Exposes 26 multi-function 3.3V general purpose I/O (GPIO)
 - 23 GPIO are digital-only, with three also being ADC capable
 - Can be surface-mounted as a module
- 3-pin Arm serial wire debug (SWD) port
- Simple yet highly flexible power supply architecture
 - Various options for easily powering the unit from micro USB, external supplies or batteries
- High quality, low cost, high availability
- Comprehensive SDK, software examples and documentation

For full details of the RP2040 microcontroller please see the [RP2040 Datasheet](#) book. Key features include:

- Dual-core cortex M0+ at up to 133MHz

Raspberry Pi Pico W Datasheet

- On-chip PLL allows variable core frequency
- 264kB multi-bank high performance SRAM
- External Quad-SPI flash with eXecute In Place (XIP) and 16kB on-chip cache
- High performance full-crossbar bus fabric
- On-board USB1.1 (device or host)
- 30 multi-function general purpose I/O (four can be used for ADC)
 - 1.8-3.3V I/O voltage
- 12-bit 500ksps analogue to digital converter (ADC)
- Various digital peripherals
 - 2 × UART, 2 × I2C, 2 × SPI, 16 × PWM channels
 - 1 × timer with 4 alarms, 1 × real time clock
- 2 × programmable I/O (PIO) blocks, 8 state machines in total
 - Flexible, user-programmable high-speed I/O
 - Can emulate interfaces such as SD card and VGA

i NOTE

Raspberry Pi Pico W I/O voltage is fixed at 3.3V


Raspberry Pi Pico W provides a minimal yet flexible external circuitry to support the RP2040 chip: flash memory (Winbond W25Q16JV), crystal (Abracon ABM8-272-T3), power supplies and decoupling, and USB connector. The majority of the RP2040 microcontroller pins are brought to the user I/O pins on the left and right edge of the board. Four RP2040 I/O are used for internal functions: driving an LED, on-board switch mode power supply (SMPS) power control, and sensing the system voltages.

Pico W has an on-board 2.4GHz wireless interface using an Infineon CYW43439. The antenna is an onboard antenna licensed from ABRACON (formerly ProAnt). The wireless interface is connected via SPI to the RP2040.

Pico W has been designed to use either soldered 0.1-inch pin-headers (it is one 0.1-inch pitch wider than a standard 40-pin DIP package), or to be positioned as a surface-mountable 'module', as the user I/O pins are also castellated. There are SMT pads underneath the USB connector and BOOTSEL button, which allow these signals to be accessed if used as a reflow-soldered SMT module.

Raspberry Pi Pico W Datasheet

Figure 2. The pinout of the Pico W Rev3 board



Raspberry Pi Pico W uses an on-board buck-boost SMPS which is able to generate the required 3.3V (to power RP2040 and external circuitry) from a wide range of input voltages (~1.8 to 5.5V). This allows significant flexibility in powering the unit from various sources, such as a single lithium-ion cell, or three AA cells in series. Battery chargers can also be very easily integrated with the Pico W powerchain.

Reprogramming the Pico W flash can be done using USB (simply drag and drop a file onto the Pico W, which appears as a mass storage device), or the standard serial wire debug (SWD) port can reset the system and load and run code without any button presses. The SWD port can also be used to interactively debug code running on the RP2040.

Getting started with Pico W

The [Getting started with Raspberry Pi Pico-series](#) book walks through loading programs onto the board, and shows how to install the C/C++ SDK and build the example C programs. See the [Raspberry Pi Pico-series Python SDK](#) book to get started with MicroPython, which is the fastest way to get code running on Pico W.

1.1. Raspberry Pi Pico W design files

The source design files, including the schematic and PCB layout, are made available openly except for the antenna. The Niche™ antenna is an Abracon/Proant patented antenna technology. Please contact niche@abracon.com for information on licensing.

Schematic The schematic is reproduced in [Appendix B](#). The schematic is also distributed alongside the [layout files](#).

Layout The CAD files, including PCB layout, can be found [here](#). Note that Pico W was designed in Cadence Allegro PCB Editor, and opening in other PCB CAD packages will require an import script or plugin.

Raspberry Pi Pico W Datasheet

STEP 3D A STEP 3D model of Raspberry Pi Pico W, for 3D visualisation and fit-check of designs which include Pico W as a module, can be found [here](#).

Fritzing A Fritzing part for use in e.g. breadboard layouts can be found [here](#).


Permission to use, copy, modify, and/or distribute this design for any purpose with or without fee is hereby granted.

THE DESIGN IS PROVIDED "AS IS" AND THE AUTHOR DISCLAIMS ALL WARRANTIES WITH REGARD TO THIS DESIGN INCLUDING ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS. IN NO EVENT SHALL THE AUTHOR BE LIABLE FOR ANY SPECIAL, DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS DESIGN.

Chapter 2. Mechanical specification

The Pico W is a single sided 51mm × 21mm × 1mm PCB with a micro USB port overhanging the top edge, and dual castellated/through-hole pins around the two long edges. The onboard wireless antenna is located on the bottom edge. To avoid detuning the antenna, no material should intrude into this space. Pico W is designed to be usable as a surface-mount module as well as presenting a dual inline package (DIP) format, with the 40 main user pins on a 2.54mm (0.1") pitch grid with 1mm holes, compatible with veroboard and breadboard. Pico W also has four 2.1mm (± 0.05 mm) drilled mounting holes to provide for mechanical fixing (see [Figure 3](#)).

Figure 3. The dimensions of the Pico W




2.1. Pico W pinout

The Pico W pinout has been designed to directly bring out as much of the RP2040 GPIO and internal circuitry function as possible, while also providing a suitable number of ground pins to reduce electro-magnetic interference (EMI) and signal crosstalk. RP2040 is built on a modern 40nm silicon process, so its digital I/O edge rates are very fast.

Raspberry Pi Pico W Datasheet

Figure 4. The pin numbering of the Pico W



NOTE

The physical pin numbering is shown in [Figure 4](#). For pin allocation see [Figure 2](#), or the full Pico W schematics in [Appendix B](#).

A few RP2040 GPIO pins are used for internal board functions:

GPIO29	OP/IP wireless SPI CLK/ADC mode (ADC3) to measure VSYS/3
GPIO25	OP wireless SPI CS - when high also enables GPIO29 ADC pin to read VSYS
GPIO24	OP/IP wireless SPI data/IRQ
GPIO23	OP wireless power on signal
WL_GPIO2	IP VBUS sense - high if VBUS is present, else low
WL_GPIO1	OP controls the on-board SMPS power save pin (Section 3.4)
WL_GPIO0	OP connected to user LED

Apart from GPIO and ground pins, there are seven other pins on the main 40-pin interface:

PIN40	VBUS
PIN39	VSYS
PIN37	3V3_EN
PIN36	3V3
PIN35	ADC_VREF
PIN33	AGND

Raspberry Pi Pico W Datasheet

PIN30 RUN

VBUS is the micro-USB input voltage, connected to micro-USB port pin 1. This is nominally 5V (or 0V if the USB is not connected or not powered).

VSYS is the main system input voltage, which can vary in the allowed range 1.8V to 5.5V, and is used by the on-board SMPS to generate the 3.3V for the RP2040 and its GPIO.

3V3_EN connects to the on-board SMPS enable pin, and is pulled high (to VSYS) via a 100kΩ resistor. To disable the 3.3V (which also de-powers the RP2040), short this pin low.

3V3 is the main 3.3V supply to RP2040 and its I/O, generated by the on-board SMPS. This pin can be used to power external circuitry (maximum output current will depend on RP2040 load and VSYS voltage; it is recommended to keep the load on this pin under 300mA).

ADC_VREF is the ADC power supply (and reference) voltage, and is generated on Pico W by filtering the 3.3V supply. This pin can be used with an external reference if better ADC performance is required.

AGND is the ground reference for GPIO26-29. There is a separate analogue ground plane running under these signals and terminating at this pin. If the ADC is not used or ADC performance is not critical, this pin can be connected to digital ground.

RUN is the RP2040 enable pin, and has an internal (on-chip) pull-up resistor to 3.3V of about ~50kΩ. To reset RP2040, short this pin low.

Finally, there are also six test points (TP1-TP6), which can be accessed if required, for example if using as a surface-mount module. These are:

TP1	Ground (close-coupled ground for differential USB signals)
TP2	USB DM
TP3	USB DP
TP4	WL_GPIO1/SMPS PS pin (do not use)
TP5	WL_GPIO0/LED (not recommended to be used)
TP6	BOOTSEL


TP1, TP2 and TP3 can be used to access USB signals instead of using the micro-USB port. TP6 can be used to drive the system into mass-storage USB programming mode (by shorting it low at power-up). Note that TP4 is not intended to be used externally, and TP5 is not really recommended to be used as it will only swing from 0V to the LED forward voltage (and hence can only really be used as an output with special care).

2.2. Surface-mount footprint

The following footprint ([Figure 5](#)) is recommended for systems which will be reflow-soldering Pico W units as modules.

Raspberry Pi Pico W Datasheet

Figure 5. The SMT footprint of the Pico W Rev3 board.




The footprint shows the test point locations and pad sizes as well as the 4 USB connector shell ground pads (A,B,C,D). The USB connector on Pico W is a through-hole part, which provides it with mechanical strength. The USB socket pins do not protrude all the way through the board, however solder does pool at these pads during manufacture and can stop the module sitting completely flat. Hence we provide pads on the SMT module footprint to allow this solder to reflow in a controlled manner when Pico W goes through reflow again.

For test points that are not used, it is acceptable to void any copper under these (with suitable clearance) on the carrier board.

Through trials with customers, we have determined that the paste stencil must be bigger than the footprint. Over-pasting the pads ensures the best possible results when soldering. The following paste stencil (Figure 6) indicates the dimensions of solder paste zones on the Pico W. We recommend paste zones 163% larger than the footprint.

Raspberry Pi Pico W Datasheet

Figure 6. The paste stencil of the Raspberry Pi Pico W Rev3 board.



Raspberry Pi Pico W Datasheet

2.2.1. Keep-out area


There is a cutout for the antenna (14mm × 9mm). If anything is placed close to the antenna (in any dimension) the effectiveness of the antenna is reduced. Raspberry Pi Pico W should be placed on the edge of a board and not enclosed in metal to avoid creating a Faraday cage. Adding ground to the sides of the antenna improves the performance slightly.

2.2. Surface-mount footprint

12

Raspberry Pi Pico W Datasheet

Figure 7. Surface-mount and through-hole footprint for attaching to Raspberry Pi Pico W



2.2. Surface-mount footprint

13

Raspberry Pi Pico W Datasheet

2.3. Recommended operating conditions

Operating conditions for the Pico W are largely a function of the operating conditions specified by its components.

Operating Temp Max	70°C (including self-heating)
Operating Temp Min	-20°C
VBUS	5V ± 10%.
VSYS Min	1.8V
VSYS Max	5.5V

Note that VBUS and VSYS current will depend on use-case, some examples are given in the next section.

Recommended maximum ambient temperature of operation is 70°C.

Chapter 3. Applications information

3.1. Programming the flash

The on-board 2MB QSPI flash can be (re)programmed either using the serial wire debug port or by the special USB mass storage device mode.

The simplest way to reprogram the Pico W's flash is to use the USB mode. To do this, power-down the board, then hold the BOOTSEL button down during board power-up (e.g. hold BOOTSEL down while connecting the USB). The Pico W will then appear as a USB mass storage device. Dragging a special '.uf2' file onto the disk will write this file to the flash and restart the Pico W.

The USB boot code is stored in ROM on RP2040, so can not be accidentally overwritten.

To get started using the SWD port see the [Debugging with SWD](#) section in the [Getting started with Raspberry Pi Pico-series](#) book.

3.2. General purpose I/O

The Pico W's GPIO is powered from the on-board 3.3V rail, and is fixed at 3.3V.

Pico W exposes 26 of the 30 possible RP2040 GPIO pins by routing them straight out to Pico W header pins. GPIO0 to GPIO22 are digital only, and GPIO 26-28 can be used either as digital GPIO or as ADC inputs (software selectable).

GPIO 26-29 are ADC-capable and have an internal reverse diode to the VDDIO (3.3V) rail, so the input voltage must not exceed VDDIO plus about 300mV. If the RP2040 is unpowered, applying a voltage to these GPIO pins will 'leak' through the diode into the VDDIO rail. GPIO pins 0-25 (and the debug pins) do not have this restriction and therefore voltage can safely be applied to these pins when RP2040 is unpowered up to 3.3V.

3.3. Using the ADC

The RP2040 ADC does not have an on-chip reference; it uses its own power supply as a reference. On Pico W the ADC_AVDD pin (the ADC supply) is generated from the SMPS 3.3V by using an R-C filter (201Ω into 2.2μF).

1. This solution relies on the 3.3V SMPS output accuracy
2. Some PSU noise will not be filtered
3. The ADC draws current (about 150μA if the temperature sense diode is disabled, which can vary between chips); there will be an inherent offset of about $150\mu\text{A} \times 200 = \sim 30\text{mV}$. There is a small difference in current draw when the ADC is sampling (about +20μA), so that offset will also vary with sampling as well as operating temperature.

Changing the resistance between the ADC_VREF and 3.3V pin can reduce the offset at the expense of more noise, which is helpful if the use case can support averaging over multiple samples.

Driving the SMPS mode pin (WL_GPIO1) high forces the power supply into PWM mode. This can greatly reduce the inherent ripple of the SMPS at light load, and therefore reduces the ripple on the ADC supply. This does reduce the power efficiency of the Pico W at light load, so at the end of an ADC conversion PFM mode can be re-enabled by driving WL_GPIO1 low once more. See [Section 3.4](#).

The ADC offset can be reduced by tying a second channel of the ADC to ground, and using this zero measurement as an approximation to the offset.

For much improved ADC performance, an external 3.0V shunt reference, such as LM4040, can be connected from the

ADC_VREF pin to ground. Note that if doing this the ADC range is limited to 0V - 3.0V signals (rather than 0V - 3.3V), and the shunt reference will draw continuous current through the 200Ω filter resistor $(3.3V - 3.0V)/200 = \sim 1.5mA$.


Note that the 1Ω resistor on Pico W (R9) is designed to help with shunt references that would otherwise become unstable when directly connected to 2.2μF. It also ensures there is filtering even in the case that 3.3V and ADC_VREF are shorted together (which users who are tolerant to noise and want to reduce the inherent offset may wish to do).

R7 is a physically large 1608 metric (0603) package resistor, so can be removed easily if a user wants to isolate ADC_VREF and make their own changes to the ADC voltage, for example powering it from an entirely separate voltage (e.g. 2.5V). Note that the ADC on RP2040 has only been qualified at 3.0/3.3V, but should work down to about 2V.

3.4. Powerchain

Pico W has been designed with a simple yet flexible power supply architecture and can easily be powered from other sources such as batteries or external supplies. Integrating the Pico W with external charging circuits is also straightforward. [Figure 8](#) shows the power supply circuitry.

Figure 8. The powerchain of the Pico W Rev3 board.



VBUS is the 5V input from the micro-USB port, which is fed through a Schottky diode to generate VSYS. The VBUS to VSYS diode (D1) adds flexibility by allowing power ORing of different supplies into VSYS.

VSYS is the main system 'input voltage' and feeds the RT6154 buck-boost SMPS, which generates a fixed 3.3V output for the RP2040 device and its I/O (and can be used to power external circuitry). VSYS divided by 3 (by R5, R6 in the Pico W schematic) and can be monitored on ADC channel 3 when a wireless transmission isn't in progress. This can be used for example as a crude battery voltage monitor.

The buck-boost SMPS, as its name implies, can seamlessly switch from buck to boost mode, and therefore can maintain an output voltage of 3.3V from a wide range of input voltages, ~1.8V to 5.5V, which allows a lot of flexibility in the choice of power source.

WL_GPIO2 monitors the existence of VBUS, while R10 and R1 act to pull VBUS down to make sure it is 0V if VBUS is not present.

WL_GPIO1 controls the RT6154 PS (power save) pin. When PS is low (the default on Pico W) the regulator is in pulse frequency modulation (PFM) mode, which, at light loads, saves considerable power by only turning on the switching MOSFETs occasionally to keep the output capacitor topped up. Setting PS high forces the regulator into pulse width modulation (PWM) mode. PWM mode forces the SMPS to switch continuously, which reduces the output ripple considerably at light loads (which can be good for some use cases) but at the expense of much worse efficiency. Note that under heavy load the SMPS will be in PWM mode irrespective of the PS pin state.

The SMPS EN pin is pulled up to VSYS by a 100kΩ resistor and made available on Pico W pin 37. Shorting this pin to ground will disable the SMPS and put it into a low power state.

NOTE

The RP2040 has an on-chip linear regulator (LDO) that powers the digital core at 1.1V (nominal) from the 3.3V supply, which is not shown in [Figure 8](#).

3.5. Powering Raspberry Pi Pico W

The simplest way to power Pico W is to plug in the micro-USB, which will power VSYS (and therefore the system) from the 5V USB VBUS voltage, via D1 (so VSYS becomes VBUS minus the Schottky diode drop).

If the USB port is the **only** power source, VSYS and VBUS can be safely shorted together to eliminate the Schottky diode drop (which improves efficiency and reduces ripple on VSYS).


If the USB port is **not** going to be used, it is safe to power Pico W by connecting VSYS to your preferred power source (in the range ~1.8V to 5.5V).

IMPORTANT

If you are using Pico W in USB host mode (e.g. using one of the TinyUSB host examples) then you must power Pico W by providing 5V to the VBUS pin.

The simplest way to safely add a second power source to Pico W is to feed it into VSYS via another Schottky diode (see [Figure 9](#)). This will 'OR' the two voltages, allowing the higher of either the external voltage or VBUS to power VSYS, with the diodes preventing either supply from back-powering the other. For example a single Lithium-Ion cell* (cell voltage ~3.0V to 4.2V) will work well, as will three AA series cells (~3.0V to ~4.8V) and any other fixed supply in the range ~2.3V to 5.5V. The downside of this approach is that the second power supply will suffer a diode drop in the same way as VBUS does, and this may not be desirable from an efficiency perspective or if the source is already close to the lower range of input voltage allowed for the RT6154.

Figure 9. Pico W power ORing using diodes.



An improved way to power from a second source is using a P-channel MOSFET (P-FET) to replace the Schottky diode as shown in [Figure 10](#). Here, the gate of the FET is controlled by VBUS, and will disconnect the secondary source when VBUS is present. The P-FET should be chosen to have low on resistance, and therefore overcomes the efficiency and


Raspberry Pi Pico W Datasheet

voltage-drop issues with the diode-only solution.

Note that the V_t (threshold voltage) of the P-FET must be chosen to be well below the minimum external input voltage, to make sure the P-FET is turned on swiftly and with low resistance. When the input VBUS is removed, the P-FET will not start to turn on until VBUS drops below the P-FET's V_t , meanwhile the body diode of the P-FET may start to conduct (depending on whether V_t is smaller than the diode drop). For inputs that have a low minimum input voltage, or if the P-FET gate is expected to change slowly (e.g. if any capacitance is added to VBUS) a secondary Schottky diode across the P-FET (in the same direction as the body diode) is recommended. This will reduce the voltage drop across the P-FET's body diode.

An example of a suitable P-MOSFET for most situations is Diodes DMG2305UX which has a maximum V_t of 0.9V and R_{on} of 100m Ω (at 2.5V V_{gs}).

Figure 10. Pico W power ORing using P-channel MOSFET.



CAUTION


If using Lithium-Ion cells they must have, or be provided with, adequate protection against over-discharge, over-charge, charging outside allowed temperature range, and overcurrent. Bare, unprotected cells are dangerous and can catch fire or explode if over-discharged, over-charged or charged / discharged outside their allowed temperature and/or current range.

3.6. Using a battery charger

Pico W can also be used with a battery charger. Although this is a slightly more complex use case it is still straightforward. Figure 11 shows an example of using a 'power path' type charger (where the charger seamlessly manages swapping between powering from battery or powering from the input source and charging the battery, as needed).

Raspberry Pi Pico W Datasheet

Figure 11. Using Pico W with a charger.



In the example we feed VBUS to the input of the charger, and we feed VSYS with the output via the previously mentioned P-FET arrangement. Depending on your use case you may also want to add a Schottky diode across the P-FET as described in the previous section.

3.7. USB

RP2040 has an integrated USB1.1 PHY and controller which can be used in both device and host mode. Pico W adds the two required 27Ω external resistors and brings this interface to a standard micro-USB port.

The USB port can be used to access the USB bootloader (BOOTSEL mode) stored in the RP2040 boot ROM. It can also be used by user code, to access an external USB device or host.

3.8. Wireless interface

Pico W contains an on-board 2.4GHz wireless interface using the Infineon CYW43439, which has the following features:

- WiFi 4 (802.11n), Single-band (2.4 GHz)
- WPA3
- SoftAP (Up to 4 clients)
- Bluetooth 5.2
 - Support for Bluetooth LE Central and Peripheral roles
 - Support for Bluetooth Classic

The antenna is an onboard antenna licensed from ABRACON (formerly ProAnt). The wireless interface is connected via SPI to the RP2040.

Due to pin limitations, some of the wireless interface pins are shared. The CLK is shared with VSYS monitor, so only when there isn't an SPI transaction in progress can VSYS be read via the ADC. The Infineon CYW43439 DIN/DOUT and IRQ all share one pin on the RP2040. Only when an SPI transaction isn't in progress is it suitable to check for IRQs. The

Raspberry Pi Pico W Datasheet

interface typically runs at 33MHz.

For best wireless performance, the antenna should be in free space. For instance, putting metal under or close by the antenna can reduce its performance both in terms of gain and bandwidth. Adding grounded metal to the sides of the antenna can improve the antenna's bandwidth.

There are three GPIO pins from the CYW43439 that are used for other board functions and can easily be accessed via the SDK:

WL_GPIO2

IP VBUS sense - high if VBUS is present, else low

WL_GPIO1

OP controls the on-board SMPS power save pin ([Section 3.4](#))

WL_GPIO0

OP connected to user LED

NOTE

Full details of the Infineon CYW43439 can be found on the [Infineon website](#).

3.9. Debugging

Pico W brings the RP2040 serial wire debug (SWD) interface to a three-pin debug header. To get started using the debug port see the [Debugging with SWD](#) section in the [Getting started with Raspberry Pi Pico-series](#) book.

NOTE

The RP2040 chip has internal pull-up resistors on the SWDIO and SWCLK pins, both nominally 60kΩ.

Appendix A: Availability

Raspberry Pi guarantee availability of the Raspberry Pi Pico W product until at least January 2028.

Support

For support see the [Pico section of the Raspberry Pi website](#), and post questions on [the Raspberry Pi forum](#).

Ordering code

Table 1. Part Number


Model	Order Code	EAN	Minimal Order Quantity	RRP
Raspberry Pi Pico W	SC0918	5056561803173	1+ pcs / Bulk	US\$6.00
Raspberry Pi Pico WH	SC0919	5056561800196	1+ pcs / Bulk	US\$7.00

NOTE

RRP was correct at time of publication and excludes taxes.


Appendix B: Pico W schematic

Figure 12. The Pico W Rev3 board schematic.




Raspberry Pi Pico W Datasheet

Figure 13. The Pico W Rev3 board schematic.



Appendix C: Pico W component locations

Figure 14. The Pico W Rev3 board component locations.



Documentation Release History

15 October 2024

- Corrected minor typos and formatting issues.
- Switched back to separate release histories per PDF.

02 May 2024

- Corrected minor typos and formatting issues.

02 Feb 2024

- Corrected minor typos and formatting issues.
- Updated ROSC register information.
- Updated to include the new recommended part number for crystals used with RP2040.
- Added new paste stencil information for Pico and Pico W.

14 Jun 2023

- Corrected minor typos and formatting issues.
- Updated instructions for the 1.5.1 release of the Raspberry Pi Pico C SDK.
- Added documentation around Bluetooth support for Raspberry Pi Pico W.

03 Mar 2023

- Corrected minor typos and formatting issues.
- Corrected SMT footprint of Raspberry Pi Pico W.
- Updated instructions for the 1.5.0 release of the Raspberry Pi Pico C SDK.
- Added errata [E15](#).
- Added package marking specifications.
- Added RP2040 baseline power consumption figures.
- Added antenna keep out diagram.

01 Dec 2022

- Corrected minor typos and formatting issues.
- Added RP2040 availability information.

Raspberry Pi Pico W Datasheet

- Added RP2040 storage conditions and thermal characteristics.
- Replaced SDK library documentation with links to the online version.
- Updated **picoprobe** build and usage instructions.

30 Jun 2022

- Initial release.
- Corrected minor typos and formatting issues.
- Update to VGA board hardware description for launch of Raspberry Pi Pico W.



Raspberry Pi is a trademark of Raspberry Pi Ltd

Raspberry Pi Ltd

A.2 Hoja de datos sensor BME280



BME280

Combined humidity and pressure sensor



BME280 – Data sheet

Document revision	1.24
Document release date	February 2024
Document number	BST-BME280-DS001-24
Sales Part Number (SPN)	0 273 141 185
Notes	Data and descriptions in this document are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product appearance

BME280**Digital humidity, pressure and temperature sensor****Key features**

- Package 2.5 mm x 2.5 mm x 0.93 mm metal lid LGA
- Digital interface I²C (up to 3.4 MHz) and SPI (3 and 4 wire, up to 10 MHz)
- Supply voltage V_{DD} main supply voltage range: 1.71 V to 3.6 V
V_{DDIO} interface voltage range: 1.2 V to 3.6 V
- Current consumption 1.8 µA @ 1 Hz humidity and temperature
2.8 µA @ 1 Hz pressure and temperature
3.6 µA @ 1 Hz humidity, pressure and temperature
0.1 µA in sleep mode
- Operating range -40...+85 °C, 0...100 % rel. humidity, 300...1100 hPa
- Humidity sensor and pressure sensor can be independently enabled / disabled
- Register and performance compatible to Bosch Sensortec BMP280 digital pressure sensor
- RoHS compliant, halogen-free, MSL1

Key parameters for humidity sensor

- Response time ($\tau_{63\%}$) 1 s
- Accuracy tolerance ± 3 % relative humidity
- Hysteresis ± 1 % relative humidity

Key parameters for pressure sensor

- RMS Noise 0.2 Pa, equiv. to 1.7 cm
- Offset temperature coefficient ± 1.5 Pa/K, equiv. to ± 12.6 cm at 1 °C temperature change

Typical application

- Context awareness, e.g. skin detection, room change detection
- Fitness monitoring / well-being
 - Warning regarding dryness or high temperatures
 - Measurement of volume and air flow
- Home automation control
 - control heating, venting, air conditioning (HVAC)
- Internet of things
- GPS enhancement (e.g. time-to-first-fix improvement, dead reckoning, slope detection)
- Indoor navigation (change of floor detection, elevator detection)
- Outdoor navigation, leisure and sports applications
- Weather forecast
- Vertical velocity indication (rise/sink speed)

Target devices

- Handsets such as mobile phones, tablet PCs, GPS devices
- Navigation systems
- Gaming, e.g. flying toys
- Camera (DSC, video)
- Home weather stations
- Flying toys
- Watches

General Description

The BME280 is as combined digital humidity, pressure and temperature sensor based on proven sensing principles. The sensor module is housed in an extremely compact metal-lid LGA package with a footprint of only $2.5 \times 2.5 \text{ mm}^2$ with a height of 0.93 mm. Its small dimensions and its low power consumption allow the implementation in battery driven devices such as handsets, GPS modules or watches. The BME280 is register and performance compatible to the Bosch Sensortec BMP280 digital pressure sensor (see chapter 5.2 for details).

The BME280 achieves high performance in all applications requiring humidity and pressure measurement. These emerging applications of home automation control, in-door navigation, fitness as well as GPS refinement require a high accuracy and a low TCO at the same time.

The humidity sensor provides an extremely fast response time for fast context awareness applications and high overall accuracy over a wide temperature range.

The pressure sensor is an absolute barometric pressure sensor with extremely high accuracy and resolution and drastically lower noise than the Bosch Sensortec BMP180.

The integrated temperature sensor has been optimized for lowest noise and highest resolution. Its output is used for temperature compensation of the pressure and humidity sensors and can also be used for estimation of the ambient temperature.

The sensor provides both SPI and I²C interfaces and can be supplied using 1.71 to 3.6 V for the sensor supply V_{DD} and 1.2 to 3.6 V for the interface supply V_{DDIO} . Measurements can be triggered by the host or performed in regular intervals. When the sensor is disabled, current consumption drops to 0.1 μA .

BME280 can be operated in three power modes (see chapter 3.3):

- sleep mode
- normal mode
- forced mode

In order to tailor data rate, noise, response time and current consumption to the needs of the user, a variety of oversampling modes, filter modes and data rates can be selected.

Please contact your regional Bosch Sensortec partner for more information about software packages.

Index of Contents

1. Specification	8
1.1 General electrical specification.....	8
1.2 Humidity parameter specification	9
1.3 Pressure sensor specification.....	10
1.4 Temperature sensor specification.....	11
2. Absolute maximum ratings	13
3. Functional description	14
3.1 Block diagram	14
3.2 Power management	14
3.3 Sensor modes.....	14
3.3.1 Sensor mode transitions	15
3.3.2 Sleep mode.....	15
3.3.3 Forced mode.....	15
3.3.4 Normal mode	16
3.4 Measurement flow	17
3.4.1 Humidity measurement.....	17
3.4.2 Pressure measurement	17
3.4.3 Temperature measurement	17
3.4.4 IIR filter.....	18
3.5 Recommended modes of operation	19
3.5.1 Weather monitoring	19
3.5.2 Humidity sensing	19
3.5.3 Indoor navigation	20
3.5.4 Gaming	20
3.6 Noise.....	21
4. Data readout.....	23
4.1 Data register shadowing.....	23

4.2	Output compensation	23
4.2.1	Computational requirements	23
4.2.2	Trimming parameter readout	24
4.2.3	Compensation formulas	25
5.	Global memory map and register description	26
5.1	General remarks	26
5.2	Register compatibility to BMP280	26
5.3	Memory map	26
5.4	Register description	27
5.4.1	Register 0xD0 "id"	27
5.4.2	Register 0xE0 "reset"	27
5.4.3	Register 0xF2 "ctrl_hum"	27
5.4.4	Register 0xF3 "status"	28
5.4.5	Register 0xF4 "ctrl_meas"	28
5.4.6	Register 0xF5 "config"	30
5.4.7	Register 0xF7...0xF9 "press" (_msb, _lsb, _xlsb)	30
5.4.8	Register 0xFA...0xFC "temp" (_msb, _lsb, _xlsb)	31
5.4.9	Register 0xFD...0xFE "hum" (_msb, _lsb)	31
6.	Digital interfaces	32
6.1	Interface selection	32
6.2	I ² C Interface	32
6.2.1	I ² C write	33
6.2.2	I ² C read	33
6.3	SPI interface	34
6.3.1	SPI write	34
6.3.2	SPI read	35
6.4	Interface parameter specification	35
6.4.1	General interface parameters	35
6.4.2	I ² C timings	35
6.4.3	SPI timings	36

7. Pin-out and connection diagram	38
7.1 Pin-out	38
7.2 Connection diagram I ² C.....	39
7.3 Connection diagram 4-wire SPI.....	40
7.4 Connection diagram 3-wire SPI.....	41
7.5 Package dimensions	42
7.6 Landing pattern recommendation.....	43
7.7 Marking	44
7.7.1 Mass production devices	44
7.7.2 Engineering samples	44
7.8 Soldering guidelines and reconditioning recommendations	45
7.9 Reconditioning Procedure	46
7.10 Tape and reel specification	46
7.10.1 Dimensions	46
7.10.2 Orientation within the reel	47
7.11 Mounting and assembly recommendations	48
7.12 Environmental safety	48
7.12.1 RoHS	48
7.12.2 Halogen content.....	48
7.12.3 Internal package structure	48
8. Appendix A: Alternative compensation formulas	49
8.1 Compensation formulas in double precision floating point.....	49
8.2 Pressure compensation in 32 bit fixed point.....	50
9. Appendix B: Measurement time and current calculation.....	51
9.1 Measurement time	51
9.2 Measurement rate in forced mode	51
9.3 Measurement rate in normal mode.....	51
9.4 Response time using IIR filter.....	52

9.5 Current consumption	52
10. Self test.....	53
10.1 Self-test flow	53
10.2 Function return codes	54
10.3 Usage	55
10.3.1 File and function pointer integration	55
10.3.2 Function call.....	55
10.3.3 Test time and interface requirements	55
10.4 Function explanation	56
10.4.1 Communication test	56
10.4.2 Bond wire test	56
10.4.3 Measurement plausibility test	56
10.5 Sample read, write and delay function	57
11. Legal disclaimer	58
11.1 Engineering samples	58
11.2 Product use.....	58
11.3 Application examples and hints	58
12. Document history and modification	59

1. Specification

If not stated otherwise,

- All values are valid over the full voltage range
- All minimum/maximum values are given for the full accuracy temperature range
- Minimum/maximum values of drifts, offsets and temperature coefficients are $\pm 3\sigma$ values over lifetime
- Typical values of drifts, offsets and temperature coefficients are $\pm 1\sigma$ values over lifetime
- Typical values of currents and state machine timings are determined at 25 °C
- Minimum/maximum values of currents are determined using corner lots over complete temperature range
- Minimum/maximum values of state machine timings are determined using corner lots over 0...+65 °C temperature range

The specification tables are split into humidity, pressure, and temperature part of BME280.

1.1 General electrical specification

Table 1: Electrical parameter specification

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage Internal Domains	V _{DD}	ripple max. 50 mVpp	1.71	1.8	3.6	V
Supply Voltage I/O Domain	V _{DDIO}		1.2	1.8	3.6	V
Sleep current	I _{DDSL}			0.1	0.3	μA
Standby current (inactive period of normal mode)	I _{DDSB}			0.2	0.5	μA
Current during humidity measurement	I _{DDH}	Max value at 85 °C		340		μA
Current during pressure measurement	I _{DDP}	Max value at -40 °C		714		μA
Current during temperature measurement	I _{DDT}	Max value at 85 °C		350		μA
Start-up time	t _{startup}	Time to first communication after both V _{DD} > 1.58 V and V _{DDIO} > 0.65 V			2	ms
Power supply rejection ratio (DC)	PSRR	full V _{DD} range			±0.01 ±5	%RH/V Pa/V
Standby time accuracy	Δt _{standby}			±5	±25	%

1.2 Humidity parameter specification

Table 2: Humidity parameter specification

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Operating range ¹	RH	For temperatures < 0 °C and > 60 °C see Figure 1	-40	25	85	°C
			0		100	%RH
Supply current	I _{DD,H}	1 Hz forced mode, humidity and temperature		1.8	2.8	µA
Absolute accuracy tolerance	A _H	20...80 %RH, 25 °C, including hysteresis		±3		%RH
Hysteresis ²	H _H	10→90→10 %RH, 25 °C		±1		%RH
Nonlinearity ³	NL _H	10→90 %RH, 25 °C		1		%RH
Response time to complete 63% of step ⁴	τ _{63%}	90→0 or 0→90 %RH, 25 °C		1		s
Resolution	R _H			0.008		%RH
Noise in humidity (RMS)	N _H	Highest oversampling, see chapter 3.6		0.02		%RH
Long term stability	ΔH _{stab}	10...90 %RH, 25 °C		0.5		%RH/ year

¹ When exceeding the operating range (e.g. for soldering), humidity sensing performance is temporarily degraded and reconditioning is recommended as described in section 7.8. Operating range only for non-condensing environment.

² For hysteresis measurement the sequence 10→30→50→70→90→70→50→30→10 %RH is used. The hysteresis is defined as the difference between measurements of the humidity up / down branch and the averaged curve of both branches

³ Non-linear contributions to the sensor data are corrected during the calculation of the relative humidity by the compensation formulas described in section 4.2.3.

⁴ The air-flow in direction to the vent-hole of the device has to be dimensioned in a way that a sufficient air exchange inside to outside will be possible. To observe effects on the response time-scale of the device an air-flow velocity of approx. 1 m/s is needed.




Figure 1: humidity sensor operating range

1.3 Pressure sensor specification

Table 3: Pressure parameter specification

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Operating temperature range	T_A	operational	-40	25	+85	°C
		full accuracy	0		+65	
Operating pressure range	P	full accuracy	300		1100	hPa
Supply current	$I_{DD,LP}$	1 Hz forced mode, pressure and temperature, lowest power		2.8	4.2	μA

Temperature coefficient of offset ⁵	TCO _P	25...65 °C, 900 hPa		±1.5		Pa/K
				±12.6		cm/K
Absolute accuracy pressure	A ^P _{ext}	300 . . 1100 hPa -20 . . . 0 °C		±1.7		hPa
	A _{P,full}	300 . . . 1100 hPa 0 . . . 65 °C		±1.0		hPa
	A ^P	1100 . . . 1250 hPa 25 . . . 40 °C		±1.5		hPa
Relative accuracy pressure V _{DD} = 3.3V	A _{rel}	700 ... 900hPa 25 . . . 40 °C		±0.12		hPa
Resolution of pressure output data	R _P	Highest oversampling		0.18		Pa
Noise in pressure	N _{P,fullBW}	Full bandwidth, highest oversampling See chapter 3.6		1.3		Pa
				11		cm
	N _{P,filtered}	Reduced bandwidth, highest oversampling See chapter 3.6		0.2		Pa
				1.7		cm
Solder drift		Minimum solder height 50µm	-0.5		+2.0	hPa
Long term stability ⁶	ΔP _{stab}	per year		±1.0		hPa
Possible sampling rate	f _{sample_P}	Lowest oversampling, see chapter 9.2	157	182		Hz

1.4 Temperature sensor specification

Table 4: Temperature parameter specification

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Operating range	T	Operational	-40	25	85	°C
		Full accuracy	0		65	°C
Supply current	I _{DD,T}	1 Hz forced mode, temperature measurement only		1.0		µA
	A _{T,25}	25 °C		±0.5		°C

⁵ When changing temperature by e.g. 10 °C at constant pressure / altitude, the measured pressure / altitude will change by (10 × TCO_P).

⁶ Long term stability is specified in the full accuracy operating pressure range 0 ... 65 °C

Absolute accuracy temperature ⁷	$A_{T,full}$	0...65 °C		±0.5		°C
	$A_{T,ext}$ ⁸	-20 0 °C		±1.25		°C
	$A_{T,ext}$ ⁹	-40 ... -20 °C		±1.5		°C
Output resolution	R_T	API output resolution		0.01		°C
RMS noise	N_T	Lowest oversampling		0.005		°C

⁷ Temperature measured by the internal temperature sensor. This temperature value depends on the PCB temperature, sensor element self-heating and ambient temperature and is typically above ambient temperature.

⁸ Target values & not guaranteed

⁹ Target values & not guaranteed

2. Absolute maximum ratings

The absolute maximum ratings are determined over complete temperature range using corner lots. The values are provided in Table 5.

Table 5: Absolute maximum ratings

Parameter	Condition	Min	Max	Unit
Voltage at any supply pin	V_{DD} and V_{DDIO} pin	-0.3	4.25	V
Voltage at any interface pin		-0.3	$V_{DDIO} + 0.3$	V
Storage temperature	$\leq 65\%$ RH	-45	+85	°C
Pressure		0	20 000	hPa
ESD	HBM, at any pin		± 2	kV
	CDM		± 500	V
	Machine model		± 200	V

3. Functional description

3.1 Block diagram

Figure 2 shows a simplified block diagram of the BME280:




Figure 2: Block diagram of BME280

3.2 Power management

The BME280 has two distinct power supply pins

- V_{DD} is the main power supply for all internal analog and digital functional blocks
- V_{DDIO} is a separate power supply pin used for the supply of the digital interface

A power-on reset (POR) generator is built in; it resets the logic part and the register values after both V_{DD} and V_{DDIO} reach their minimum levels. There are no limitations on slope and sequence of raising the V_{DD} and V_{DDIO} levels. After powering up, the sensor settles in sleep mode (described in chapter 3.3.2).

It is prohibited to keep any interface pin (SDI, SDO, SCK or CSB) at a logical high level when V_{DDIO} is switched off. Such a configuration can permanently damage the device due an excessive current flow through the ESD protection diodes.

If V_{DDIO} is supplied, but V_{DD} is not, the interface pins are kept at a high-Z level. The bus can therefore already be used freely before the BME280 V_{DD} supply is established.

Resetting the sensor is possible by cycling V_{DD} level or by writing a soft reset command. Cycling the V_{DDIO} level will not cause a reset.

3.3 Sensor modes

The BME280 offers three sensor modes: sleep mode, forced mode and normal mode. These can be selected using the *mode*[1:0] setting (see chapter 5.4.5). The available modes are:

- Sleep mode: no operation, all registers accessible, lowest power, selected after startup
- Forced mode: perform one measurement, store results and return to sleep mode
- Normal mode: perpetual cycling of measurements and inactive periods.

The modes will be explained in detail in chapters 3.3.2 (sleep mode), 3.3.3 (forced mode) and 3.3.4 (normal mode).

3.3.1 Sensor mode transitions

The supported mode transitions are shown in Figure 3. If the device is currently performing a measurement, execution of mode switching commands is delayed until the end of the currently running measurement period. Further mode change commands or other write commands to the register *ctrl_hum* are ignored until the mode change command has been executed. Mode transitions other than the ones shown below are tested for stability but do not represent recommended use of the device.




Figure 3: Sensor mode transition diagram

3.3.2 Sleep mode

Sleep mode is entered by default after power on reset. In sleep mode, no measurements are performed and power consumption (I_{DDSM}) is at a minimum. All registers are accessible; Chip-ID and compensation coefficients can be read. There are no special restrictions on interface timings.

3.3.3 Forced mode

In forced mode, a single measurement is performed in accordance to the selected measurement and filter options. When the measurement is finished, the sensor returns to sleep mode and the measurement results can be obtained from the data registers. For a next measurement, forced mode needs to be selected again. This is similar to BMP180 operation. Using forced mode is recommended for applications which require low sampling rate or host-based synchronization. The timing diagram is shown below.




Figure 4: Forced mode timing diagram

3.3.4 Normal mode

Normal mode comprises an automated perpetual cycling between an (active) measurement period and an (inactive) standby period.

The measurements are performed in accordance to the selected measurement and filter options. The standby time is determined by the setting $t_{sb}[2:0]$ and can be set to between 0.5 and 1000 ms according to Table 27.

The total cycle time depends on the sum of the active time (see chapter 9) and standby time $t_{standby}$.

The current in the standby period (I_{DDSB}) is slightly higher than in sleep mode. After setting the measurement and filter options and enabling normal mode, the last measurement results can always be obtained at the data registers without the need of further write accesses.

Using normal mode is recommended when using the IIR filter. This is useful for applications in which short-term disturbances (e.g. blowing into the sensor) should be filtered. The timing diagram is shown below:




Figure 5: Normal mode timing diagram

3.4 Measurement flow

The BME280 measurement period consists of a temperature, pressure and humidity measurement with selectable oversampling. After the measurement period, the pressure and temperature data can be passed through an optional IIR filter, which removes short-term fluctuations in pressure (e.g. caused by slamming a door). For humidity, such a filter is not needed and has not been implemented. The flow is depicted in the diagram below.




Figure 6: BME280 measurement cycle

The individual blocks of the diagram above will be detailed in the following subchapters.

3.4.1 Humidity measurement

The humidity measurement can be enabled or skipped. When enabled, several oversampling options exist. The humidity measurement is controlled by the *osrs_h[2:0]* setting, which is detailed in chapter 5.4.3. For the humidity measurement, oversampling is possible to reduce the noise. The resolution of the humidity measurement is fixed at 16 bit ADC output.

3.4.2 Pressure measurement

Pressure measurement can be enabled or skipped. When enabled, several oversampling options exist. The pressure measurement is controlled by the *osrs_p[2:0]* setting which is detailed in chapter 5.4.5. For the pressure measurement, oversampling is possible to reduce the noise. The resolution of the pressure data depends on the IIR filter (see chapter 3.4.4) and the oversampling setting (see chapter 5.4.5):

- When the IIR filter is enabled, the pressure resolution is 20 bit.
- When the IIR filter is disabled, the pressure resolution is $16 + (osrs_p - 1)$ bit, e.g. 18 bit when *osrs_p* is set to '3'.

3.4.3 Temperature measurement

Temperature measurement can be enabled or skipped. Skipping the measurement could be useful to measure pressure extremely rapidly. When enabled, several oversampling options exist. The temperature measurement is controlled by the *osrs_t[2:0]* setting which is detailed in chapter 5.4.5. For the temperature measurement, oversampling is possible to reduce the noise.

The resolution of the temperature data depends on the IIR filter (see chapter 3.4.4) and the oversampling setting (see chapter 5.4.5):

- When the IIR filter is enabled, the temperature resolution is 20 bit.

- When the IIR filter is disabled, the temperature resolution is $16 + (osrs_t - 1)$ bit, e.g. 18 bit when $osrs_t$ is set to '3'.

3.4.4 IIR filter

The humidity value inside the sensor does not fluctuate rapidly and does not require low pass filtering. However, the environmental pressure is subject to many short-term changes, caused e.g. by slamming of a door or window, or wind blowing into the sensor. To suppress these disturbances in the output data without causing additional interface traffic and processor work load, the BME280 features an internal IIR filter. It effectively reduces the bandwidth of the temperature and pressure output signals¹⁰ and increases the resolution of the pressure and temperature output data to 20 bit. The output of a next measurement step is filtered using the following formula:

$$data_filtered = \frac{data_filtered_old \cdot (filter_coefficient - 1) + data_ADC}{filter_coefficient}$$

Data_filtered_old is the data coming from the current filter memory, and data_ADC is the data coming from current ADC acquisition. Data_filtered is the new value of filter memory and the value that will be sent to the output registers.

The IIR filter can be configured to different filter coefficients, which slows down the response to the sensor inputs. Note that the response time with enabled IIR filter depends on the number of samples generated, which means that the data output rate must be known to calculate the actual response time. For register configuration, please refer to Table 28. A sample response time calculation is shown in chapter 9.4.

Table 6: *filter* settings

Filter coefficient	Samples to reach ≥75 % of step response
Filter off	1
2	2
4	5
8	11
16	22

In order to find a suitable setting for *filter*, please consult chapter 3.5.

When writing to the register *filter*, the filter is reset. The next ADC values will pass through the filter unchanged and become the initial memory values for the filter. If temperature or pressure measurements are skipped, the corresponding filter memory will be kept unchanged even though the output registers are set to 0x80000. When the previously skipped measurement is re-enabled, the output will be filtered using the filter memory from the last time when the measurement was not skipped. If this is not desired, please write to the *filter* register in order to re-initialize the filter.

¹⁰ Since the BME280 does not sample continuously, filtering can suffer from signals with a frequency higher than the sampling rate of the sensor. E.g. environmental fluctuations caused by windows being opened and closed might have a frequency <5 Hz. Consequently, a sampling rate of ODR = 10 Hz is sufficient to obey the Nyquist theorem.

The step response (e.g. response to a sudden change in height) of the different filter settings is displayed in Figure 7.




Figure 7: Step response at different IIR filter settings

3.5 Recommended modes of operation

The different oversampling options, filter settings and sensor modes result in a large number of possible settings. In this chapter, a number of settings recommended for various scenarios are presented.

3.5.1 Weather monitoring

Description: Only a very low data rate is needed. Power consumption is minimal. Noise of pressure values is of no concern. Humidity, pressure and temperature are monitored.

Table 7: Settings and performance for weather monitoring

Suggested settings for weather monitoring	
Sensor mode	forced mode, 1 sample / minute
Oversampling settings	pressure ×1, temperature ×1, humidity ×1
IIR filter settings	filter off
Performance for suggested settings	
Current consumption	0.16 µA
RMS Noise	3.3 Pa / 30 cm, 0.07 %RH
Data output rate	1/60 Hz

3.5.2 Humidity sensing

Description: A low data rate is needed. Power consumption is minimal. Forced mode is used to minimize power consumption and to synchronize readout, but using normal mode would also be possible.

Table 8: Settings and performance for humidity sensing

Suggested settings for weather monitoring	
Sensor mode	forced mode, 1 sample / second
Oversampling settings	pressure ×0, temperature ×1, humidity ×1
IIR filter settings	filter off
Performance for suggested settings	
Current consumption	2.9 µA
RMS Noise	0.07 %RH
Data output rate	1 Hz

3.5.3 Indoor navigation

Lowest possible altitude noise is needed. A very low bandwidth is preferred. Increased power consumption is tolerated. Humidity is measured to help detect room changes. This setting is suggested for the Android settings 'SENSOR_DELAY_NORMAL' and 'SENSOR_DELAY_UI'.

Table 9: Settings and performance for indoor navigation

Suggested settings for indoor navigation	
Sensor mode	normal mode, $t_{\text{standby}} = 0.5 \text{ ms}$
Oversampling settings	pressure ×16, temperature ×2, humidity ×1
IIR filter settings	filter coefficient 16
Performance for suggested settings	
Current consumption	633 µA
RMS Noise	0.2 Pa / 1.7 cm
Data output rate	25Hz
Filter bandwidth	0.53 Hz
Response time (75%)	0.9 s

3.5.4 Gaming

Low altitude noise is needed. The required bandwidth is ~2 Hz in order to respond quickly to altitude changes (e.g. be able to dodge a flying monster in a game). Increased power consumption is tolerated. Humidity sensor is disabled. This setting is suggested for the Android settings 'SENSOR_DELAY_GAMING' and 'SENSOR_DELAY_FASTEST'.

Table 10: Settings and performance for gaming

Suggested settings for gaming	
Sensor mode	normal mode, $t_{\text{standby}} = 0.5 \text{ ms}$
Oversampling settings	pressure $\times 4$, temperature $\times 1$, humidity $\times 0$
IIR filter settings	filter coefficient 16
Performance for suggested settings	
Current consumption	581 μA
RMS Noise	0.3 Pa / 2.5 cm
Data output rate	83 Hz
Filter bandwidth	1.75 Hz
Response time (75%)	0.3 s

3.6 Noise

The noise depends on the oversampling and, for pressure and temperature, on the filter setting used. The stated values were determined in a controlled environment and are based on the average standard deviation of 32 consecutive measurement points taken at highest sampling speed. This is needed in order to exclude long term drifts from the noise measurement. The noise depends both on humidity/pressure oversampling and temperature oversampling, since the temperature value is used for humidity/pressure temperature compensation. The oversampling combinations use below results in an optimal power to noise ratio.

Table 11: Noise and current for humidity

Humidity / temperature oversampling setting	Typical RMS noise in humidity [%RH] at 25 °C	Typ. current [μA] at 1 Hz forced mode, 25 °C, humidity and temperature measurement, incl. I_{DDSM}
$\times 1 / \times 1$	0.07	1.8
$\times 2 / \times 1$	0.05	2.5
$\times 4 / \times 1$	0.04	3.8
$\times 8 / \times 1$	0.03	6.5
$\times 16 / \times 1$	0.02	11.7

Table 12: Noise and current for pressure

Typical RMS noise in pressure [Pa] at 25 °C						Typ. current [μA] at 1 Hz forced mode, 25 °C, pressure and temperature measurement, incl. I _{DDSM}
Pressure / temperature oversampling setting	IIR filter coefficient					
	off	2	4	8	16	
×1 / ×1	3.3	1.9	1.2	0.9	0.4	2.8
×2 / ×1	2.6	1.5	1.0	0.6	0.4	4.2
×4 / ×1	2.1	1.2	0.8	0.5	0.3	7.1
×8 / ×1	1.6	1.0	0.6	0.4	0.2	12.8
×16 / ×2	1.3	0.8	0.5	0.4	0.2	24.9

Table 13: Temperature dependence of pressure noise

RMS noise at different temperatures	
Temperature	Typical change in noise compared to 25 °C
-10 °C	+25 %
25 °C	±0 %
75 °C	-5 %

Table 14: Noise in temperature

Temperature oversampling setting	Typical RMS noise in temperature [°C] at 25 °C
×1	0.005
×2	0.004
×4	0.003
×8	0.003
×16	0.002

4. Data readout

To read out data after a conversion, it is strongly recommended to use a burst read and not address every register individually. This will prevent a possible mix-up of bytes belonging to different measurements and reduce interface traffic. Note that in I²C mode, even when pressure was not measured, reading the unused registers is faster than reading temperature and humidity data separately.

Data readout is done by starting a burst read from 0xF7 to 0xFC (temperature and pressure) or from 0xF7 to 0xFE (temperature, pressure and humidity). The data are read out in an unsigned 20-bit format both for pressure and for temperature and in an unsigned 16-bit format for humidity. It is strongly recommended to use the BME280 API, available from Bosch Sensortec, for readout and compensation. For details on memory map and interfaces, please consult chapters 5 and 6 respectively.

After the uncompensated values for pressure, temperature and humidity 'ut', 'up' and 'uh' have been read, the actual humidity, pressure and temperature needs to be calculated using the compensation parameters stored in the device. The procedure is elaborated in chapter 4.2.

4.1 Data register shadowing

In normal mode, the timing of measurements is not necessarily synchronized to the readout by the user. This means that new measurement results may become available while the user is reading the results from the previous measurement. In this case, shadowing is performed in order to guarantee data consistency. Shadowing will only work if all data registers are read in a single burst read. Therefore, the user must use burst reads if he does not synchronize data readout with the measurement cycle. Using several independent read commands may result in inconsistent data. If a new measurement is finished and the data registers are still being read, the new measurement results are transferred into shadow data registers. The content of shadow registers is transferred into data registers as soon as the user ends the burst read, even if not all data registers were read. The end of the burst read is marked by the rising edge of CSB pin in SPI case or by the recognition of a stop condition in I²C case. After the end of the burst read, all user data registers are updated at once.

4.2 Output compensation

The BME280 output consists of the ADC output values. However, each sensing element behaves differently. Therefore, the actual pressure and temperature must be calculated using a set of calibration parameters. In this chapter, the method to read out the trimming values will be given. The recommended calculation uses fixed point arithmetic and is given in chapter 4.2.3.

In high-level languages like Matlab™ or LabVIEW™, fixed-point code may not be well supported. In this case the floating-point code in appendix 8.1 can be used as an alternative.

For 8-bit micro controllers, the variable size may be limited. In this case a simplified 32 bit integer code with reduced accuracy is given in appendix 8.2.

4.2.1 Computational requirements

In the table below an overview is given for the number of clock cycles needed for compensation on a 32 bit Cortex-M3 micro controller with GCC optimization level -O2. This controller does not feature a floating point unit, thus all floating-point calculations are emulated. Floating point is only recommended for PC application, where an FPU is present and these calculations are performed drastically faster.

Table 15: Computational requirements for compensation formulas

Compensation of	Number of clocks (ARM Cortex-M3)		
	32 bit integer	64 bit integer	Double precision
Humidity	~83	–	~2900 ¹¹
Temperature	~46	–	~2400 ¹¹
Pressure	~112 ¹²	~1400	~5400 ¹¹

4.2.2 Trimming parameter readout

The trimming parameters are programmed into the devices' non-volatile memory (NVM) during production and cannot be altered by the customer. Each compensation word is a 16-bit signed or unsigned integer value stored in two's complement. As the memory is organized into 8-bit words, two words must always be combined in order to represent the compensation word. The 8-bit registers are named calib00...calib41 and are stored at memory addresses 0x88...0xA1 and 0xE1...0xE7. The corresponding compensation words are named dig_T# for temperature compensation related values, dig_P# for pressure related values and dig_H# for humidity related values. The mapping is seen in Table 16.

Table 16: Compensation parameter storage, naming and data type

Register Address	Register content	Data type
0x88 / 0x89	dig_T1 [7:0] / [15:8]	unsigned short
0x8A / 0x8B	dig_T2 [7:0] / [15:8]	signed short
0x8C / 0x8D	dig_T3 [7:0] / [15:8]	signed short
0x8E / 0x8F	dig_P1 [7:0] / [15:8]	unsigned short
0x90 / 0x91	dig_P2 [7:0] / [15:8]	signed short
0x92 / 0x93	dig_P3 [7:0] / [15:8]	signed short
0x94 / 0x95	dig_P4 [7:0] / [15:8]	signed short
0x96 / 0x97	dig_P5 [7:0] / [15:8]	signed short
0x98 / 0x99	dig_P6 [7:0] / [15:8]	signed short
0x9A / 0x9B	dig_P7 [7:0] / [15:8]	signed short
0x9C / 0x9D	dig_P8 [7:0] / [15:8]	signed short
0x9E / 0x9F	dig_P9 [7:0] / [15:8]	signed short
0xA1	dig_H1 [7:0]	unsigned char
0xE1 / 0xE2	dig_H2 [7:0] / [15:8]	signed short
0xE3	dig_H3 [7:0]	unsigned char
0xE4 / 0xE5[3:0]	dig_H4 [11:4] / [3:0]	signed short
0xE5[7:4] / 0xE6	dig_H5 [3:0] / [11:4]	signed short

¹¹ Use only recommended for high-level programming languages like Matlab™ or LabVIEW™

¹² Use only recommended for 8-bit micro controllers

0xE7

dig_H6

signed char

4.2.3 Compensation formulas

Please note that it is strongly advised to use the API available from Bosch Sensortec to perform readout and compensation. If this is not wanted, the code below can be applied at the user's risk. Both pressure and temperature values are expected to be received in 20 bit format, positive, stored in a 32 bit signed integer. Humidity is expected to be received in 16 bit format, positive, stored in a 32 bit signed integer.

The variable `t_fine` (signed 32 bit) carries a fine resolution temperature value over to the pressure and humidity compensation formula and could be implemented as a global variable.

The data type "BME280_S32_t" should define a 32 bit signed integer variable type and can usually be defined as "long signed int".

The data type "BME280_U32_t" should define a 32 bit unsigned integer variable type and can usually be defined as "long unsigned int".

For best possible calculation accuracy in pressure, 64 bit integer support is needed. If this is not possible on your platform, please see appendix 8.2 for a 32 bit alternative.

The data type "BME280_S64_t" should define a 64 bit signed integer variable type, which on most supporting platforms can be defined as "long long signed int". The revision of the code is rev.1.1.

```
// Returns temperature in DegC, resolution is 0.01 DegC. Output value of "5123" equals 51.23
DegC.
// t_fine carries fine temperature as global value
BME280_S32_t t_fine;
BME280_S32_t BME280_compensate_T_int32(BME280_S32_t adc_T)
{
    BME280_S32_t var1, var2, T;
    var1 = (((adc_T >> 3) - ((BME280_S32_t)dig_T1 << 1))) * ((BME280_S32_t)dig_T2) >> 11;
    var2 = (((adc_T >> 4) - ((BME280_S32_t)dig_T1)) * ((adc_T >> 4) - ((BME280_S32_t)dig_T1))
    >> 12) *
        ((BME280_S32_t)dig_T3) >> 14;
    t_fine = var1 + var2;
    T = (t_fine * 5 + 128) >> 8;
    return T;
}

// Returns pressure in Pa as unsigned 32 bit integer in Q24.8 format (24 integer bits and 8
fractional bits).
// Output value of "24674867" represents 24674867/256 = 96386.2 Pa = 963.862 hPa
BME280_U32_t BME280_compensate_P_int64(BME280_S32_t adc_P)
{
    BME280_S64_t var1, var2, p;
    var1 = ((BME280_S64_t)t_fine) - 128000;
    var2 = var1 * var1 * (BME280_S64_t)dig_P6;
    var2 = var2 + ((var1 * (BME280_S64_t)dig_P5) << 17);
    var2 = var2 + (((BME280_S64_t)dig_P4) << 35);
    var1 = ((var1 * var1 * (BME280_S64_t)dig_P3) >> 8) + ((var1 * (BME280_S64_t)dig_P2) << 12);
    var1 = (((((BME280_S64_t)1) << 47) + var1)) * ((BME280_S64_t)dig_P1) >> 33;
    if (var1 == 0)
    {
        return 0; // avoid exception caused by division by zero
    }
    p = 1048576 - adc_P;
    p = (((p << 31) - var2) * 3125) / var1;
    var1 = (((BME280_S64_t)dig_P9) * (p >> 13) * (p >> 13)) >> 25;
    var2 = (((BME280_S64_t)dig_P8) * p) >> 19;
    p = ((p + var1 + var2) >> 8) + (((BME280_S64_t)dig_P7) << 4);
    return (BME280_U32_t)p;
}

// Returns humidity in %RH as unsigned 32 bit integer in Q22.10 format (22 integer and 10
fractional bits).
// Output value of "47445" represents 47445/1024 = 46.333 %RH
BME280_U32_t BME280_compensate_H_int32(BME280_S32_t adc_H)
{
    BME280_S32_t v_x1_u32r;

    v_x1_u32r = (t_fine - ((BME280_S32_t)76800));
```

```

v_x1_u32r = (((((adc_H << 14) - (((BME280_S32_t)dig_H4) << 20) - (((BME280_S32_t)dig_H5) *
v_x1_u32r)) + (((BME280_S32_t)16384)) >> 15) * ((((((v_x1_u32r *
(BME280_S32_t)dig_H6)) >> 10) * (((v_x1_u32r * ((BME280_S32_t)dig_H3)) >> 11) +
((BME280_S32_t)32768))) >> 10) + ((BME280_S32_t)2097152)) * ((BME280_S32_t)dig_H2) +
8192) >> 14));
v_x1_u32r = (v_x1_u32r - (((((v_x1_u32r >> 15) * (v_x1_u32r >> 15)) >> 7) *
(BME280_S32_t)dig_H1)) >> 4));
v_x1_u32r = (v_x1_u32r < 0 ? 0 : v_x1_u32r);
v_x1_u32r = (v_x1_u32r > 419430400 ? 419430400 : v_x1_u32r);
return (BME280_U32_t)(v_x1_u32r>>12);
}

```

5. Global memory map and register description

5.1 General remarks

The entire communication with the device is performed by reading from and writing to registers. Registers have a width of 8 bits. There are several registers which are reserved; they should not be written to and no specific value is guaranteed when they are read. For details on the interface, consult chapter 6.

5.2 Register compatibility to BMP280

The BME280 is downward register compatible to the BMP280, which means that the pressure and temperature control and readout is identical to BMP280. However, the following exceptions have to be considered:

Table 17: Register incompatibilities between BMP280 and BME280

Register	Bits	Content	BMP280	BME280
0xD0 “id”	7:0	chip_id	Read value is 0x56 / 0x57 (samples) 0x58 (mass production)	Read value is 0x60
0xF5 “config”	7:5	t_sb	‘110’: 2000 ms ‘111’: 4000 ms	‘110’: 10 ms ‘111’: 20 ms
0xF7...0xF9 “press”	19:0	press	Resolution (16...20 bit) depends only on <i>osrs_p</i>	Without filter, resolution depends on <i>osrs_p</i> ; when using filter, resolution is always 20 bit
0xFA...0xFC “temp”	19:0	temp	Resolution (16...20 bit) only depends on <i>osrs_t</i>	Without filter, resolution depends on <i>osrs_t</i> ; when using filter, resolution is always 20 bit

5.3 Memory map

The memory map is given in Table 18 below. Reserved registers are not shown.

Table 18: Memory map

Register Name	Address	bit7	bit6	bit5	bit4	bit3	bit2	bit1	bit0	Reset state		
hum_lsb	0xFE	hum_lsb<7:0>								0x00		
hum_msb	0xFD	hum_msb<7:0>								0x80		
temp_xlsb	0xFC	temp_xlsb<7:4>				0	0	0	0	0x00		
temp_lsb	0xFB	temp_lsb<7:0>								0x00		
temp_msb	0xFA	temp_msb<7:0>								0x80		
press_xlsb	0xF9	press_xlsb<7:4>				0	0	0	0	0x00		
press_lsb	0xF8	press_lsb<7:0>								0x00		
press_msb	0xF7	press_msb<7:0>								0x80		
config	0xF5	t_sb[2:0]				filter[2:0]				spi3w_en[0]	0x00	
ctrl_meas	0xF4	osrs_t[2:0]				osrs_p[2:0]				mode[1:0]	0x00	
status	0xF3	measuring[0]								im_update[0]		0x00
ctrl_hum	0xF2									osrs_h[2:0]		0x00
calib26..calib41	0xE1...0xF0	calibration data										individual
reset	0xE0	reset[7:0]										0x00
id	0xD0	chip_id[7:0]										0x60
calib00..calib25	0x88...0xA1	calibration data										individual

Registers:	Reserved registers do not change	Calibration data	Control registers	Data registers	Status registers	Chip ID	Reset
Type:		read only	read / write	read only	read only	read only	write only

5.4 Register description

5.4.1 Register 0xD0 “id”

The “id” register contains the chip identification number chip_id[7:0], which is 0x60. This number can be read as soon as the device finished the power-on-reset.

5.4.2 Register 0xE0 “reset”

The “reset” register contains the soft reset word reset[7:0]. If the value 0xB6 is written to the register, the device is reset using the complete power-on-reset procedure. Writing other values than 0xB6 has no effect. The readout value is always 0x00.

5.4.3 Register 0xF2 “ctrl_hum”

The “ctrl_hum” register sets the humidity data acquisition options of the device. **Changes to this register only become effective after a write operation to “ctrl_meas”.**

Table 19: Register 0xF2 “ctrl_hum”

Register 0xF2 “ctrl_hum”	Name	Description
Bit 2, 1, 0	osrs_h[2:0]	Controls oversampling of humidity data. See Table 20 for settings and chapter 3.4.1 for details.

Table 20: register settings osrs_h

osrs_h[2:0]	Humidity oversampling
000	Skipped (output set to 0x8000)
001	oversampling ×1
010	oversampling ×2
011	oversampling ×4
100	oversampling ×8
101, others	oversampling ×16

5.4.4 Register 0xF3 “status”

The “status” register contains two bits which indicate the status of the device.

Table 21: Register 0xF3 “status”

Register 0xF3 “status”	Name	Description
Bit 3	measuring[0]	Automatically set to ‘1’ whenever a conversion is running and back to ‘0’ when the results have been transferred to the data registers.
Bit 0	im_update[0]	Automatically set to ‘1’ when the NVM data are being copied to image registers and back to ‘0’ when the copying is done. The data are copied at power-on-reset and before every conversion.

5.4.5 Register 0xF4 “ctrl_meas”

The “ctrl_meas” register sets the pressure and temperature data acquisition options of the device. The register needs to be written after changing “ctrl_hum” for the changes to become effective.

Table 22: Register 0xF4 “ctrl_meas”

Register 0xF4 “ctrl_meas”	Name	Description
Bit 7, 6, 5	osrs_t[2:0]	Controls oversampling of temperature data. See Table 24 for settings and chapter 3.4.3 for details.
Bit 4, 3, 2	osrs_p[2:0]	Controls oversampling of pressure data. See Table 23 for settings and chapter 3.4.2 for details.
Bit 1, 0	mode[1:0]	Controls the sensor mode of the device. See Table 25 for settings and chapter 3.3 for details.

Table 23: register settings osrs_p

osrs_p[2:0]	Pressure oversampling
000	Skipped (output set to 0x80000)
001	oversampling ×1
010	oversampling ×2
011	oversampling ×4
100	oversampling ×8
101, others	oversampling ×16

Table 24: register settings osrs_t

osrs_t[2:0]	Temperature oversampling
000	Skipped (output set to 0x80000)
001	oversampling ×1
010	oversampling ×2
011	oversampling ×4
100	oversampling ×8
101, others	oversampling ×16

Table 25: register settings mode

mode[1:0]	Mode
00	Sleep mode
01 and 10	Forced mode
11	Normal mode

5.4.6 Register 0xF5 “config”

The “config” register sets the rate, filter and interface options of the device. Writes to the “config” register in normal mode may be ignored. In sleep mode writes are not ignored.

Table 26: Register 0xF5 “config”

Register 0xF5 “config”	Name	Description
Bit 7, 6, 5	t_sb[2:0]	Controls inactive duration t _{standby} in normal mode. See Table 27 for settings and chapter 3.3.4 for details.
Bit 4, 3, 2	filter[2:0]	Controls the time constant of the IIR filter. See Table 27 for settings and chapter 3.4.4 for details.
Bit 0	spi3w_en[0]	Enables 3-wire SPI interface when set to ‘1’. See chapter 6.3 for details.

Table 27: t_sb settings

t_sb[2:0]	t _{standby} [ms]
000	0.5
001	62.5
010	125
011	250
100	500
101	1000
110	10
111	20

Table 28: filter settings

filter[2:0]	Filter coefficient
000	Filter off
001	2
010	4
011	8
100, others	16

5.4.7 Register 0xF7...0xF9 “press” (_msb, _lsb, _xlsb)

The “press” register contains the raw pressure measurement output data up[19:0]. For details on how to read out the pressure and temperature information from the device, please consult chapter 4.

Table 29: Register 0xF7 ... 0xF9 “press”

Register 0xF7...0xF9 “press”	Name	Description
0xF7	press_msb[7:0]	Contains the MSB part up[19:12] of the raw pressure measurement output data.
0xF8	press_lsb[7:0]	Contains the LSB part up[11:4] of the raw pressure measurement output data.
0xF9 (bit 7, 6, 5, 4)	press_xlsb[3:0]	Contains the XLSB part up[3:0] of the raw pressure measurement output data. Contents depend on temperature resolution.

5.4.8 Register 0xFA...0xFC “temp” (_msb, _lsb, _xlsb)

The “temp” register contains the raw temperature measurement output data ut[19:0]. For details on how to read out the pressure and temperature information from the device, please consult chapter 4.

Table 30: Register 0xFA ... 0xFC “temp”

Register 0xFA...0xFC “temp”	Name	Description
0xFA	temp_msb[7:0]	Contains the MSB part ut[19:12] of the raw temperature measurement output data.
0xFB	temp_lsb[7:0]	Contains the LSB part ut[11:4] of the raw temperature measurement output data.
0xFC (bit 7, 6, 5, 4)	temp_xlsb[3:0]	Contains the XLSB part ut[3:0] of the raw temperature measurement output data. Contents depend on pressure resolution.

5.4.9 Register 0xFD...0xFE “hum” (_msb, _lsb)

The “temp” register contains the raw temperature measurement output data ut[19:0]. For details on how to read out the pressure and temperature information from the device, please consult chapter 4.

Table 31: Register 0xFD ... 0xFE “hum”

Register 0xFD...0xFE “hum”	Name	Description
0xFD	hum_msb[7:0]	Contains the MSB part uh[15:8] of the raw humidity measurement output data.
0xFE	temp_lsb[7:0]	Contains the LSB part uh[7:0] of the raw humidity measurement output data.

6. Digital interfaces

The BME280 supports the I²C and SPI digital interfaces; it acts as a slave for both protocols. The I²C interface supports the Standard, Fast and High Speed modes. The SPI interface supports both SPI mode '00' (CPOL = CPHA = '0') and mode '11' (CPOL = CPHA = '1') in 4-wire and 3-wire configuration.

The following transactions are supported:

- Single byte write
- multiple byte write (using pairs of register addresses and register data)
- single byte read
- multiple byte read (using a single register address which is auto-incremented)

6.1 Interface selection

Interface selection is done automatically based on CSB (chip select) status. If CSB is connected to V_{DDIO}, the I²C interface is active. If CSB is pulled down, the SPI interface is activated. After CSB has been pulled down once (regardless of whether any clock cycle occurred), the I²C interface is disabled until the next power-on-reset. This is done in order to avoid inadvertently decoding SPI traffic to another slave as I²C data. Since the device startup is deferred until both V_{DD} and V_{DDIO} are established, there is no risk of incorrect protocol detection because of the power-up sequence used. However, if I²C is to be used and CSB is not directly connected to V_{DDIO} but is instead connected to a programmable pin, it must be ensured that this pin already outputs the V_{DDIO} level during power-on-reset of the device. If this is not the case, the device will be locked in SPI mode and not respond to I²C commands.

6.2 I²C Interface

The I²C slave interface is compatible with Philips I²C Specification version 2.1. For detailed timings, please review Table 33. All modes (standard, fast, high speed) are supported. SDA and SCL are not pure open-drain. Both pads contain ESD protection diodes to V_{DDIO} and GND. As the device does not perform clock stretching, the SCL structure is a high-Z input without drain capability.




Figure 8: SDI/SCK ESD drawing

The 7-bit device address is 111011x. The 6 MSB bits are fixed. The last bit is changeable by SDO value and can be changed during operation. Connecting SDO to GND results in slave address 1110110 (0x76); connection it to V_{DDIO} results in slave address 1110111 (0x77), which is the same as

BMP280's I²C address. The SDO pin cannot be left floating; if left floating, the I²C address will be undefined.

The I²C interface uses the following pins:

- SCK: serial clock (SCL)
- SDI: data (SDA)
- SDO: Slave address LSB (GND = '0', V_{DDIO} = '1')

CSB must be connected to V_{DDIO} to select I²C interface. SDI is bi-directional with open drain to GND: it must be externally connected to V_{DDIO} via a pull up resistor. Refer to chapter 7 for connection instructions.

The following abbreviations will be used in the I²C protocol figures:

- S Start
- P Stop
- ACKS Acknowledge by slave
- ACKM Acknowledge by master
- NACKM Not acknowledge by master

6.2.1 I²C write

Writing is done by sending the slave address in write mode (RW = '0'), resulting in slave address 111011X0 ('X' is determined by state of SDO pin). Then the master sends pairs of register addresses and register data. The transaction is ended by a stop condition. This is depicted in Figure 9.



Figure 9: I²C multiple byte write (not auto-incremented)

6.2.2 I²C read

To be able to read registers, first the register address must be sent in write mode (slave address 111011X0). Then either a stop or a repeated start condition must be generated. After this the slave is addressed in read mode (RW = '1') at address 111011X1, after which the slave sends out data from auto-incremented register addresses until a NOACKM and stop condition occurs. This is depicted in Figure 10, where register 0xF6 and 0xF7 are read.




Figure 10: I²C multiple byte read

6.3 SPI interface

The SPI interface is compatible with SPI mode '00' (CPOL = CPHA = '0') and mode '11' (CPOL = CPHA = '1'). The automatic selection between mode '00' and '11' is determined by the value of SCK after the CSB falling edge.

The SPI interface has two modes: 4-wire and 3-wire. The protocol is the same for both. The 3-wire mode is selected by setting '1' to the register spi3w_en. The pad SDI is used as a data pad in 3-wire mode.

The SPI interface uses the following pins:

- CSB: chip select, active low
- SCK: serial clock
- SDI: serial data input; data input/output in 3-wire mode
- SDO: serial data output; hi-Z in 3-wire mode

Refer to chapter 7 for connection instructions.

CSB is active low and has an integrated pull-up resistor. Data on SDI is latched by the device at SCK rising edge and SDO is changed at SCK falling edge. Communication starts when CSB goes to low and stops when CSB goes to high; during these transitions on CSB, SCK must be stable. The SPI protocol is shown in Figure 11. For timing details, please review Table 34.




Figure 11: SPI protocol (shown for mode '11' in 4-wire configuration)

In SPI mode, only 7 bits of the register addresses are used; the MSB of register address is not used and replaced by a read/write bit (RW = '0' for write and RW = '1' for read).

Example: address 0xF7 is accessed by using SPI register address 0x77. For write access, the byte 0x77 is transferred, for read access, the byte 0xF7 is transferred.

6.3.1 SPI write

Writing is done by lowering CSB and sending pairs control bytes and register data. The control bytes consist of the SPI register address (= full register address without bit 7) and the write command (bit7 = RW = '0'). Several pairs can be written without raising CSB. The transaction is ended by a raising CSB. The SPI write protocol is depicted in Figure 12.




Figure 12: SPI multiple byte write (not auto-incremented)

6.3.2 SPI read

Reading is done by lowering CSB and first sending one control byte. The control bytes consist of the SPI register address (= full register address without bit 7) and the read command (bit 7 = RW = '1'). After writing the control byte, data is sent out of the SDO pin (SDI in 3-wire mode); the register address is automatically incremented. The SPI read protocol is depicted in Figure 13.




Figure 13: SPI multiple byte read

6.4 Interface parameter specification

6.4.1 General interface parameters

The general interface parameters are given in Table 32 below.

Table 32: interface parameters

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Input low level	V_{il_si}	$V_{DDIO}=1.2\text{ V to }3.6\text{ V}$			20	% V_{DDIO}
Input high level	V_{ih_si}	$V_{DDIO}=1.2\text{ V to }3.6\text{ V}$	80			% V_{DDIO}
Output low level I ² C	V_{ol_SDI}	$V_{DDIO}=1.62\text{ V, }I_{ol}=3\text{ mA}$			20	% V_{DDIO}
Output low level I ² C	$V_{ol_SDI_1.2}$	$V_{DDIO}=1.20\text{ V, }I_{ol}=3\text{ mA}$			23	% V_{DDIO}
Output low level SPI	V_{ol_SDO}	$V_{DDIO}=1.62\text{ V, }I_{ol}=1\text{ mA}$			20	% V_{DDIO}
Output low level SPI	$V_{ol_SDO_1.2}$	$V_{DDIO}=1.20\text{ V, }I_{ol}=1\text{ mA}$			23	% V_{DDIO}
Output high level	V_{oh}	$V_{DDIO}=1.62\text{ V, }I_{oh}=1\text{ mA}$ (SDO, SDI)	80			% V_{DDIO}
Output high level	$V_{oh_1.2}$	$V_{DDIO}=1.20\text{ V, }I_{oh}=1\text{ mA}$ (SDO, SDI)	60			% V_{DDIO}
Pull-up resistor	R_{pull}	Internal CSB pull-up resistance to V_{DDIO}	70	120	190	k Ω
I ² C bus load capacitor	C_b	On SDI and SCK			400	pF

6.4.2 I²C timings

For I²C timings, the following abbreviations are used:

- “S&F mode” = standard and fast mode
- “HS mode” = high speed mode
- C_b = bus capacitance on SDA line

All other naming refers to I²C specification 2.1 (January 2000).

The I²C timing diagram is in Figure 14. The corresponding values are given in Table 33.




Figure 14: I²C timing diagram

Table 33: I²C timings

Parameter	Symbol	Condition	Min	Typ	Max	Unit
SDI setup time	$t_{SU,DAT}$	S&F Mode	160			ns
		HS mode	30			ns
SDI hold time	$t_{HD,DAT}$	S&F Mode, $C_b \leq 100$ pF	80			ns
		S&F Mode, $C_b \leq 400$ pF	90			ns
		HS mode, $C_b \leq 100$ pF	18		115	ns
		HS mode, $C_b \leq 400$ pF	24		150	ns
SCK low pulse	t_{LOW}	HS mode, $C_b \leq 100$ pF $V_{DDIO} = 1.62$ V	160			ns
SCK low pulse	t_{LOW}	HS mode, $C_b \leq 100$ pF $V_{DDIO} = 1.2$ V	210			ns

The above-mentioned I²C specific timings correspond to the following internal added delays:

- Input delay between SDI and SCK inputs: SDI is more delayed than SCK by typically 100 ns in Standard and Fast Modes and by typically 20 ns in High Speed Mode.
- Output delay from SCK falling edge to SDI output propagation is typically 140 ns in Standard and Fast Modes and typically 70 ns in High Speed Mode.

6.4.3 SPI timings

The SPI timing diagram is in Figure 15, while the corresponding values are given in Table 34. All timings apply both to 4- and 3-wire SPI.




Figure 15: SPI timing diagram

Table 34: SPI timings

Parameter	Symbol	Condition	Min	Typ	Max	Unit
SPI clock input frequency	F_spi		0		10	MHz
SCK low pulse	T_low_sck		20			ns
SCK high pulse	T_high_sck		20			ns
SDI setup time	T_setup_sdi		20			ns
SDI hold time	T_hold_sdi		20			ns
SDO output delay	T_delay_sdo	25 pF load, V _{DDIO} =1.6 V min			30	ns
SDO output delay	T_delay_sdo	25 pF load, V _{DDIO} =1.2 V min			40	ns
CSB setup time	T_setup_csb		20			ns
CSB hold time	T_hold_csb		20			ns

7. Pin-out and connection diagram

7.1 Pin-out





Figure 16: Pin-out top and bottom view

Note: The pin numbering of BME280 is performed in the untypical clockwise direction when seen in top view and counter-clockwise when seen in bottom view.

Table 35: Pin description

Pin	Name	I/O Type	Description	Connect to		
				SPI 4W	SPI 3W	I ² C
1	GND	Supply	Ground	GND		
2	CSB	In	Chip select	CSB	CSB	V _{DDIO}
3	SDI	In/Out	Serial data input	SDI	SDI/SDO	SDA
4	SCK	In	Serial clock input	SCK	SCK	SCL
5	SDO	In/Out	Serial data output	SDO	DNC	GND for default address
6	V _{DDIO}	Supply	Digital / Interface supply	V _{DDIO}		
7	GND	Supply	Ground	GND		
8	V _{DD}	Supply	Analog supply	V _{DD}		

7.2 Connection diagram I²CFigure 17: I²C connection diagram

Notes:

- The recommended value for C₁, C₂ is 100 nF
- The value for the pull-up resistors R₁, R₂ should be based on the interface timing and the bus load; a normal value is 4.7 kΩ
- A direct connection between CSB and V_{DDIO} is required

7.3 Connection diagram 4-wire SPI




Figure 18: 4-wire SPI connection diagram

Note: The recommended value for C_1 , C_2 is 100 nF

7.4 Connection diagram 3-wire SPI




Figure 19: 3-wire SPI connection diagram

Note: The recommended value for C_1 , C_2 is 100 nF

7.5 Package dimensions




Figure 20: Package dimensions for top, bottom and side view

7.6 Landing pattern recommendation

For the design of the landing pattern, the following dimensioning is recommended:




Figure 21: Recommended landing pattern (top view)


Note: red areas demark exposed PCB metal pads.

- In case of a solder mask defined (SMD) PCB process, the land dimensions should be defined by solder mask openings. The underlying metal pads are larger than these openings.
- In case of a non solder mask defined (NSMD) PCB process, the land dimensions should be defined in the metal layer. The mask openings are larger than these metal pads.

7.7 Marking


7.7.1 Mass production devices

Table 36: Marking of mass production parts

Marking	Symbol	Description
	CCC	<u>Lot counter</u> : 3 alphanumeric digits, variable to generate mass production trace-code
	T	<u>Product number</u> : 1 alphanumeric digit, fixed to identify product type, T = "U" "U" is associated with the product BME280 (part number 0 273 141 185)
	L	<u>Sub-contractor ID</u> : 1 alphanumeric digit, variable to identify sub-contractor (L = "P")

7.7.2 Engineering samples

Table 37: Marking of engineering samples

Marking	Symbol	Description
	XX	<u>Sample ID</u> : 2 alphanumeric digits, variable to generate trace-code
	N	<u>Eng. Sample ID</u> : 1 alphanumeric digit, fixed to identify engineering sample, N = "*" or "e" or "E"
	CC	<u>Counter ID</u> : 2 alphanumeric digits, variable to generate trace-code

7.8 Soldering guidelines and reconditioning recommendations

The moisture sensitivity level of the BME280 sensors corresponds to JEDEC Level 1, see also:

- IPC/JEDEC J-STD-020C “Joint Industry Standard: Moisture/Reflow Sensitivity Classification for non-hermetic Solid State Surface Mount Devices”
- IPC/JEDEC J-STD-033A “Joint Industry Standard: Handling, Packing, Shipping and Use of Moisture/Reflow Sensitive Surface Mount Devices”.

The sensor fulfils the lead-free soldering requirements of the above-mentioned IPC/JEDEC standard, i.e. reflow soldering with a peak temperature up to 260°C. The minimum height of the solder after reflow shall be at least 50µm. This is required for good mechanical decoupling between the sensor device and the printed circuit board (PCB).

Profile Feature		Pb-Free Assembly
Average Ramp-Up Rate ($T_{S_{max}}$ to T_p)		3° C/second max.
Preheat		
– Temperature Min ($T_{S_{min}}$)		150 °C
– Temperature Max ($T_{S_{max}}$)		200 °C
– Time ($t_{S_{min}}$ to $t_{S_{max}}$)		60-180 seconds
Time maintained above:		
– Temperature (T_L)		217 °C
– Time (t_L)		60-150 seconds
Peak/Classification Temperature (T_p)		260 °C
Time within 5 °C of actual Peak Temperature (t_p)		20-40 seconds
Ramp-Down Rate		6 °C/second max.
Time 25 °C to Peak Temperature		8 minutes max.

Note 1: All temperatures refer to topside of the package, measured on the package body surface.




Figure 22: Soldering profile

7.9 Reconditioning Procedure

After exposing the device to operating conditions, which exceed the limits specified in section 1.2, e.g. after reflow, the humidity sensor may possess an additional offset. Therefore the following reconditioning procedure is mandatory to restore the calibration state:

1. Dry-Baking: 120 °C at <5% rH for 2 h
2. Re-Hydration: 70 °C at 75% rH for 6 h

or alternatively

1. Dry-Baking: 120 °C at <5% rH for 2 h
2. Re-Hydration: 25 °C at 75% rH for 24 h

or alternatively after solder reflow only

1. Do not perform Dry-Baking
2. Ambient Re-Hydration: ~25 °C at >40% rH for >5d

7.10 Tape and reel specification

7.10.1 Dimensions




Figure 23: Tape and Reel dimensions

Quantity per reel: 10 kpcs.

7.10.2 Orientation within the reel




Figure 24: Orientation within tape

7.11 Mounting and assembly recommendations

In order to achieve the specified performance for your design, the following recommendations and the “Handling, soldering & mounting instructions BME280” should be taken into consideration when mounting a pressure sensor on a printed-circuit board (PCB):

- The clearance above the metal lid shall be 0.1mm at minimum.
- For the device housing appropriate venting needs to be provided in case the ambient pressure shall be measured.
- Liquids shall not come into direct contact with the device.
- During operation the sensor chip is sensitive to light, which can influence the accuracy of the measurement (photo-current of silicon). The position of the vent hole minimizes the light exposure of the sensor chip. Nevertheless, Bosch Sensortec recommends avoiding the exposure of BME280 to strong light sources.
- Soldering may not be done using vapor phase processes since the sensor will be damaged by the liquids used in these processes.

7.12 Environmental safety

7.12.1 RoHS

The BME280 sensor meets the requirements of the EC restriction of hazardous substances (RoHS) directive, see also:

RoHS-Directive 2011/65/EU and its amendments, including the amendment 2015/863/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

7.12.2 Halogen content

The BME280 is halogen-free. For more details on the analysis results please contact your Bosch Sensortec representative.

7.12.3 Internal package structure

Within the scope of Bosch Sensortec's ambition to improve its products and secure the mass product supply, Bosch Sensortec qualifies additional sources (e.g. 2nd source) for the package of the BME280.

While Bosch Sensortec took care that all of the technical packages parameters are described above are 100% identical for all sources, there can be differences in the chemical content and the internal structural between the different package sources.

However, as secured by the extensive product qualification process of Bosch Sensortec, this has no impact to the usage or to the quality of the BME280 product.

8. Appendix A: Alternative compensation formulas

8.1 Compensation formulas in double precision floating point

Please note that it is strongly advised to use the API available from Bosch Sensortec to perform readout and compensation. If this is not wanted, the code below can be applied at the user's risk. Both pressure and temperature values are expected to be received in 20 bit format, positive, stored in a 32 bit signed integer. Humidity is expected to be received in 16 bit format, positive, stored in a 32 bit signed integer.

The variable `t_fine` (signed 32 bit) carries a fine resolution temperature value over to the pressure compensation formula and could be implemented as a global variable.

The data type "BME280_S32_t" should define a 32 bit signed integer variable type and could usually be defined as "long signed int". The revision of the code is rev. 1.1 (pressure and temperature) and rev. 1.0 (humidity).

Compensating the measurement value with double precision gives the best possible accuracy but is only recommended for PC applications.

```
// Returns temperature in DegC, double precision. Output value of "51.23" equals 51.23 DegC.
// t_fine carries fine temperature as global value
BME280_S32_t t_fine;
double BME280_compensate_T_double(BME280_S32_t adc_T)
{
    double var1, var2, T;
    var1 = (((double)adc_T)/16384.0 - ((double)dig_T1)/1024.0) * ((double)dig_T2);
    var2 = (((double)adc_T)/131072.0 - ((double)dig_T1)/8192.0) *
        (((double)adc_T)/131072.0 - ((double)dig_T1)/8192.0) * ((double)dig_T3);
    t_fine = (BME280_S32_t)(var1 + var2);
    T = (var1 + var2) / 5120.0;
    return T;
}
// Returns pressure in Pa as double. Output value of "96386.2" equals 96386.2 Pa = 963.862 hPa
double BME280_compensate_P_double(BME280_S32_t adc_P)
{
    double var1, var2, p;
    var1 = ((double)t_fine/2.0) - 64000.0;
    var2 = var1 * var1 * ((double)dig_P6) / 32768.0;
    var2 = var2 + var1 * ((double)dig_P5) * 2.0;
    var2 = (var2/4.0) + ((double)dig_P4) * 65536.0;
    var1 = ((double)dig_P3) * var1 * var1 / 524288.0 + ((double)dig_P2) * var1 / 524288.0;
    var1 = (1.0 + var1 / 32768.0) * ((double)dig_P1);
    if (var1 == 0.0)
    {
        return 0; // avoid exception caused by division by zero
    }
    p = 1048576.0 - (double)adc_P;
    p = (p - (var2 / 4096.0)) * 6250.0 / var1;
    var1 = ((double)dig_P9) * p * p / 2147483648.0;
    var2 = p * ((double)dig_P8) / 32768.0;
    p = p + (var1 + var2 + ((double)dig_P7)) / 16.0;
    return p;
}
// Returns humidity in %rH as as double. Output value of "46.332" represents
46.332 %rH
double bme280_compensate_H_double(BME280_S32_t adc_H);
{
    double var_H;

    var_H = (((double)t_fine) - 76800.0);
    var_H = (adc_H - (((double)dig_H4) * 64.0 + ((double)dig_H5) / 16384.0 *
        var_H)) * (((double)dig_H2) / 65536.0 * (1.0 + ((double)dig_H6) /
        67108864.0 * var_H *
        (1.0 + ((double)dig_H3) / 67108864.0 * var_H)));
    var_H = var_H * (1.0 - ((double)dig_H1) * var_H / 524288.0);

    if (var_H > 100.0)
        var_H = 100.0;
    else if (var_H < 0.0)
        var_H = 0.0;
    return var_H;
}
```

8.2 Pressure compensation in 32 bit fixed point

Please note that it is strongly advised to use the API available from Bosch Sensortec to perform readout and compensation. If this is not wanted, the code below can be applied at the user's risk. Both pressure and temperature values are expected to be received in 20 bit format, positive, stored in a 32 bit signed integer.

The variable `t_fine` (signed 32 bit) carries a fine resolution temperature value over to the pressure compensation formula and could be implemented as a global variable.

The data type "BME280_S32_t" should define a 32 bit signed integer variable type and can usually be defined as "long signed int".

The data type "BME280_U32_t" should define a 32 bit unsigned integer variable type and can usually be defined as "long unsigned int".

Compensating the pressure value with 32 bit integer has an accuracy of typically 1 Pa (1-sigma). At high filter levels this adds a significant amount of noise to the output values and reduces their resolution.

```
// Returns temperature in DegC, resolution is 0.01 DegC. Output value of "5123" equals 51.23
// DegC.
// t_fine carries fine temperature as global value
BME280_S32_t t_fine;
BME280_S32_t BME280_compensate_T_int32(BME280_S32_t adc_T)
{
    BME280_S32_t var1, var2, T;
    var1 = (((adc_T >> 3) - ((BME280_S32_t)dig_T1 << 1))) * ((BME280_S32_t)dig_T2) >> 11;
    var2 = (((((adc_T >> 4) - ((BME280_S32_t)dig_T1)) * ((adc_T >> 4) - ((BME280_S32_t)dig_T1)))
    >> 12) *
        ((BME280_S32_t)dig_T3)) >> 14;
    t_fine = var1 + var2;
    T = (t_fine * 5 + 128) >> 8;
    return T;
}

// Returns pressure in Pa as unsigned 32 bit integer. Output value of "96386" equals 96386 Pa
// = 963.86 hPa
BME280_U32_t BME280_compensate_P_int32(BME280_S32_t adc_P)
{
    BME280_S32_t var1, var2;
    BME280_U32_t p;
    var1 = (((BME280_S32_t)t_fine >> 1) - (BME280_S32_t)64000;
    var2 = (((var1 >> 2) * (var1 >> 2)) >> 11) * ((BME280_S32_t)dig_P6);
    var2 = var2 + ((var1 * ((BME280_S32_t)dig_P5) << 1);
    var2 = (var2 >> 2) + (((BME280_S32_t)dig_P4) << 16);
    var1 = (((dig_P3 * (((var1 >> 2) * (var1 >> 2)) >> 13)) >> 3) + (((BME280_S32_t)dig_P2) *
    var1) >> 1)) >> 18;
    var1 = (((((32768 + var1)) * ((BME280_S32_t)dig_P1)) >> 15);
    if (var1 == 0)
    {
        return 0; // avoid exception caused by division by zero
    }
    p = (((BME280_U32_t) (((BME280_S32_t)1048576 - adc_P) - (var2 >> 12))) * 3125;
    if (p < 0x80000000)
    {
        p = (p << 1) / ((BME280_U32_t)var1);
    }
    else
    {
        p = (p / (BME280_U32_t)var1) * 2;
    }
    var1 = (((BME280_S32_t)dig_P9) * ((BME280_S32_t) ((p >> 3) * (p >> 3)) >> 13)) >> 12;
    var2 = (((BME280_S32_t)(p >> 2)) * ((BME280_S32_t)dig_P8)) >> 13;
    p = (BME280_U32_t) (((BME280_S32_t)p + ((var1 + var2 + dig_P7) >> 4));
    return p;
}
```

9. Appendix B: Measurement time and current calculation

In this chapter, formulas are given to calculate measurement rate, filter bandwidth and current consumption in different settings.

9.1 Measurement time

The active measurement time depends on the selected values for humidity, temperature and pressure oversampling and can be calculated in milliseconds using the formulas below.

$$t_{\text{measure,typ}} = 1 + [2 \cdot T_{\text{oversampling}}]_{\text{osrs}_t \neq 0} + [2 \cdot P_{\text{oversampling}} + 0.5]_{\text{osrs}_p \neq 0} + [2 \cdot H_{\text{oversampling}} + 0.5]_{\text{osrs}_h \neq 0}$$

$$t_{\text{measure,max}} = 1.25 + [2.3 \cdot T_{\text{oversampling}}]_{\text{osrs}_t \neq 0} + [2.3 \cdot P_{\text{oversampling}} + 0.575]_{\text{osrs}_p \neq 0} + [2.3 \cdot H_{\text{oversampling}} + 0.575]_{\text{osrs}_h \neq 0}$$

For example, using temperature oversampling $\times 1$, pressure oversampling $\times 4$ and no humidity measurement, the measurement time is:

$$t_{\text{measure,typ}} = 1 + [2 \cdot 1] + [2 \cdot 4 + 0.5] + [0] = 11.5 \text{ ms}$$

$$t_{\text{measure,max}} = 1.25 + [2.3 \cdot 1] + [2.3 \cdot 4 + 0.575] + [0] = 13.325 \text{ ms}$$

9.2 Measurement rate in forced mode

In forced mode, the measurement rate depends on the rate at which it is forced by the master. The highest possible frequency in Hz can be calculated as:

$$ODR_{\text{max,forced}} = \frac{1000}{t_{\text{measure}}}$$

If measurements are forced faster than they can be executed, the data rate saturates at the attainable data rate. For the example above with 11.5 ms measurement time, the typically achievable output data rate would be:

$$ODR_{\text{max,forced}} = \frac{1000}{11.5} = 87 \text{ Hz}$$

9.3 Measurement rate in normal mode

The measurement rate in normal mode depends on the measurement time and the standby time and can be calculated in Hz using the following formula:

$$ODR_{\text{normal_mode}} = \frac{1000}{t_{\text{measure}} + t_{\text{standby}}}$$

The accuracy of t_{standby} is described in the specification parameter $\Delta t_{\text{standby}}$. For the example above with 11.5 ms measurement time, setting normal mode with a standby time of 62.5 ms would result in a data rate of:

$$ODR_{\text{normal_mode}} = \frac{1000}{11.5 + 62.5} = 13.51 \text{ Hz}$$

9.4 Response time using IIR filter

When using the IIR filter, the response time of the sensor depends on the selected filter coefficient and the data rate used. It can be calculated using the following formula:

$$t_{response, 75\%} = \frac{1000 \cdot n_{samples, 75\%}}{ODR}$$

For the example above with a data rate of 13.51 Hz, the user could select a filter coefficient of 8. According to Table 6, the number of samples needed to reach 75% of a step response using this filter setting is 11. The response time with filter is therefore:

$$t_{response, 75\%} = \frac{1000 \cdot 11}{13.51} = 814 \text{ ms}$$

9.5 Current consumption

The current consumption depends on the selected oversampling settings, the measurement rate and the sensor mode, but not on the IIR filter setting. It can be calculated as:

$$I_{DD,forced} = I_{DDSL} \cdot (1 - t_{measure} \cdot ODR) + \frac{ODR}{1000} \cdot (205 + I_{DDT} \cdot [2 \cdot T_{oversampling}]_{OSRS_t \neq 0} + I_{DDP} \cdot [2 \cdot P_{oversampling} + 0.5]_{OSRS_p \neq 0} + I_{DDH} \cdot [2 \cdot H_{oversampling} + 0.5]_{OSRS_h \neq 0})$$

$$I_{DD,normal} = I_{DDSB} \cdot (1 - t_{measure} \cdot ODR) + \frac{ODR}{1000} \cdot (205 + I_{DDT} \cdot [2 \cdot T_{oversampling}]_{OSRS_t \neq 0} + I_{DDP} \cdot [2 \cdot P_{oversampling} + 0.5]_{OSRS_p \neq 0} + I_{DDH} \cdot [2 \cdot H_{oversampling} + 0.5]_{OSRS_h \neq 0})$$

Note that the only difference between forced and normal mode current consumption is that the current for the inactive time is either I_{DDSL} or I_{DDSB} . For the example above, the current would be

$$\begin{aligned} I_{DD,normal} &= 0.2 \cdot (1 - 0.0115 \cdot 13.51) + \frac{13.51}{1000} (205 + 350 \cdot [2 \cdot 1] + 714 \cdot [2 \cdot 4 + 0.5] + [0]) \\ &= 0.2 \cdot (0.845) + \frac{13.51}{1000} (205 + 700 + 6069 + 0) \\ &= 0.2 + 94.2 = 94.4 \mu\text{A} \end{aligned}$$

10. Self test

The following chapter provides an explanation to the self-test code for the Bosch Sensortec BME280. The code itself refers to the API (Application Programming Interface) of the sensor, which can be obtained from Bosch Sensortec and is also included in this release package.

10.1 Self-test flow

The self-test starts by performing a soft reset of the device. After this, Chip-ID and trimming data are read and verified. Then temperature and pressure are measured and compared against customisable plausibility limits. A flow chart is given below.




Figure 25: Self-test flow chart

10.2 Function return codes

A list of the possible function return codes can be found below.

0	Sensor OK
10	Communication error or wrong device found
20	Trimming data out of bound
30	Temperature bond wire failure or MEMS defect
31	Pressure bond wire failure or MEMS defect
40	Implausible temperature (default limits: 0...40°C)
41	Implausible pressure (default limits: 900...1100 hPa)
42	Implausible humidity (default limits: 20...80 %rH)

Error testing is done in ascending error code sequence. This means that if e.g. a trimming data error is detected (code 20), the temperature plausibility (code 40) is not checked anymore. Instead, error code 20 is returned and no others tests are performed.

10.3 Usage

10.3.1 File and function pointer integration

- ▶ Include bme280.c in your programming environment and add the path to the compiler.
- ▶ Include bme280_selftest.c in your programming environment and add the path to the compiler.
- ▶ Modify the lines with read/write function pointer to match your system. Sample functions are given in chapter 10.5:

```
bme280.bus_read  = BME280_I2C_bus_read; // must be defined by customer
bme280.bus_write = BME280_I2C_bus_write; // must be defined by customer
bme280.delay_msec = BME280_delay_msec;   // must be defined by customer
```

- ▶ If necessary, adapt the measurement plausibility limits in bme280_selftest.h. The default limits are 0...40°C for temperature and 900...1100 hPa for pressure measurement.
- ▶ If you are using I²C communication with the address 0x77 (SDO pin high), then change the BME280.h line

```
#define BME280_I2C_ADDRESS    BME280_I2C_ADDRESS1
    into
#define BME280_I2C_ADDRESS    BME280_I2C_ADDRESS2
```

10.3.2 Function call

Call the self test function using:

```
unsigned char testresult;
testresult = bme280_selftest();
```

A test result of 0 indicates no error. The other return codes are detailed in chapter 10.2.

10.3.3 Test time and interface requirements

The self test uses a total wait time of 9 milliseconds. Of this, 2 milliseconds are used as wait time for soft reset and 7 milliseconds are used as wait time for conversion. The soft reset is performed in order to erase any possible old settings and could be omitted if the sensor is known to be in an untouched state after power on.

In the self test function, 4 write commands and 6 read commands are issued. In total, 4 bytes are written and 34 bytes are read. Assuming burst read is used, the following time duration can be expected for communication including overhead:

- ▶ 6.0 ms for I²C at 100 kHz
- ▶ 1.5 ms for I²C at 400 kHz
- ▶ 0.5 ms for SPI at 1 MHz

Assuming a 400 kHz I²C interface with burst reads, the total function run time therefore equals 10.5 milliseconds.

10.4 Function explanation

10.4.1 Communication test

This function attempts to read the Chip ID. If it is correct, a functioning communication is assumed. Note that the write function functionality is not explicitly tested.

10.4.2 Bond wire test

A pressure and temperature measurement is performed and uncompensated pressure and temperature values are read out. If the measurement results are clipped to the respective minimum or maximum ADC values, this is usually caused by defective bond wires. However, a defective sensing element could also cause this test to fail.

Please note that some combinations of bond wire or sensing element defects do not result in clipping of the measurement value and will therefore not be detected with this test. These cases can be detected by the plausibility test instead.

10.4.3 Measurement plausibility test

The pressure and temperature values read out previously are compensated using the read out compensation parameters. The compensated temperature and pressure is compared against plausibility limits set in `bme280_selftest.h`, which must be set to match the customer production environment. Please use the the plausibility limits as described in chapter 3.

10.5 Sample read, write and delay function

Below some samples read, write and delay functions are given. These are platform dependant and should only give an idea of how the functions could look.

```
signed char BME280_I2C_bus_read(unsigned char device_addr, unsigned char
    reg_addr, unsigned char *reg_data, unsigned char cnt)
{
    int iError=0;
    unsigned char array[I2C_BUFFER_LEN];
    unsigned char stringpos;
    array[0] = reg_addr;
    iError = I2C_write_read_string(I2C0, device_addr, array, array, 1, cnt);
    for(stringpos=0;stringpos<cnt;stringpos++)
    {
        *(reg_data + stringpos) = array[stringpos];
    }
    return (signed char)iError;
}

signed char BME280_I2C_bus_write(unsigned char device_addr, unsigned char
    reg_addr, unsigned char *reg_data, unsigned char cnt)
{
    int iError=0;
    unsigned char array[I2C_BUFFER_LEN];
    unsigned char stringpos;
    array[0] = reg_addr;
    for(stringpos=0;stringpos<cnt;stringpos++)
    {
        array[stringpos+1] = *(reg_data + stringpos);
    }
    iError = I2C_write_string(I2C0, device_addr, array, cnt+1);
    return (signed char)iError;
}

void BME280_delay_msec(BME280_U16_t msec) //delay in milliseconds
{
    BME280_U32_t counter;
    for (counter = 0; counter/2000 < msec; counter++); // 2000 counts = 1
msec
}
```

11. Legal disclaimer

11.1 Engineering samples

Engineering Samples are marked with an asterisk (*), (E) or (e). Samples may vary from the valid technical specifications of the product series contained in this data sheet. They are therefore not intended or fit for resale to third parties or for use in end products. Their sole purpose is internal client testing. The testing of an engineering sample may in no way replace the testing of a product series. Bosch Sensortec assumes no liability for the use of engineering samples. The Purchaser shall indemnify Bosch Sensortec from all claims arising from the use of engineering samples.

11.2 Product use

Bosch Sensortec products are developed for the consumer goods industry. They may only be used within the parameters of this product data sheet. They are not fit for use in life-sustaining or safety-critical systems. Safety-critical systems are those for which a malfunction is expected to lead to bodily harm, death or severe property damage. In addition, they shall not be used directly or indirectly for military purposes (including but not limited to nuclear, chemical or biological proliferation of weapons or development of missile technology), nuclear power, deep sea or space applications (including but not limited to satellite technology).

Bosch Sensortec products are released on the basis of the legal and normative requirements relevant to the Bosch Sensortec product for use in the following geographical target market: BE, BG, DK, DE, EE, FI, FR, GR, IE, IT, HR, LV, LT, LU, MT, NL, AT, PL, PT, RO, SE, SK, SI, ES, CZ, HU, CY, US, CN, JP, KR, TW. If you need further information or have further requirements, please contact your local sales contact.

The resale and/or use of Bosch Sensortec products are at the purchaser's own risk and his own responsibility. The examination of fitness for the intended use is the sole responsibility of the purchaser.

The purchaser shall indemnify Bosch Sensortec from all third party claims arising from any product use not covered by the parameters of this product data sheet or not approved by Bosch Sensortec and reimburse Bosch Sensortec for all costs in connection with such claims.

The purchaser accepts the responsibility to monitor the market for the purchased products, particularly with regard to product safety, and to inform Bosch Sensortec without delay of all safety-critical incidents.

11.3 Application examples and hints

With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Bosch Sensortec hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights or copyrights of any third party. The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. They are provided for illustrative purposes only and no evaluation regarding infringement of intellectual property rights or copyrights or regarding functionality, performance or error has been made.

12. Document history and modification

Rev. No	Page	Description of modification/changes	Date
0.1		Document creation	2012-11-06
1.0		Final datasheet	2014-11-12
1.1	48	Updated RoHS directive to 2011/65/EU effective 8 June 2011	2015-05-07
1.2	2, 3	Adjusted target devices, applications	2015-10-15
1.4		Minor corrections	2018-01-17
1.5		Template update	2018-09-17
1.8	Chapter 10	Updated legal disclaimer	2020-03-12
1.9	Chapter 10	Update disclaimer	2020-11-23
1.10	Chapter 10	New added chapter self-test disclaimer now 11	2021-03-18
1.21	Chapter 1.4	New typical accuracy	2021-07-22
1.22	Chapter 7.12	Update of ROHS directive	2021-10-22
1.23	1.4	Final Temperature spec	2022-01-22
1.24	Chapter 2	Remove condensation	2024-02-20



Bosch Sensortec GmbH
Gerhard-Kindler-Straße 9
72770 Reutlingen / Germany

contact@bosch-sensortec.com
www.bosch-sensortec.com


Modifications reserved
Document number: BST-BME280-DS001-24
Revision_1.24_022024

A.3 Hoja de datos sensor GUVA-S12SD


ROITHNER LASERTECHNIK GmbH

 WIEDNER HAUPTSTRASSE 76 1040 VIENNA AUSTRIA
 TEL. +43 1 586 52 43 -0. FAX. -44. OFFICE@ROITHNER-LASER.COM


GUVa-S12SD



TECHNICAL DATA

UV-B Sensor

Features

- Gallium Nitride Based Material
- Schottky-type Photodiode
- Photovoltaic Mode Operation
- Good Visible Blindness
- High Responsivity & Low Dark Current

Applications

- UV Index Monitoring
- UV-A Lamp Monitoring

Absolute Maximum Ratings


Item	Symbol	Value	Unit
Forward Current	I_F	1	mA
Reverse Voltage	V_R	5	V
Operating Temperature	T_{op}	-30 ... +85	°C
Storage Temperature	T_{st}	-40 ... +90	°C
Soldering Temperature *	T_{sol}	260	°C

* must be completed within 10 seconds

Characteristics (25°C)


Item	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Dark Current	I_D	$V_R = 0.1 \text{ V}$	-	-	1	nA
Photo Current	I_{PD}	UVA Lamp, 1 mW/cm ²	-	113	-	nA
		1 UVI	-	26	-	nA
Temperature Coefficient	I_{TC}	UVA Lamp	-	0.08	-	% / °C
Responsivity	R	$\lambda = 350 \text{ nm}, V_R = 0 \text{ V}$	-	0.14	-	A/W
Spectral Detection Range	λ	10% of R	240	-	370	nm

Package Dimension







Responsivity Curve



Photocurrent along UV Power



A.4 Hoja de datos veleta RS-FXJT-N01



1

Wind direction transmitter instruction manual (type 485)

RS-FXJT-N01

Wind direction transmitter user's manual (Type 485)

Document version: V2.1



2

Wind direction transmitter instruction manual (type 485)





3

Wind direction transmitter instruction manual (type 485)




Table of Contents

1. product description.....	4
2. Equipment installation instructions.....	5
3.Configuration software installation and use.....	7
4. letter of agreement.....	9
5. Common problems and solutions.....	11
6. contact details.....	错误！未定义书签。
7. Document history.....	错误！未定义书签。
8. Dimensions.....	13



1. product description

1.1 product description

RS-FXJT-N01 wind direction transmitter, compact and lightweight, easy to carry and assemble. The new design concept can effectively obtain the wind direction information. The shell is made of polycarbonate composite material, which has good characteristics such as corrosion resistance and erosion resistance, which can ensure The transmitter does not deform for a long time, and at the same time cooperates with a smooth internal bearing system to ensure the accuracy of information collection. It is widely used in wind direction measurement of greenhouses, environmental protection, weather stations, ships, terminals, breeding and other environments.

1.2 Features

1. Range: 8 directions
2. Anti-electromagnetic interference treatment
3. Imported high-performance bearings, small rotation resistance and accurate measurement
4. Polycarbonate shell, high mechanical strength, high hardness, corrosion resistance, no rust, can be used outdoors for a long time
5. The equipment structure and weight are carefully designed and distributed, the moment of inertia is small, and the response is sensitive
6. Standard ModBus-RTU communication protocol, easy access

1.3 Main Specifications

DC powered (default)	10~30V DC
Power consumption	≤0.3W
Transmitter circuit operating temperature	-20℃~+60℃, 0%RH~80%RH
Communication Interface	485 communication (modbus) protocol Baud rate: 2400, 4800 (default), 9600 Data bit length: 8 bits Parity mode: None Stop bit length: 1 bit Default ModBus communication address: 1 Support function code: 03
parameter settings	Use the provided configuration software to configure through the 485 interface
Measuring range	8 directions



5

Wind direction transmitter instruction manual (type 485)

Dynamic response speed	≤0.5s
------------------------	-------

2. Equipment installation instructions

2.1 Check before equipment installation

Equipment List:

1. Transmitter equipment
- 2.4 mounting screws
3. Qualification certificate, warranty card, wiring instructions, etc.
4. USB to 485 (optional)
5. 485 terminal resistance (optional)

2.2 Interface Description

Wide voltage power input can be 10 ~ 30V. When wiring the 485 signal line, pay attention that the two wires A \ B cannot be reversed, and the addresses of multiple devices on the bus must not conflict.

2.3 Electrical wiring

	Thread color	Description
power supply	brown	Power supply (10 ~ 30V DC)
	black	Negative power
Communication	green	485-A
	blue	485-B

2.4 Field wiring instructions

When multiple 485 models are connected to the same bus, there are certain requirements for field wiring. For details, please refer to the "485 Equipment Field Wiring Manual" in the reference package.

2.5 Installation method

It adopts flange installation and threaded flange connection to firmly fix the lower pipe of the wind direction sensor to the flange. The chassis is Ø80mm. Four Ø4.5mm mounting holes are opened on the Ø68mm circumference, and it is firmly fixed with bolts. The bracket keeps the entire set of instruments at the optimal level to ensure the accuracy of the wind direction data. The flange connection is easy to use and can withstand large pressures.



6

Wind direction transmitter instruction manual (type 485)





7

Wind direction transmitter instruction manual (type 485)



2.6 Precautions

1. The user is not allowed to dismantle by himself, nor touch the sensor core, so as not to cause damage to the product.
2. Try to stay away from high-power interference equipment to avoid inaccurate measurements, such as inverters, motors, etc. When installing and removing the transmitter, you must first disconnect the power supply. Water entering the transmitter can cause irreversible changes.
3. To prevent chemical reagents, oil, dust and other direct damage to the sensor, do not use it for a long time in the environment of condensation, extreme temperature, and prevent cold and heat shock.

3. Configuration software installation and use

3.1 Software selection

Open the package and select "Debugging Software" --- "485 Parameter Configuration"




8

Wind direction transmitter instruction manual (type 485)

Software" and find  485参数配置工具
control
KITControl.Micros... Just open it.

3.2 parameter settings

① Select the correct COM port (check the COM port in "My Computer-Properties-Device Manager-Port"). The following figure lists several different 485 converter driver names.



- ② Connect only one device and power on. Click the software to test the baud rate. The software will test the baud rate and address of the current device. The default baud rate is 4800bit / s and the default address is 0x01.
- ③ Modify the address and baud rate according to the needs of use, and can query the current function status of the device.
- ④ If the test is unsuccessful, please recheck the equipment wiring and 485 driver installation.



9

Wind direction transmitter instruction manual (type 485)

4. letter of agreement

4.1 Basic communication parameters

Code	8-bit binary
Data bit	8-bit
Parity bit	no
Stop bit	1 person
Error checking	CRC (Redundant Cyclic Code)
Baud rate	2400bit / s, 4800bit / s, 9600 bit / s can be set, the factory default is 4800 bit / s

4.2 Data frame format definition

Modbus-RTU communication protocol is adopted, the format is as follows:

Initial structure $\geq$ 4 bytes of time

Shandong Renke Control Technology Co., Ltd.

9

www.renkeer.com



10

Wind direction transmitter instruction manual (type 485)

Address code = 1 byte

Function code = 1 byte

Data area = N bytes

Error check = 16-bit CRC

Ending structure $\geq$ 4 bytes of time

Address code: It is the address of the transmitter, which is unique in the communication network (factory default 0x01).

Function code: The function instruction of the command issued by the host, this transmitter only uses the function code 0x03 (reading register data).

Data area: The data area is the specific communication data. Note that the high byte of the 16bits data comes first!

CRC code: two-byte check code.

Host inquiry frame structure:

address code	function code	Register start address	Register length	Low check bit	Check code high
1byte	1byte	2byte	2byte	1byte	1byte

Slave response frame structure:

address code	function code	Number of valid bytes	Data area	Second data area	Nth data area	Check code
1byte	1byte	1byte	2byte	2byte	2byte	2byte

4.3 Register address

Register address	PLCOr configuration address	content	operating
0000 H	40001	Wind direction (0-7 gear) The uploaded data is the real value	Read-only
0001 H	40002	Wind direction (0-360 °) The uploaded data is the real value	Read-only

4.4 Numerical correspondence conversion relationship

Collection value (0-7 files)	Acquisition value (0-360 °)	Corresponding direction
0	0°	North wind
1	45°	Northeast wind



11

Wind direction transmitter instruction manual (type 485)

2	90°	Dongfeng
3	135°	Southeast wind
4	180°	south wind
5	225°	Southwest wind
6	270°	Westerly
7	315°	Northwest wind

4.5 Communication protocol example and explanation

Example: Read wind direction at device address 0x01

Inquiry frame:

address code	function code	starting address	Data length	Low check bit	Check code high
0x01	0x03	0x00 0x00	0x00 0x02	0xC4	0x0B

Inquiry frame: (For example, reading the wind direction value (0-7 gear) is 2, and (0-360°) is 90°)

address code	function code	Returns the number of valid bytes	wind direction (0-7 files)	wind direction (0-360°)	Low check bit	Check code high
0x01	0x03	0x04	0x00 0x02	0x00 0x5A	0xDB	0xC8

Wind direction calculation:

(0-7 files): 0002H (hexadecimal) = 2 => wind direction = east wind

(0-360°): 005AH (hexadecimal) = 90 => wind direction = east wind

5. Common problems and solutions

5.1 Device cannot be connected to PLC or computer

possible reason:

- 1) The computer has multiple COM ports, and the selected port is incorrect.
- 2) The device address is wrong, or there are devices with duplicate addresses (the factory defaults are all 1).
- 3) Baud rate, check mode, data bit, stop bit error.
- 4) The host polling interval and waiting for response time are too short, both need to be set above 200ms.
- 5) The 485 bus is disconnected, or the A and B wires are reversed.
- 6) If there are too many devices or the wiring is too long, you should supply power nearby, add a 485 booster, and increase the 120Ω terminal resistance.
- 7) The USB to 485 driver is not installed or damaged.
- 8) The equipment is damaged.



12

Wind direction transmitter instruction manual (type 485)

6. Contact

Shandong Renke Control Technology Co., Ltd.

Address: 2 / F, East Block, Building 8, Shun Tai Plaza, High-tech Zone, Jinan City, Shandong Province

Post code: 250101

Phone: 400-085-5807

Website: www.renkeer.com

Cloud platform address: en.0531yun.cn Or: eniot.0531yun.cn

Web QR:





13

Wind direction transmitter instruction manual (type 485)


7. Document history

V1.0 document creation.

V2.0 documentation update.

V2.1 Product size change.

8. Dimensions



A.5 Hoja de datos sensor SS49E

Honeywell



SS39ET/SS49E/SS59ET Series
Linear Hall-effect Sensor ICs



[Datasheet](#)

Magnetoresistive Sensor ICs

The SS39ET/SS49E/SS59ET Series low-cost linear Hall-effect sensor ICs are small, versatile devices that are operated by the magnetic field from a permanent magnet or an electromagnet. They are designed and manufactured for cost competitiveness.

The linear sourcing output voltage is set by the supply voltage and varies in proportion to the strength of the magnetic field. Low voltage capability as low as 2.7 Vdc and reduced current consumption of only 6 mA typically at 5 Vdc help make this product energy efficient.

The integrated circuitry features low noise output, which makes it unnecessary to use external filtering. These sensor ICs interface with many electrical components without buffering. They also include thin film resistors to provide increased temperature stability and accuracy.

These linear Hall-effect sensor ICs have an operating temperature range of -40 °C to 100°C [-40 °F to 212 °F], appropriate for industrial and medical environments. Thermal balancing allows for stable operation over the full temperature range.

They are available in three package styles, all of which may be supplied on tape for automated, lower-cost assembly:

- **SOT-23:** SS39ET. This small footprint takes up less space on the PC board, typically allowing for more components.
- **Flat TO-92-style, with different lead configurations:** SS49E, SS49E-L, SS49E-F.
- **SOT-89B:** SS59ET.

Key Features

- **Miniature and subminiature construction:** Designed for compact designs with tight space requirements
- **Energy efficient:** Low current consumption of 6 mA at 5 Vdc
- **Easy PC board interface:** Single current sourcing output for common electronic circuits
- **Circuit design flexibility:** Voltage range of 2.7 Vdc to 6.5 Vdc
- **Low noise output:** Virtually eliminates the need for filtering
- **Stable output:** Thin film resistors improve accuracy
- **Wide range of environments:** Temperature range of -40 °C to 100 °C [-40 °F to 212 °F]
- **Application flexibility:** Responds to either positive or negative Gauss

Potential Applications

INDUSTRIAL

- Basic current sensing for motor load monitoring, detection
- Anti-tampering magnetic field sensor in smart remote utility meters
- Pump control in heavy-duty equipment and household appliances
- Simple linear or angular displacement sensing
- Handlebar/throttle position sensing in e-bikes and scooters
- Current sensing in appliances
- Speed adjustment trigger in tools and appliances
- Magnetic code reading in safes, security and building access control systems

MEDICAL

- Position sensing in infusion pumps

SS39ET/SS49E/SS59ET Series

Table 1. Operating Characteristics ($V_s = 5.0\text{ V}$, $T_A = -40\text{ }^\circ\text{C}$ to $85\text{ }^\circ\text{C}$ [$-40\text{ }^\circ\text{F}$ to $185\text{ }^\circ\text{F}$], except where noted.)

Characteristic	Condition	Min.	Typ.	Max.	Unit
Output type		linear, sourcing			—
Magnetics type		analog			—
Supply voltage	—	2.7	—	6.5	Vdc
Supply current	$25\text{ }^\circ\text{C}$ [$77\text{ }^\circ\text{F}$]	—	6	10	mA
Output voltage	—	1.0	1.4	1.75	mV/Gauss
Output current	$V_s > 3.0\text{ V}$	1.0	1.5	1.5	mA
Null	0 Gauss, $25\text{ }^\circ\text{C}$	2.25	2.50	2.75	Vdc
Output voltage span	—	1.05 to ($V_s - 1.05$)	0.95 to ($V_s - 0.95$)	—	Vdc
Magnetic range	—	± 650	± 1000	—	Gauss
Sensitivity	$25\text{ }^\circ\text{C}$	1.0	1.4	1.75	mV/Gauss
Operating temperature	—	-40 [-40]	—	100 [212]	$^\circ\text{C}$ [$^\circ\text{F}$]
Temperature error:					
Null drift	—	-0.10	—	0.10	$\% / ^\circ\text{C}$
Sensitivity drift	$\geq 25\text{ }^\circ\text{C}$	-0.15	—	0.05	
	$\leq 25\text{ }^\circ\text{C}$	-0.04	—	0.185	
Linearity	—	—	-0.7	—	% of span
Response time	—	—	3	—	μs

Table 2. Absolute Maximum Ratings

Characteristic	Parameter
Supply voltage (V_s)	-5.0 Vdc to 8.0 Vdc
Output current	10 mA
Storage temperature	$-55\text{ }^\circ\text{C}$ to $165\text{ }^\circ\text{C}$ [$-67\text{ }^\circ\text{F}$ to $329\text{ }^\circ\text{F}$]

NOTICE

Absolute maximum ratings are the extreme limits that the device will withstand without damage to the device. However, the electrical and mechanical characteristics are not guaranteed as the maximum limits (above recommended operating conditions) are approached, nor will the device necessarily operate at absolute maximum ratings.



Figure 1. Current Sourcing Output Block Diagram






Figure 2. Transfer Characteristics ($V_s = 5.0\text{ Vdc}$)




Linear Hall-effect Sensor ICs

Figure 3. Performance Graphics


Null Shift vs Temperature




Sensitivity Shift vs Temperature




Typical Frequency Response



Supply Current vs Temperature




Sensitivity per Volt vs Vsupply




SS39ET/SS49E/SS59ET Series

Figure 4. Mounting Dimensions (For reference only. mm/[in].)


SS39ET



Tape




Reel




Linear Hall-effect Sensor ICs

Figure 4. Mounting Dimensions (continued)



SS39ET/SS49E/SS59ET Series



Figure 4. Mounting Dimensions (continued)



sensing.honeywell.com 7

Linear Hall-effect Sensor ICs

Table 3. Order Guide

Catalog Listing	Description		Catalog Listing	Description	
SS39ET	Linear Hall-effect sensor IC, SOT-23, tape and reel packaging (3000 units per reel)		SS59ET	Linear Hall-effect sensor IC, SOT-89B, tape and reel packaging (1000 units per reel)	
SS49E	Linear Hall-effect sensor IC, flat TO-92-style, straight leads, 14,99 mm [0.59 in] lead length, 1,30 mm [0.05 in] spacing, bulk packaging (1000 units per bag)		SS49E-T3	Linear Hall-effect sensor IC, flat TO-92-style, tape-in-box (ammopack) packaging, straight leads (5000 units per box)	
SS49E-F	Linear Hall-effect sensor IC, flat TO-92-style, formed leads, 14,99 mm [0.59 in] lead length, 2,54 mm [0.10 in] spacing, bulk packaging (1000 units per bag)		SS49E-T2	Linear Hall-effect sensor IC, flat TO-92-style, tape-in-box (ammopack) packaging, formed leads (5000 units per box)	
SS49E-L	Linear Hall-effect sensor IC, flat TO-92-style, straight leads, 18,67 mm [0.75 in] lead length, 1,30 mm [0.05 in] spacing, bulk packaging (1000 units per bag)				

ADDITIONAL INFORMATION

The following associated literature is available at sensing.honeywell.com:

- Product line guide
- Product range guide
- Product installation instructions
- Application note

Find out more

Honeywell serves its customers through a worldwide network of sales offices, representatives and distributors. For application assistance, current specifications, pricing or name of the nearest Authorized Distributor, contact your local sales office.

To learn more about Honeywell's sensing and control products, call **+1-815-235-6847** or **1-800-537-6945**, visit **sensing.honeywell.com**, or e-mail inquiries to **info.sc@honeywell.com**

Sensing and Control
Honeywell
1985 Douglas Drive North
Golden Valley, MN 55422
honeywell.com

⚠ WARNING**PERSONAL INJURY**

DO NOT USE these products as safety or emergency stop devices or in any other application where failure of the product could result in personal injury.

Failure to comply with these instructions could result in death or serious injury.

⚠ WARNING**MISUSE OF DOCUMENTATION**

- The information presented in this product sheet is for reference only. Do not use this document as a product installation guide.
- Complete installation, operation, and maintenance information is provided in the instructions supplied with each product.

Failure to comply with these instructions could result in death or serious injury.

WARRANTY/REMEDY

Honeywell warrants goods of its manufacture as being free of defective materials and faulty workmanship. Honeywell's standard product warranty applies unless agreed to otherwise by Honeywell in writing; please refer to your order acknowledgement or consult your local sales office for specific warranty details. If warranted goods are returned to Honeywell during the period of coverage, Honeywell will repair or replace, at its option, without charge those items it finds defective. **The foregoing is buyer's sole remedy and is in lieu of all other warranties, expressed or implied, including those of merchantability and fitness for a particular purpose. In no event shall Honeywell be liable for consequential, special, or indirect damages.**

While we provide application assistance personally, through our literature and the Honeywell website, it is up to the customer to determine the suitability of the product in the application.

Specifications may change without notice. The information we supply is believed to be accurate and reliable as of this printing. However, we assume no responsibility for its use.

Honeywell

005850-4-EN IL50
February 2015
© 2015 Honeywell International Inc. All rights reserved.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:


[Honeywell:](#)

[SS49E](#) [SS49E-L](#) [SS39ET](#) [SS49E-F](#)

A.6 Hoja de datos pantalla LCD16D2


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

16 x 2 Character LCD

FEATURES

- Type: Character
- Display format: 16 x 2 characters
- Built-in controller: ST 7066 (or equivalent)
- Duty cycle: 1/16
- 5 x 8 dots includes cursor
- + 5 V power supply
- LED can be driven by pin 1, pin 2, or A and K
- N.V. optional for + 3 V power supply
- Optional: Smaller character size (2.95 mm x 4.35 mm)
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912



MECHANICAL DATA		
ITEM	STANDARD VALUE	UNIT
Module Dimension	80.0 x 36.0 x 13.2 (max.)	mm
Viewing Area	66.0 x 16.0	
Dot Size	0.55 x 0.65	
Dot Pitch	0.60 x 0.70	
Mounting Hole	75.0 x 31.0	
Character Size	2.95 x 5.55	

ABSOLUTE MAXIMUM RATINGS					
ITEM	SYMBOL	STANDARD VALUE			UNIT
		MIN.	TYP.	MAX.	
Power Supply	V_{DD} to V_{SS}	- 0.3	-	13	V
Input Voltage	V_I	V_{SS}	-	V_{DD}	

Note

- $V_{SS} = 0$ V, $V_{DD} = 5.0$ V

ELECTRICAL CHARACTERISTICS						
ITEM	SYMBOL	CONDITION	STANDARD VALUE			UNIT
			MIN.	TYP.	MAX.	
Input Voltage	V_{DD}	$V_{DD} = + 5$ V	4.5	5.0	5.5	V
Supply Current	I_{DD}	$V_{DD} = + 5$ V	1.0	1.2	1.5	mA
Recommended LC Driving Voltage for Normal Temperature Version Module	V_{DD} to V_0	- 20 °C	-	-	5.2	V
		0 °C	-	-	-	
		25 °C	-	3.7	-	
		50 °C	-	-	-	
		70 °C	3.1	-	-	
LED Forward Voltage	V_F	25 °C	-	4.2	4.6	V
LED Forward Current - Array	I_F	25 °C	-	100	-	mA
LED Forward Current - Edge			-	20	40	
EL Power Supply Current	I_{EL}	$V_{EL} = 110$ V _{AC} , 400 Hz	-	-	5.0	mA

DISPLAY CHARACTER ADDRESS CODE																
Display Position																
	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
DD RAM Address	00	01	02	03	04	05	06	07	08	09	0A	0B	0C	0D	0E	0F
DD RAM Address	40	41	42	43	44	45	46	47	48	49	4A	4B	4C	4D	4E	4F

Revision: 18-Mar-13

1

Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000




www.vishay.com

LCD-016N002B-CFH-ET

Vishay

Interface Pin Function		
PIN NO.	SYMBOL	FUNCTION
1	V _{SS}	Ground
2	V _{DD}	Supply voltage for logic
3	V ₀	Operating voltage for LCD
4	RS	H: Data/L: Instruction code
5	R/ $\overline{W}$	H: Read (MPU → Module)/L: Write (MPU → Module)
6	E	H → L chip enable signal
7	DB0	Data bus line
8	DB1	Data bus line
9	DB2	Data bus line
10	DB3	Data bus line
11	DB4	Data bus line
12	DB5	Data bus line
13	DB6	Data bus line
14	DB7	Data bus line
15	A	Supply power for LED+
16	R	Supply power for Red-
17	G	Supply power for Green-
18	B	Supply power for Blue-

DIMENSIONS in millimeters



Revision: 18-Mar-13

2

Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

1. Module Classification Information

LCD -016 N 002 B -C F H -ET

① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

1. Brand : Vishay Intertechnology, Inc.
2. Horizontal Format: 16 characters
3. Display Type : N→Character Type, H→Graphic Type
4. Vertical Format: 2 Lines
5. Model serials no.: B
6. Backlight N→Without backlight A→LED, Amber
 Type : B→EL, Blue green R→LED, Red
 D→EL, Green O→LED, Orange
 W→EL, White G→LED, Green
 F→CCFL, White T→LED, White
 Y→LED, Yellow Green C→LED, RGB color
7. LCD B→TN Positive, Gray T→FSTN Negative
 Mode : N→TN Negative,
 G→STN Positive, Gray
 Y→STN Positive, Yellow Green
 M→STN Negative, Blue
 F→FSTN Positive
8. LCD A→Reflective, N.T, 6:00 H→Transflective, W.T,6:00
 Polarize D→Reflective, N.T, 12:00 K→Transflective, W.T,12:00
 Type/ G→Reflective, W. T, 6:00 C→Transmissive, N.T,6:00
 Temperatur J→Reflective, W. T, 12:00 F→Transmissive, N.T,12:00
 e range/ B→Transflective, N.T,6:00 I→Transmissive, W. T, 6:00
 View E→Transflective, N.T,12:00 L→Transmissive, W.T,12:00
 direction
9. Special ET : English and European standard font
 Code Compliant with the ROHS Directions and regulations

Revision: 18-Mar-13

3

Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT
 ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

2.Precautions in use of LCD Modules

- (1) Avoid applying excessive shocks to the module or making any alterations or modifications to it.
- (2) Don't make extra holes on the printed circuit board, modify its shape or change the components of LCD module.
- (3) Don't disassemble the LCM.
- (4) Don't operate it above the absolute maximum rating.
- (5) Don't drop, bend or twist LCM.
- (6) Soldering: only to the I/O terminals.
- (7) Storage: please storage in anti-static electricity container and clean environment.

3.General Specification

Item	Dimension	Unit
Number of Characters	16 characters x 2 Lines	—
Module dimension	80.0 x 36.0 x 13.2(MAX)	mm
View area	66.0 x 16.0	mm
Active area	56.2 x 11.5	mm
Dot size	0.55 x 0.65	mm
Dot pitch	0.60 x 0.70	mm
Character size	2.95 x 5.55	mm
Character pitch	3.55 x 5.95	mm
LCD type	FSTN Positive, Transflective	
Duty	1/16	
View direction	6 o'clock	
Backlight Type	LED, Triple-color	

Revision: 18-Mar-13

4

Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

4. Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	T_{OP}	-20	—	+70	°C
Storage Temperature	T_{ST}	-30	—	+80	°C
Input Voltage	V_I	V_{SS}	—	V_{DD}	V
Supply Voltage For Logic	$V_{DD}-V_{SS}$	-0.3	—	7	V
Supply Voltage For LCD	$V_{DD}-V_0$	-0.3	—	13	V

5. Electrical Characteristics

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage For Logic	$V_{DD}-V_{SS}$	—	4.5	5.0	5.5	V
Supply Voltage For LCD	$V_{DD}-V_0$	$T_a=-20^{\circ}\text{C}$	—	—	5.2	V
		$T_a=25^{\circ}\text{C}$	—	3.7	—	V
		$T_a=70^{\circ}\text{C}$	3.1	—	—	V
Input High Volt.	V_{IH}	—	0.7	—	V_{DD}	V
Input Low Volt.	V_{IL}	—	0	—	0.6	V
Output High Volt.	V_{OH}	—	3.9	—	V_{DD}	V
Output Low Volt.	V_{OL}	—	0	—	0.4	V
Supply Current	I_{DD}	$V_{DD}=5\text{V}$	1.0	1.2	1.5	mA

Revision: 18-Mar-13

5

Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT
ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000



www.vishay.com
LCD-016N002B-CFH-ET

Vishay


6. Optical Characteristics

Item	Symbol	Condition	Min	Typ	Max	Unit
View Angle	(V) θ	$CR \geq 5$	30	—	60	deg
	(H) φ	$CR \geq 5$	-45	—	45	deg
Contrast Ratio	CR	—	—	5	—	—
Response Time	T rise	—	—	150	200	ms
	T fall	—	—	150	200	ms

Definition of Operation Voltage (Vop)




Definition of Response Time (Tr, Tf)



Conditions :

Operating Voltage : Vop Viewing Angle(θ , φ) : 0° , 0°
 Frame Frequency : 64 HZ Driving Waveform : 1/N duty , 1/a bias

Definition of viewing angle($CR \geq 2$)



Revision: 18-Mar-13

6

Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

7.Interface Pin Function

Pin No.	Symbol	Level	Description
1	V _{SS}	0V	Ground
2	V _{DD}	5.0V	Supply Voltage for logic
3	VO	(Variable)	Operating voltage for LCD
4	RS	H/L	H: DATA, L: Instruction code
5	R/W	H/L	H: Read(MPU→Module) L: Write(MPU→Module)
6	E	H,H→L	Chip enable signal
7	DB0	H/L	Data bus line
8	DB1	H/L	Data bus line
9	DB2	H/L	Data bus line
10	DB3	H/L	Data bus line
11	DB4	H/L	Data bus line
12	DB5	H/L	Data bus line
13	DB6	H/L	Data bus line
14	DB7	H/L	Data bus line
15	A	—	Supply power for LED +
16	R	—	Supply power for Red -
17	G		Supply power for Green -
18	B		Supply power for Blue -

Revision: 18-Mar-13

7



Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT
ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

8. Contour Drawing & Block Diagram

Character located	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
DDRAM address	00	01	02	03	04	05	06	07	08	09	0A	0B	0C	0D	0E	0F
DDRAM address	40	41	42	43	44	45	46	47	48	49	4A	4B	4C	4D	4E	4F

Revision: 18-Mar-13

8

Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT
ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

9. Function Description

The LCD display Module is built in a LSI controller, the controller has two 8-bit registers, an instruction register (IR) and a data register (DR).

The IR stores instruction codes, such as display clear and cursor shift, and address information for display data RAM (DDRAM) and character generator (CGRAM). The IR can only be written from the MPU. The DR temporarily stores data to be written or read from DDRAM or CGRAM. When address information is written into the IR, then data is stored into the DR from DDRAM or CGRAM. By the register selector (RS) signal, these two registers can be selected.

RS	R/W	Operation
0	0	IR write as an internal operation (display clear, etc.)
0	1	Read busy flag (DB7) and address counter (DB0 to DB7)
1	0	Write data to DDRAM or CGRAM (DR to DDRAM or CGRAM)
1	1	Read data from DDRAM or CGRAM (DDRAM or CGRAM to DR)

Busy Flag (BF)


When the busy flag is 1, the controller LSI is in the internal operation mode, and the next instruction will not be accepted. When RS=0 and R/W=1, the busy flag is output to DB7. The next instruction must be written after ensuring that the busy flag is 0.

Address Counter (AC)

The address counter (AC) assigns addresses to both DDRAM and CGRAM

Display Data RAM (DDRAM)

This DDRAM is used to store the display data represented in 8-bit character codes. Its extended capacity is 80x8 bits or 80 characters. Below figure is the relationship between DDRAM addresses and positions on the liquid crystal display.




www.vishay.com
LCD-016N002B-CFH-ET

Vishay

Display position DDRAM address

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
00	01	02	03	04	05	06	07	08	09	0A	0B	0C	0D	0E	0F
40	41	42	43	44	45	46	47	48	49	4A	4B	4C	4D	4E	4F

2-Line by 16-Character Display

Character Generator ROM (CGROM)

The CGROM generate 5×8 dot or 5×10 dot character patterns from 8-bit character codes. See Table 2.

Character Generator RAM (CGRAM)

In CGRAM, the user can rewrite character by program. For 5×8 dots, eight character patterns can be written, and for 5×10 dots, four character patterns can be written.

Write into DDRAM the character code at the addresses shown as the left column of table 1. To show the character patterns stored in CGRAM.


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

Relationship between CGRAM Addresses, Character Codes (DDRAM) and Character patterns
Table 1.

For 5 * 8 dot character patterns

Character Codes (DDRAM data)								CGRAM Address								Character Patterns (CGRAM data)																															
7	6	5	4	3	2	1	0	5	4	3	2	1	0	7	6	5	4	3	2	1	0																										
High				Low				High				Low				High				Low																											
0 0 0 0 * 0 0 0								0 0 0				0	0	0	*	*	*	0	0	0	0	Character pattern(1)	0																								
												0	0	1	*	*	*	0	0	0	0																										
												0	1	0	*	*	*	0	0	0	0																										
												0	1	1	*	*	*	0	0	0	0																										
												0 0 0 0 * 0 0 1								0 0 1				0	0	0	*	*	*	0	0	0	0	Cursor pattern	0												
																								0	0	1	*	*	*	0	0	0	0														
																								0	1	0	*	*	*	0	0	0	0														
																								0	1	1	*	*	*	0	0	0	0														
																																				1	0	0	*	*	*	0	0	0	0	Character pattern(2)	0
																																				1	0	1	*	*	*	0	0	0	0		
1	1	0	*	*	*	0	0	0	0																																						
1	1	1	*	*	*	0	0	0	0																																						
																								0	0	0	*	*	*	0	0	0	0	Cursor pattern	0												
																								0	0	1	*	*	*	0	0	0	0														
												0 0 0 0 * 1 1 1								1 1 1				1	0	0	*	*	*	0	0	0	0				0										
																								1	0	1	*	*	*	0	0	0	0														
1	1	0	*	*	*	0	0	0	0																																						
1	1	1	*	*	*	0	0	0	0																																						
												*	*	*											0																						

For 5 * 10 dot character patterns

Character Codes (DDRAM data)								CGRAM Address								Character Patterns (CGRAM data)												
7	6	5	4	3	2	1	0	5				4	3	2	1	0	7	6	5	4	3	2	1	0				
High				Low				High				Low				High				Low								
0 0 0 0 * 0 0 0								0 0								0	0	0	0	*	*	*	0	0	0	0	0	Character pattern
																0	0	0	1	*	*	*	0	0	0	0	0	
																0	0	1	0	*	*	*	0	0	0	0	0	
																0	0	1	1	*	*	*	0	0	0	0	0	
																0	1	0	0	*	*	*	0	0	0	0	0	
																0	1	0	1	*	*	*	0	0	0	0	0	
																0	1	1	1	*	*	*	0	0	0	0	0	
																1	0	0	0	*	*	*	0	0	0	0	0	
																1	0	0	1	*	*	*	0	0	0	0	0	
																1	0	1	0	*	*	*	0	0	0	0	0	
																				*	*	*						
																				*	*	*						
																1	1	1	1	*	*	*						
																				*	*	*						

■ : " High "


www.vishay.com

LCD-016N002B-CFH-ET

Vishay

10.Character Generator ROM Pattern

Table.2

Upper 4 bit Lower 4 bit	LLLL	LLH	LLHL	LLHH	LHLL	LHLH	LHHL	LHHH	HLLL	HLLH	HLHL	HLHH	HHLL	HHLH	HHHL	HHHH
LLLL	CG RAM (1)	±			0	1	2	3	4	5	6	7	8	9	A	B
LLH	CG RAM (2)	≡	.	1	2	3	4	5	6	7	8	9	A	B	C	D
LLHL	CG RAM (3)	7	"	2	3	4	5	6	7	8	9	A	B	C	D	E
LLHH	CG RAM (4)	L	#	3	4	5	6	7	8	9	A	B	C	D	E	F
LHLL	CG RAM (5)	7	#	4	5	6	7	8	9	A	B	C	D	E	F	G
LHLH	CG RAM (6)	7	%	5	6	7	8	9	A	B	C	D	E	F	G	H
LHHL	CG RAM (7)	7	%	6	7	8	9	A	B	C	D	E	F	G	H	I
LHHH	CG RAM (8)	7	'	7	8	9	A	B	C	D	E	F	G	H	I	J
HLLL	CG RAM (1)	7	<	8	9	A	B	C	D	E	F	G	H	I	J	K
HLLH	CG RAM (2)	7	>	9	A	B	C	D	E	F	G	H	I	J	K	L
HLHL	CG RAM (3)	8	*	#	J	K	L	M	N	O	P	Q	R	S	T	U
HLHH	CG RAM (4)	7	+	;	<	C	K	C	I	R	3	4	5	6	7	8
HHLL	CG RAM (5)	≡	.	<	L	\	1	1	1	2	3	4	5	6	7	8
HHLH	CG RAM (6)	7	-	=	7	1	n	3	1	3	3	4	5	6	7	8
HHHL	CG RAM (7)	8	.	>	N	n	~	2	3	3	4	5	6	7	8	9
HHHH	CG RAM (8)	8	/	?	0	L	o	4	4	4	5	6	7	8	9	0

Revision: 18-Mar-13

12

Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT
ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

11. Instruction Table

Instruction	Instruction Code										Description	Execution time (fosc=270Khz)
	RS	R/W	DB7	DB6	DB5	DB4	DB3	DB2	DB1	DB0		
Clear Display	0	0	0	0	0	0	0	0	0	1	Write "00H" to DDRAM and set DDRAM address to "00H" from AC	1.53ms
Return Home	0	0	0	0	0	0	0	0	1	—	Set DDRAM address to "00H" from AC and return cursor to its original position if shifted. The contents of DDRAM are not changed.	1.53ms
Entry Mode Set	0	0	0	0	0	0	0	1	I/D	SH	Assign cursor moving direction and enable the shift of entire display.	39 μ s
Display ON/OFF Control	0	0	0	0	0	0	1	D	C	B	Set display (D), cursor (C), and blinking of cursor (B) on/off control bit.	39 μ s
Cursor or Display Shift	0	0	0	0	0	1	S/C	R/L	—	—	Set cursor moving and display shift control bit, and the direction, without changing of DDRAM data.	39 μ s
Function Set	0	0	0	0	1	DL	N	F	—	—	Set interface data length (DL:8-bit/4-bit), numbers of display line (N:2-line/1-line)and, display font type (F:5x11 dots/5x8 dots)	39 μ s
Set CGRAM Address	0	0	0	1	AC5	AC4	AC3	AC2	AC1	AC0	Set CGRAM address in address counter.	39 μ s
Set DDRAM Address	0	0	1	AC6	AC5	AC4	AC3	AC2	AC1	AC0	Set DDRAM address in address counter.	39 μ s
Read Busy Flag and Address	0	1	BF	AC6	AC5	AC4	AC3	AC2	AC1	AC0	Whether during internal operation or not can be known by reading BF. The contents of address counter can also be read.	0 μ s
Write Data to RAM	1	0	D7	D6	D5	D4	D3	D2	D1	D0	Write data into internal RAM (DDRAM/CGRAM).	43 μ s
Read Data from RAM	1	1	D7	D6	D5	D4	D3	D2	D1	D0	Read data from internal RAM (DDRAM/CGRAM).	43 μ s

* "—" : don't care



www.vishay.com
LCD-016N002B-CFH-ET

Vishay

12. Timing Characteristics

12.1 Write Operation

- Writing data from MPU



Ta=25°C, VDD=5.0V


Item	Symbol	Min	Typ	Max	Unit
Enable cycle time	T_C	1200	—	—	ns
Enable pulse width	T_{PW}	140	—	—	ns
Enable rise/fall time	T_R, T_F	—	—	25	ns
Address set-up time (RS, R/W to E)	t_{AS}	0	—	—	ns
Address hold time	t_{AH}	10	—	—	ns
Data set-up time	t_{DSW}	40	—	—	ns
Data hold time	t_H	10	—	—	ns


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

12.2 Read Operation

- Reading data from ST7066U




Ta=25°C, VDD=5V

Item	Symbol	Min	Typ	Max	Unit
Enable cycle time	T_C	1200	—	—	ns
Enable pulse width (high level)	T_{PW}	140	—	—	ns
Enable rise/fall time	T_R, T_F	—	—	25	ns
Address set-up time (RS, R/W to E)	t_{AS}	0	—	—	ns
Address hold time	t_{AH}	10	—	—	ns
Data delay time	t_{DDR}	—	—	100	ns
Data hold time	t_H	10	—	—	ns


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

13. Initializing of LCM

4-Bit Ineterface

Revision: 18-Mar-13

16


Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT
ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay



8-Bit Ineterface

Revision: 18-Mar-13

17

Document Number: 37484

For technical questions, contact: displays@vishay.com


THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT
ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

14. Reliability

Content of Reliability Test (wide temperature, -20°C~70°C)

Environmental Test			
Test Item	Content of Test	Test Condition	Note
High Temperature storage	Endurance test applying the high storage temperature for a long time.	80°C 200hrs	2
Low Temperature storage	Endurance test applying the high storage temperature for a long time.	-30°C 200hrs	1,2
High Temperature Operation	Endurance test applying the electric stress (Voltage & Current) and the thermal stress to the element for a long time.	70°C 200hrs	—
Low Temperature Operation	Endurance test applying the electric stress under low temperature for a long time.	-20°C 200hrs	1
High Temperature/ Humidity Operation	The module should be allowed to stand at 60°C, 90%RH max For 96hrs under no-load condition excluding the polarizer, Then taking it out and drying it at normal temperature.	60°C, 90%RH 96hrs	1,2
Thermal shock resistance	The sample should be allowed stand the following 10 cycles of operation -20°C 25°C 70°C 	-20°C/70°C 10 cycles	—
Vibration test	Endurance test applying the vibration during transportation and using.	Total fixed amplitude : 1.5mm Vibration Frequency : 10~55Hz One cycle 60 seconds to 3 directions of X,Y,Z for Each 15 minutes	3
Static electricity test	Endurance test applying the electric stress to the terminal.	VS=800V, RS=1.5kΩ CS=100pF 1 time	—

Note1: No dew condensation to be observed.

Note2: The function test shall be conducted after 4 hours storage at the normal Temperature and humidity after remove from the test chamber.

Note3: Vibration test will be conducted to the product itself without putting it in a container.

Revision: 18-Mar-13

18

Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com

LCD-016N002B-CFH-ET

Vishay

15. Backlight Information

Specification

PARAMETER	SYMBOL		MIN	TYP	MAX	UNIT	TEST CONDITION
Supply Current	ILED	R	20	24	28	mA	V=5.0V
		G	25	30	34		
		B	25	30	34		
Supply Voltage	V		4.9	5.0	5.1	V	—
Reverse Voltage	VR		—	7.0	—	V	—
Luminous Intensity	IV	R	32	40	—	CD/M²	ILED(red)=24mA
		G	140	180			ILED(green)=30mA
		B	22	28			ILED(blue)=30mA
Wave Length	λ	R	620	625	630	nm	—
		G	515	520	525		
		B	465	470	475		
Life Time	R	80K	100K		Hr.	ILED≤15mA For each LED Lamp	
	G	40K	50K				
	B	40K	50K				
Color	Red, Green, Blue						

Note:

1. The LED B/L of “triple color” is designed for voltage driving, user have to follow The drive voltage that can make driving current in safety range (current between minimum and maximum).
2. Owing to having 3 chips in one LED lamp, which caused many combinations of different wave length. This situation will caused wave length shifting while driving 2 colors or more in the same time.
3. The luminous intensity is measured on B/L surface only.

Revision: 18-Mar-13

19

Document Number: 37484


For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

1 Backlight Drive Method



The driving circuit of suggestion is showed as above, owing to B/L being designed
In parallel mode, so user can use transistor ~ FET or TRIC to control.

Revision: 18-Mar-13

20

Document Number: 37484



For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT
ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

16. Inspection specification

NO	Item	Criterion	AQL																								
01	Electrical Testing	1.1 Missing vertical, horizontal segment, segment contrast defect. 1.2 Missing character , dot or icon. 1.3 Display malfunction. 1.4 No function or no display. 1.5 Current consumption exceeds product specifications. 1.6 LCD viewing angle defect. 1.7 Mixed product types. 1.8 Contrast defect.	0.65																								
02	Black or white spots on LCD (display only)	2.1 White and black spots on display $\leq 0.25\text{mm}$, no more than three white or black spots present. 2.2 Densely spaced: No more than two spots or lines within 3mm	2.5																								
03	LCD black spots, white spots, contamination (non-display)	3.1 Round type : As following drawing $\Phi = (x + y) / 2$  <table border="1"> <thead> <tr> <th>SIZE</th> <th>Acceptable Q TY</th> </tr> </thead> <tbody> <tr> <td>$\Phi \leq 0.10$</td> <td>Accept no dense</td> </tr> <tr> <td>$0.10 < \Phi \leq 0.20$</td> <td>2</td> </tr> <tr> <td>$0.20 < \Phi \leq 0.25$</td> <td>1</td> </tr> <tr> <td>$0.25 < \Phi$</td> <td>0</td> </tr> </tbody> </table> 3.2 Line type : (As following drawing)  <table border="1"> <thead> <tr> <th>Length</th> <th>Width</th> <th>Acceptable Q TY</th> </tr> </thead> <tbody> <tr> <td>---</td> <td>$W \leq 0.02$</td> <td>Accept no dense</td> </tr> <tr> <td>$L \leq 3.0$</td> <td>$0.02 < W \leq 0.03$</td> <td rowspan="2">2</td> </tr> <tr> <td>$L \leq 2.5$</td> <td>$0.03 < W \leq 0.05$</td> </tr> <tr> <td>---</td> <td>$0.05 < W$</td> <td>As round type</td> </tr> </tbody> </table>	SIZE	Acceptable Q TY	$\Phi \leq 0.10$	Accept no dense	$0.10 < \Phi \leq 0.20$	2	$0.20 < \Phi \leq 0.25$	1	$0.25 < \Phi$	0	Length	Width	Acceptable Q TY	---	$W \leq 0.02$	Accept no dense	$L \leq 3.0$	$0.02 < W \leq 0.03$	2	$L \leq 2.5$	$0.03 < W \leq 0.05$	---	$0.05 < W$	As round type	2.5
SIZE	Acceptable Q TY																										
$\Phi \leq 0.10$	Accept no dense																										
$0.10 < \Phi \leq 0.20$	2																										
$0.20 < \Phi \leq 0.25$	1																										
$0.25 < \Phi$	0																										
Length	Width	Acceptable Q TY																									
---	$W \leq 0.02$	Accept no dense																									
$L \leq 3.0$	$0.02 < W \leq 0.03$	2																									
$L \leq 2.5$	$0.03 < W \leq 0.05$																										
---	$0.05 < W$	As round type																									
04	Polarizer bubbles	If bubbles are visible, judge using black spot specifications, not easy to find, must check in specify direction. <table border="1"> <thead> <tr> <th>Size Φ</th> <th>Acceptable Q TY</th> </tr> </thead> <tbody> <tr> <td>$\Phi \leq 0.20$</td> <td>Accept no dense</td> </tr> <tr> <td>$0.20 < \Phi \leq 0.50$</td> <td>3</td> </tr> <tr> <td>$0.50 < \Phi \leq 1.00$</td> <td>2</td> </tr> <tr> <td>$1.00 < \Phi$</td> <td>0</td> </tr> <tr> <td>Total Q TY</td> <td>3</td> </tr> </tbody> </table>	Size Φ	Acceptable Q TY	$\Phi \leq 0.20$	Accept no dense	$0.20 < \Phi \leq 0.50$	3	$0.50 < \Phi \leq 1.00$	2	$1.00 < \Phi$	0	Total Q TY	3	2.5												
Size Φ	Acceptable Q TY																										
$\Phi \leq 0.20$	Accept no dense																										
$0.20 < \Phi \leq 0.50$	3																										
$0.50 < \Phi \leq 1.00$	2																										
$1.00 < \Phi$	0																										
Total Q TY	3																										

Revision: 18-Mar-13



21

Document Number: 37484

For technical questions, contact: displays@vishay.com
 THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT
 ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

NO	Item	Criterion	AQL																		
05	Scratches	Follow NO.3 LCD black spots, white spots, contamination																			
06	Chipped glass	Symbols Define: x: Chip length y: Chip width z: Chip thickness k: Seal width t: Glass thickness a: LCD side length L: Electrode pad length: 6.1 General glass chip : 6.1.1 Chip on panel surface and crack between panels:  <table><tr><td>z: Chip thickness</td><td>y: Chip width</td><td>x: Chip length</td></tr><tr><td>$Z \leq 1/2t$</td><td>Not over viewing area</td><td>$x \leq 1/8a$</td></tr><tr><td>$1/2t < z \leq 2t$</td><td>Not exceed 1/3k</td><td>$x \leq 1/8a$</td></tr></table> ⊙If there are 2 or more chips, x is total length of each chip. 6.1.2 Corner crack:  <table><tr><td>z: Chip thickness</td><td>y: Chip width</td><td>x: Chip length</td></tr><tr><td>$Z \leq 1/2t$</td><td>Not over viewing area</td><td>$x \leq 1/8a$</td></tr><tr><td>$1/2t < z \leq 2t$</td><td>Not exceed 1/3k</td><td>$x \leq 1/8a$</td></tr></table> ⊙If there are 2 or more chips, x is the total length of each chip.	z: Chip thickness	y: Chip width	x: Chip length	$Z \leq 1/2t$	Not over viewing area	$x \leq 1/8a$	$1/2t < z \leq 2t$	Not exceed 1/3k	$x \leq 1/8a$	z: Chip thickness	y: Chip width	x: Chip length	$Z \leq 1/2t$	Not over viewing area	$x \leq 1/8a$	$1/2t < z \leq 2t$	Not exceed 1/3k	$x \leq 1/8a$	2.5
z: Chip thickness	y: Chip width	x: Chip length																			
$Z \leq 1/2t$	Not over viewing area	$x \leq 1/8a$																			
$1/2t < z \leq 2t$	Not exceed 1/3k	$x \leq 1/8a$																			
z: Chip thickness	y: Chip width	x: Chip length																			
$Z \leq 1/2t$	Not over viewing area	$x \leq 1/8a$																			
$1/2t < z \leq 2t$	Not exceed 1/3k	$x \leq 1/8a$																			

Revision: 18-Mar-13

22




Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT
ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

NO	Item	Criterion	AQL						
06	Glass crack	Symbols : x: Chip length y: Chip width z: Chip thickness k: Seal width t: Glass thickness a: LCD side length L: Electrode pad length 6.2 Protrusion over terminal : 6.2.1 Chip on electrode pad :							
									
		<table><tr><td>y: Chip width</td><td>x: Chip length</td><td>z: Chip thickness</td></tr><tr><td>$y \leq 0.5\text{mm}$</td><td>$x \leq 1/8a$</td><td>$0 < z \leq t$</td></tr></table>	y: Chip width	x: Chip length	z: Chip thickness	$y \leq 0.5\text{mm}$	$x \leq 1/8a$	$0 < z \leq t$	
		y: Chip width	x: Chip length	z: Chip thickness					
		$y \leq 0.5\text{mm}$	$x \leq 1/8a$	$0 < z \leq t$					
6.2.2 Non-conductive portion:									
									
		<table><tr><td>y: Chip width</td><td>x: Chip length</td><td>z: Chip thickness</td></tr><tr><td>$y \leq L$</td><td>$x \leq 1/8a$</td><td>$0 < z \leq t$</td></tr></table> ⊙ If the chipped area touches the ITO terminal, over 2/3 of the ITO must remain and be inspected according to electrode terminal specifications. ⊙ If the product will be heat sealed by the customer, the alignment mark not be damaged. 6.2.3 Substrate protuberance and internal crack. 	y: Chip width	x: Chip length	z: Chip thickness	$y \leq L$	$x \leq 1/8a$	$0 < z \leq t$	
y: Chip width	x: Chip length	z: Chip thickness							
$y \leq L$	$x \leq 1/8a$	$0 < z \leq t$							
		<table><tr><td>y: width</td><td>x: length</td></tr><tr><td>$y \leq 1/3L$</td><td>$x \leq a$</td></tr></table>	y: width	x: length	$y \leq 1/3L$	$x \leq a$	2.5		
y: width	x: length								
$y \leq 1/3L$	$x \leq a$								

Revision: 18-Mar-13

23


Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT
ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

NO	Item	Criterion	AQL
07	Cracked glass	The LCD with extensive crack is not acceptable.	2.5
08	Backlight elements	8.1 Illumination source flickers when lit. 8.2 Spots or scratched that appear when lit must be judged. Using LCD spot, lines and contamination standards. 8.3 Backlight doesn't light or color wrong.	0.65 2.5 0.65
09	Bezel	9.1 Bezel may not have rust, be deformed or have fingerprints, stains or other contamination. 9.2 Bezel must comply with job specifications.	2.5 0.65
10	PCB、COB	10.1 COB seal may not have pinholes larger than 0.2mm or contamination. 10.2 COB seal surface may not have pinholes through to the IC. 10.3 The height of the COB should not exceed the height indicated in the assembly diagram. 10.4 There may not be more than 2mm of sealant outside the seal area on the PCB. And there should be no more than three places. 10.5 No oxidation or contamination PCB terminals. 10.6 Parts on PCB must be the same as on the production characteristic chart. There should be no wrong parts, missing parts or excess parts. 10.7 The jumper on the PCB should conform to the product characteristic chart. 10.8 If solder gets on bezel tab pads, LED pad, zebra pad or screw hold pad, make sure it is smoothed down. 10.9 The Scraping testing standard for Copper Coating of PCB  $X * Y \leq 2\text{mm}^2$	2.5 2.5 0.65 2.5 2.5 0.65 0.65 2.5 2.5
11	Soldering	11.1 No un-melted solder paste may be present on the PCB. 11.2 No cold solder joints, missing solder connections, oxidation or icicle. 11.3 No residue or solder balls on PCB. 11.4 No short circuits in components on PCB.	2.5 2.5 2.5 0.65

Revision: 18-Mar-13

24

Document Number: 37484

For technical questions, contact: displays@vishay.comTHIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


www.vishay.com
LCD-016N002B-CFH-ET

Vishay

NO	Item	Criterion	AQL
12	General appearance	12.1 No oxidation, contamination, curves or, bends on interface Pin (OLB) of TCP.	2.5
		12.2 No cracks on interface pin (OLB) of TCP.	0.65
		12.3 No contamination, solder residue or solder balls on product.	2.5
		12.4 The IC on the TCP may not be damaged, circuits.	2.5
		12.5 The uppermost edge of the protective strip on the interface pin must be present or look as if it causes the interface pin to sever.	2.5
		12.6 The residual rosin or tin oil of soldering (component or chip component) is not burned into brown or black color.	2.5
		12.7 Sealant on top of the ITO circuit has not hardened.	0.65
		12.8 Pin type must match type in specification sheet.	0.65
		12.9 LCD pin loose or missing pins.	0.65
		12.10 Product packaging must the same as specified on packaging specification sheet.	0.65
		12.11 Product dimension and structure must conform to product specification sheet.	0.65

Revision: 18-Mar-13

25

Document Number: 37484

For technical questions, contact: displays@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

www.vishay.com**Legal Disclaimer Notice**

Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

© 2025 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED


Revision: 01-Jan-2025

1

Document Number: 91000

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

A.7 Hoja de datos potenciómetro 3296Y1102



Features

- Multiturn / Cermet / Industrial / Sealed
- 5 terminal styles
- Tape and reel packaging available
- Chevron seal design
- Listed on the QPL for style RJ24 per MIL-R-22097 and RJR24 per High-Rel Mil-R-39035

- Mounting hardware available (H-117P)
- RoHS compliant* version available
- For trimmer applications/processing guidelines, [click here](#)

3296 - 3/8" Square Trimpot® Trimming Potentiometer

Electrical Characteristics

Standard Resistance Range 10 ohms to 2 megohms (see standard resistance table)
 Resistance Tolerance $\pm 10\%$ std. (tighter tolerance available)
 Absolute Minimum Resistance 1 $\%$ or 2 ohms max. (whichever is greater)
 Contact Resistance Variation 1.0 $\%$ or 3 ohms max. (whichever is greater)
 Adjustability
 Voltage $\pm 0.01\%$
 Resistance $\pm 0.05\%$
 Resolution Infinite
 Insulation Resistance 500 vdc, 1,000 megohms min.
 Dielectric Strength
 Sea Level 900 vac
 70,000 Feet 350 vac
 Effective Travel25 turns nom.

Environmental Characteristics

Power Rating (300 volts max.)
 70 °C 0.5 watt
 125 °C 0 watt
 Temperature Range -55 °C to +125 °C
 Temperature Coefficient ± 100 ppm/°C
 Seal Test 85 °C Fluorinert†
 Humidity MIL-STD-202 Method 103 96 hours
 (2 $\%$ Δ TR, 10 Megohms IR)
 Vibration 20 G (1 $\%$ Δ TR; 1 $\%$ Δ VR)
 Shock 100 G (1 $\%$ Δ TR; 1 $\%$ Δ VR)
 Load Life.. 1,000 hours 0.5 watt @ 70 °C
 (3 $\%$ Δ TR; 3 $\%$ or 3 ohms, whichever is greater, CRV)
 Rotational Life 200 cycles
 (4 $\%$ Δ TR; 3 $\%$ or 3 ohms, whichever is greater, CRV)
 Moisture Sensitivity Level N/A
 ESD Classification (HBM) 2

Physical Characteristics


Torque 3.0 oz-in. max.
 Mechanical Stops Wiper idles
 Terminals Solderable pins
 Weight 0.03 oz.
 Marking Manufacturer's trademark, resistance code, wiring diagram, date code, mfr's. model number and style
 Wiper 50 $\%$ (Actual TR) $\pm 10\%$
 Flammability U.L. 94V-0
 Standard Packaging 50 pcs. per tube
 Adjustment Tool H-90




WARNING
 Cancer and Reproductive Harm
www.P65Warnings.ca.gov

Product Dimensions


Common Dimensions




3296P



3296W



3296X




Standard Resistance Table



Resistance (Ohms)	Resistance Code
10	100
20	200
50	500
100	101
200	201
500	501
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
25,000	253
50,000	503
100,000	104
200,000	204
250,000	254
500,000	504
1,000,000	105
2,000,000	205

Popular values listed in boldface. Special resistances available.

3296Y



3296Z



DIMENSIONS: MM (INCHES)

TOLERANCES: ± 0.25 (0.010) EXCEPT WHERE NOTED

How To Order



3296 W - 1 - 103 LF

Model _____
 Style _____
 Standard or Modified _____
 Product Indicator _____
 -1 = Standard Product
 Resistance Code _____
 Packaging Designator _____
 Blank = Tube (Standard)
 R = Tape and Reel (X and W Pin Styles Only)
 A = Ammo Pack (X and W Pin Styles Only)
 Tape and reel material meets Antistatic ANSI/ESD 5541-2003 packaging standards.
 Terminations _____
 LF = 100 $\%$ Tin-plated (RoHS compliant)
 Blank = 90 $\%$ Tin / 10 $\%$ Lead-plated (Standard)
 Consult factory for other available options.

*RoHS Directive 2002/95/EC Jan. 27, 2003 including annex and RoHS Recast 2011/65/EU June 8, 2011.

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

†"Fluorinert" is a registered trademark of 3M Co.

3296 - 3/8 " Square Trimpot® Trimming Potentiometer**BOURNS®****Packaging Specifications****SIDE ADJUST
3296X-1****TOP ADJUST
3296W-1**

Meets EIA Specification 468.

REV. 06/18

"Trimpot" is a registered trademark of Bourns, Inc.

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at www.bourns.com/docs/legal/disclaimer.pdf.

Legal Disclaimer Notice**BOURNS®**

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain types of applications are based on Bourns' knowledge of typical requirements in generic applications. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Users should always verify the actual performance of the Bourns® product in their specific devices and applications, and make their own independent judgments regarding the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification. Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in nuclear, lifesaving, life-critical or life-sustaining applications, nor in any other applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage. Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any Bourns® products in such unauthorized applications might not be safe and thus is at the user's sole risk. Life-critical applications include devices identified by the U.S. Food and Drug Administration as Class III devices and generally equivalent classifications outside of the United States.

Bourns expressly identifies those Bourns® standard products that are suitable for use in automotive applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard products in an automotive application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk. If Bourns expressly identifies a sub-category of automotive application in the data sheet for its standard products (such as infotainment or lighting), such identification means that Bourns has reviewed its standard product and has determined that if such Bourns® standard product is considered for potential use in automotive applications, it should only be used in such sub-category of automotive applications. Any reference to Bourns® standard product in the data sheet as compliant with the AEC-Q standard or "automotive grade" does not by itself mean that Bourns has approved such product for use in an automotive application.

Bourns® standard products are not tested to comply with United States Federal Aviation Administration standards generally or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aircraft or space applications. Bourns expressly identifies Bourns® standard products that are suitable for use in aircraft or space applications on such products' data sheets in the section entitled "Applications." Unless expressly and specifically approved in writing by two authorized Bourns representatives on a case-by-case basis, use of any other Bourns® standard product in an aircraft or space application might not be safe and thus is not recommended, authorized or intended and is at the user's sole risk.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Users shall not sell, transfer, export or re-export any Bourns® products or technology for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology in any facility which engages in activities relating to such devices. The foregoing restrictions apply to all uses and applications that violate national or international prohibitions, including embargos or international regulations. Further, Bourns® products and Bourns technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products may not, without prior authorization from Bourns and/or the U.S. Government, be resold, transferred, or re-exported to any party not eligible to receive U.S. commodities, software, and technical data.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties, including implied warranties of fitness for particular purpose, non-infringement and merchantability.

For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:


Web Page: <http://www.bourns.com/legal/disclaimers-terms-and-policies>

PDF: <http://www.bourns.com/docs/Legal/disclaimer.pdf>

C1753 05/17/18R

Anexo B


Esquemático




Anexo C

PCB


C.1 Pistas de cobre de la cara superior




C.2 Pistas de cobre de la cara inferior



C.3 Serigrafía



C.4 Contorno de la PCB



Anexo D

Códigos Arduino IDE

D.1 Sensor BME280

```
1 //Sensor BME280 que mide Temperatura, Humedad y Presi n
2 //Conexiones Raspberry Pi Pico W
3 //Conectar SDA —> pin 11
4 //Conectar SCL —> pin 12
5 //Conectar VCC y CSB —> pin 36
6 //Conectar GND y SDO —> pin 38
7
8
9 #include <Wire.h>
10 #include <Adafruit_Sensor.h>
11 #include <Adafruit_BME280.h>
12
13 #define I2C_SDA 8 // GP8 – PIN 11
14 #define I2C_SCL 9 // GP9 – PIN 12
15
16 Adafruit_BME280 bme; // Crea el objeto del sensor
17
18 void setup() {
19     Serial.begin(115200);
20     Wire.setSDA(I2C_SDA);
21     Wire.setSCL(I2C_SCL);
22     Wire.begin();
23
24     if (!bme.begin(0x76)) {
25         Serial.println("Error: No se encontr el BME280.");
26         while (1);
27     }
28
29     Serial.println("BME280 detectado correctamente.");
30 }
31
32 void loop() {
33     Serial.print("Temperatura: ");
34     Serial.print(bme.readTemperature());
35     Serial.println(" C ");
36
37     Serial.print("Humedad: ");
38     Serial.print(bme.readHumidity());
39     Serial.println(" %");
40 }
```

```
41 Serial.print("Presi n: ");
42 Serial.print(bme.readPressure() / 100.0F);
43 Serial.println(" hPa");
44
45 Serial.println("_____");
46 delay(2000);
47 }
```

Listing D.1: Código sensor BME280.

D.2 Sensor GUVA-S12SD

```

1 //Sensor GUVA-S12SD que mide ndice UV
2 //Conexiones Raspberry Pi Pico W
3 //Conectar SIG —> pin 31
4 //Conectar VCC —> pin 36
5 //Conectar GND —> pin 38
6
7 #define UV_SENSOR_PIN 26 // GPIO26 = ADC0
8 #define FACTOR_CONVERSION 7.64 // Curva hallada (falta restar 1.97)
9
10 void setup() {
11     Serial.begin(115200);
12 }
13
14 void loop() {
15     int uv_raw = analogRead(UV_SENSOR_PIN);
16     uv = (uv_raw / 1023) * 3.3 * FACTOR_CONVERSION - 1.97;
17     String riesgo_uv;
18     if (uv < 3) {
19         riesgo_uv = "Bajo";
20     } else if (uv >= 3 && uv < 6) {
21         riesgo_uv = "Moderado";
22     } else if (uv >= 6 && uv < 8) {
23         riesgo_uv = "Alto";
24     } else if (uv >= 8 && uv < 11) {
25         riesgo_uv = "Muy Alto";
26     } else {
27         riesgo_uv = "Extremo";
28     }
29
30     Serial.print("Lectura ADC: ");
31     Serial.print(uv_raw);
32     Serial.println(" V ");
33
34     Serial.print(" ndice UV: ");
35     Serial.print(uv);
36     Serial.println(" UVI");
37
38     Serial.print(" Riesgo ");
39     Serial.println(riesgo_uv);
40
41     Serial.println("_____");
42
43     delay(1000);
44 }

```

Listing D.2: Código sensor GUVA-S12SD.

D.3 Veleta

```

1 // ETIQUETA VELETA APUNTA AL NORTE!!! y acordarse de poner
  resistencia
2
3 //Veleta ZTS-3000-FXJT-V05-360
4 //Conexiones Raspberry Pi Pico W
5 //Conectar Negro —> GND OUT Conversor y Patilla (1) Resistencia 270
6
7 //Conectar Marron —> VOUT Conversor
8 //Conectar Amarillo —> GND OUT Conversor y Patilla (1) Resistencia
  270
9 //Conectar Azul —> pin 32 y Patilla (2) Resistencia 270
10
11 //Converos a 10 Voltios
12 //GND IN —> pin 38
13 //VIN —> pin 36
14 //GND OUT —> Negro y Amarillo Veleta y RES1
15 //VOUT —> Marron Veleta
16
17 const int pinVeleta = 27; // GP27 es ADC1
18
19 void setup() {
20     Serial.begin(115200);
21 }
22
23 void loop() {
24     int lectura = analogRead(pinVeleta); // Leer se al anal gica
      (0-800 en Pico) 0/800 norte 0 , 200 este 90 , 400 sur 180 , 600
      oeste 270 ETIQUETA APUNTA AL NORTE!!!
25     float voltaje = lectura * (3.3 / 800.0); // Convertir a voltaje no
      se muy bien si es 800 o 4095
26
27
28     // Convertimos a grados
29     float grados = lectura * (360.0 / 800.0);
30
31
32     Serial.print("Valor ADC: ");
33     Serial.print(lectura);
34     Serial.print(" - Voltaje: ");
35     Serial.print(voltaje);
36     Serial.print(" - Grados: ");
37     Serial.println(grados);
38
39     if (grados > 350 || grados < 10) Serial.print("NORTE");
40     if (grados > 80 && grados < 100) Serial.print("ESTE");
41     if (grados > 170 && grados < 190) Serial.print("SUR");
42     if (grados > 260 && grados < 280) Serial.print("OESTE");
43
44     delay(500); // Leer cada medio segundo
45 }

```

Listing D.3: Código veleta.

D.4 Anemómetro

```

1 //Sensor de efecto Hall SS49E que mide la velocidad del viento
2 //Conexiones Raspberry Pi Pico W
3 //Conectar VCC (1) —> pin 36
4 //Conectar GND (2) —> pin 38
5 //Conectar Vout (3) —> pin 26
6
7
8 // Definiciones
9 const int pinAnemometro = 20; // Pin GPIO para el sensor Hall
10 const float CALIBRATION_FACTOR_ANEMOMETRO = 0.0377; // Factor de
    calibraci n 2*pi*r*60/1000 (r=0.1)
11 const unsigned long REPORTINTERVAL = 3000; // Intervalo de reporte en
    ms
12
13 // Variables para interrupciones
14 volatile unsigned long pulseCountAnem = 0;
15 volatile unsigned long lastPulseTimeAnem = 0;
16 float rpm = 0.0;
17 float windSpeedKmh = 0.0;
18
19 // Declaraci n anticipada (prototipo) de la funci n ISR
20 void hallSensorISR();
21
22 void setup() {
23     Serial.begin(115200);
24     while (!Serial); // Esperar inicializaci n serial
25
26     pinMode(pinAnemometro, INPUT_PULLUP);
27     attachInterrupt(digitalPinToInterrupt(pinAnemometro), hallSensorISR,
        RISING); // FALLING o RISING
28
29     Serial.println("Anem metro inicializado – Mediciones continuas");
30 }
31
32 void loop() {
33     static unsigned long lastReportTime = 0;
34     unsigned long currentTime = millis();
35
36     if (currentTime - lastReportTime >= REPORTINTERVAL) {
37         noInterrupts();
38         unsigned long pulses = pulseCountAnem;
39         unsigned long lastTime = lastPulseTimeAnem;
40         pulseCountAnem = 0;
41         interrupts();
42
43         if (pulses > 0 && lastTime > 0) {
44             float measurementTime = (currentTime - lastReportTime) / 1000.0;
45             rpm = (pulses / measurementTime) * 60.0;
46             windSpeedKmh = rpm * CALIBRATION_FACTOR_ANEMOMETRO;
47         } else {
48             rpm = 0.0;
49             windSpeedKmh = 0.0;
50         }
51
52         Serial.print("RPM: ");
53         Serial.print(rpm);

```

```
54     Serial.print(" | Velocidad: ");
55     Serial.print(windSpeedKmh);
56     Serial.print(" km/h | ");
57     Serial.print(windSpeedKmh / 3.6);
58     Serial.println(" m/s");
59
60     lastReportTime = currentTime;
61 }
62 }
63
64 // Implementaci3n de la ISR (ahora sin IRAM_ATTR que causaba
65 // problemas)
66 void hallSensorISR() {
67     pulseCountAnem++;
68     lastPulseTimeAnem = micros();
69     Serial.println(" + uno");
70 }
```

Listing D.4: C3digo anem3metro.

D.5 Pluviómetro

```

1 //Sensor de efecto Hall SS49E que mide la velocidad del viento
2 //Conexiones Raspberry Pi Pico W
3 //Conectar VCC (1) —> pin 36
4 //Conectar GND (2) —> pin 38
5 //Conectar Vout (3) —> pin 27
6
7
8 // Definiciones
9 const int HALL_SENSOR_PIN = 21; // Pin GPIO para el sensor Hall
10 const float CALIBRATION_FACTOR = 3.7; // Factor de calibración 3.7
    ml cada balanceo
11 const unsigned long REPORT_INTERVAL = 3000; // Intervalo de reporte en
    ms
12
13 // Variables para interrupciones
14 volatile unsigned long pulseCount = 0;
15 volatile unsigned long lastPulseTime = 0;
16 float contador_min = 0.0;
17 float cantidad_ml = 0.0;
18
19 // Declaración anticipada (prototipo) de la función ISR
20 void hallSensorISR();
21
22 void setup() {
23     Serial.begin(115200);
24     while (!Serial); // Esperar inicialización serial
25
26     pinMode(HALL_SENSOR_PIN, INPUT_PULLUP);
27     attachInterrupt(digitalPinToInterrupt(HALL_SENSOR_PIN),
        hallSensorISR, RISING); // FALLING o RISING
28
29     Serial.println("Pluviómetro inicializado – Mediciones continuas");
30 }
31
32 void loop() {
33     static unsigned long lastReportTime = 0;
34     unsigned long currentTime = millis();
35
36     if (currentTime - lastReportTime >= REPORT_INTERVAL) {
37         noInterrupts();
38         unsigned long pulses = pulseCount;
39         unsigned long lastTime = lastPulseTime;
40         pulseCount = 0;
41         interrupts();
42
43         if (pulses > 0 && lastTime > 0) {
44             float measurementTime = (currentTime - lastReportTime) / 1000.0;
45             //pulses
46             cantidad_ml = pulses * CALIBRATION_FACTOR;
47         } else {
48
49             cantidad_ml = 0.0;
50         }
51
52         Serial.print("Contador desde la última interrupción: ");
53         Serial.println(pulses);

```

```
54     Serial.print(" | Cantidad desde la ltima interrupci n: ");
55     Serial.print(cantidad_ml/0.000014725, 2); //9.5*15.5 cm Area del
embudo = 0.014725 m^2 / 1000 para pasar de ml a l
56     Serial.println(" l/m^2 | ");
57
58
59     lastReportTime = currentTime;
60 }
61 }
62
63 // Implementaci n de la ISR (ahora sin IRAM_ATTR que causaba
problemas)
64 void hallSensorISR() {
65     pulseCount++;
66     lastPulseTime = micros();
67     Serial.println(" + uno");
68 }
```

Listing D.5: Código pluviómetro.

D.6 Pantalla LCD

```

1 //Pantalla LDC
2 //Conexiones Raspberry Pi Pico W
3 //Conectar VSS —> pin 38
4 //Conectar VDD —> pin 36
5 //Conectar V0 —> Potenci metro central
6 //Conectar RS —> pin 1a
7 //Conectar RW —> pin 38
8 //Conectar E —> pin 2
9 //Conectar D4 —> pin 4
10 //Conectar D5 —> pin 5
11 //Conectar D6 —> pin 6
12 //Conectar D7 —> pin 7
13 //Conectar A —> pin 40
14 //Conectar K —> pin 38
15
16
17 #include <LiquidCrystal.h>
18
19 // Configura pines (RS, E, D4, D5, D6, D7)
20 LiquidCrystal lcd(0, 1, 2, 3, 4, 5); // Usando GP0, GP1, GP2, GP3,
    GP4, GP5
21
22 // Variables para el control del tiempo
23 unsigned long previousTime = 0;
24 const long interval = 3000; // Intervalo de 3 segundos (3000 ms)
25 int step = 0; // Paso actual del bucle
26
27 void setup() {
28     lcd.begin(16, 2); // Inicializa LCD (16 columnas, 2 filas)
29     lcd.print("Iniciando...");
30     delay(1000);
31     lcd.clear();
32 }
33
34 void loop() {
35     unsigned long currentTime = millis(); // Tiempo actual
36
37     // Cada 3 segundos, cambia el mensaje
38     if (currentTime - previousTime >= interval) {
39         previousTime = currentTime; // Reinicia el temporizador
40
41         lcd.clear(); // Limpia la pantalla
42
43         switch (step) {
44             case 0:
45                 lcd.setCursor(0, 0);
46                 lcd.print("Temperatura:");
47                 lcd.setCursor(0, 1);
48                 lcd.print("25.5 C"); // Reemplaza con tu sensor real
49                 break;
50             case 1:
51                 lcd.setCursor(0, 0);
52                 lcd.print("Humedad:");
53                 lcd.setCursor(0, 1);
54                 lcd.print("60%"); // Reemplaza con tu sensor real
55                 break;

```

```
56     case 2:
57         lcd.setCursor(0, 0);
58         lcd.print("Presi n:");
59         lcd.setCursor(0, 1);
60         lcd.print("1013 hPa"); // Reemplaza con tu sensor real
61         break;
62     case 3:
63         lcd.setCursor(0, 0);
64         lcd.print("Indice UV:");
65         lcd.setCursor(0, 1);
66         lcd.print("Moderado"); // Reemplaza con tu sensor real
67         break;
68     }
69
70     step++; // Avanza al siguiente paso
71     if (step > 3) step = 0; // Reinicia el bucle despu s del ndice
    UV
72 }
73 }
```

Listing D.6: Código pantalla LCD.

D.7 Código completo

```

1 #include <Wire.h> //viene integrada con arduino IDE
2 #include <Adafruit_Sensor.h> //Adafruit Unified Sensor by Adafruit
3 #include <Adafruit_BME280.h> //Adafruit BME280 Library by Adafruit
4 #include <LiquidCrystal.h> //viene integrada con arduino IDE
5 #include <WiFi.h> //se instala desde board manager Arduino Mbed OS
   RP2040 Boards
6 #include <PubSubClient.h> //PubSubClient by Nick O'Leary
7
8
9
10 const char* ssid = "TU_SSID_WIFI";
11 const char* password = "TU_CONTRSEA_WIFI";
12
13 const char* mqtt_server = "192.168.1.105"; // IP de PC con Mosquitto
14 const int mqtt_port = 1883; // Puerto por defecto
15
16 WiFiClient espClient;
17 PubSubClient client(espClient);
18
19 // Configuraci n LCD (4-bit)
20 LiquidCrystal lcd(0, 1, 2, 3, 4, 5); // RS=GP0, E=GP1, D4=GP2, D5=GP3
   , D6=GP4, D7=GP5
21
22 // Configuraci n BME280
23 #define I2C_SDA 8 // GP8 (Pin 11)
24 #define I2C_SCL 9 // GP9 (Pin 12)
25 Adafruit_BME280 bme;
26
27 // Configuraci n Sensor UV
28 #define UV_SENSOR_PIN 26 // GP26 (ADC0)
29 #define FACTOR_CONVERSION 7.64 // falta restar 1.97
30
31 // Configuraci n Veleta
32 #define pinVeleta 27 // GP27 (ADC1)
33
34 // Configuraci n Anem metro
35 #define pinAnemometro 20 // GP20
36 #define CALIBRATION_FACTOR_ANEMOMETRO 0.0377 // Factor de calibraci n
   2*pi*r*60/1000 (r=0.1 m)
37 #define REPORTINTERVAL 3000
38 volatile unsigned long pulseCountAnem = 0;
39 volatile unsigned long lastPulseTimeAnem = 0;
40 float rpm = 0.0;
41 float windSpeedKmh = 0.0;
42
43 // Configuraci n Pluvi metro
44 #define pinPluviometro 21 // GP21
45 #define CALIBRATION_FACTOR_PLUVIOMETRO 3.7 // Factor de calibraci n
   3.7 ml cada balanceo
46 volatile unsigned long pulseCountPluv = 0;
47 volatile unsigned long lastPulseTimePluv = 0;
48 float contador_min = 0.0;
49 float cantidad_ml = 0.0;
50
51 // Variables de envio de datos
52 float temp = 0.0;

```

```

53 float hum = 0.0;
54 float pres = 0.0;
55 float grados = 0.0;
56 float uv = 0.0;
57
58 // Interrupciones
59 void hallSensorISRanem();
60 void hallSensorISRpluv();
61
62 void setup() {
63     // Inicia Serial Monitor
64     Serial.begin(115200);
65     while(!Serial); // Espera solo en entornos con USB nativo
66     setup_wifi();
67     client.setServer(mqtt_server, mqtt_port);
68     Serial.println("\n\nIniciando sistema...");
69
70     // Inicia LCD
71     lcd.begin(16, 2);
72     lcd.print("Iniciando...");
73     delay(1000);
74     lcd.clear();
75
76     // Inicia I2C
77     Wire.setSDA(I2C_SDA);
78     Wire.setSCL(I2C_SCL);
79     Wire.begin();
80
81     // Inicia Anemometro
82     pinMode(pinAnemometro, INPUT_PULLUP);
83     attachInterrupt(digitalPinToInterrupt(pinAnemometro),
84         hallSensorISRanem, RISING); // FALLING o RISING
85
86     // Inicia Pluviometro
87     pinMode(pinPluviometro, INPUT_PULLUP);
88     attachInterrupt(digitalPinToInterrupt(pinPluviometro),
89         hallSensorISRpluv, RISING); // FALLING o RISING
90
91     // Intenta conectar al BME280 (prueba ambas direcciones)
92     bool bme_status = false;
93     if (!bme.begin(0x76)) {
94         Serial.println("Fall 0x76, probando 0x77...");
95         bme_status = bme.begin(0x77);
96     } else {
97         bme_status = true;
98     }
99
100     if (!bme_status) {
101         Serial.println("Error BME280! Verifica:");
102         Serial.println("— Conexiones SDA/SCL a GP8/GP9");
103         Serial.println("— Alimentaci n 3.3V estable");
104         Serial.println("— Direcci n I2C (0x76/0x77)");
105         lcd.clear();
106         lcd.print("Error BME280");
107         while(1);
108     }
109     Serial.println("BME280 conectado!");
110 }

```

```

109 // Configura sensor UV
110 pinMode(UV_SENSOR_PIN, INPUT);
111 Serial.println("Sistema listo");
112 lcd.clear();
113 lcd.print("Sistema listo");
114 delay(1000);
115 }
116
117 void loop() {
118
119     if (!client.connected()) {
120         reconnect();
121     }
122     client.loop();
123     static unsigned long lastMsg = 0;
124     if (millis() - lastMsg > 6000) {
125         lastMsg = millis();
126         String mensaje = "{";
127         mensaje += "\"t\":" + String(temp, 2) + ","; //comentario
128         mensaje += "\"h\":" + String(hum, 2) + ",";
129         mensaje += "\"pn\":" + String(pres, 2) + ",";
130         mensaje += "\"v\":" + String(grados, 2) + ",";
131         mensaje += "\"a\":" + String(windSpeedKmh, 2) + ",";
132         mensaje += "\"pl\":" + String(cantidad_ml, 2) + ",";
133         mensaje += "\"r\":" + String(uv, 2);
134         mensaje += "}";
135
136         char buffer[mensaje.length() + 1];
137         mensaje.toCharArray(buffer, sizeof(buffer));
138
139         client.publish("/teleco/estacion1", buffer);
140
141         Serial.println("Mensajes publicado");
142     }
143
144
145     static unsigned long lastUpdate = 0;
146     static uint8_t displayState = 0;
147     static unsigned long lastReportTime = 0;
148     unsigned long currentTime = millis();
149
150     if (currentTime - lastReportTime >= REPORTINTERVAL) {
151         noInterrupts();
152         unsigned long pulsesAnem = pulseCountAnem;
153         unsigned long lastTimeAnem = lastPulseTimeAnem;
154         pulseCountAnem = 0;
155
156         unsigned long pulsesPluv = pulseCountPluv;
157         unsigned long lastTimePluv = lastPulseTimePluv;
158         pulseCountPluv = 0;
159         interrupts();
160
161         float measurementTime = (currentTime - lastReportTime) / 1000.0;
162
163         if (pulsesAnem > 0 && lastTimeAnem > 0) {
164             rpm = (pulsesAnem / measurementTime) * 60.0;
165             windSpeedKmh = rpm * CALIBRATION_FACTOR_ANEMOMETRO;
166         } else {

```

```

167     rpm = 0.0;
168     windSpeedKmh = 0.0;
169 }
170
171 if (pulsesPluv > 0 && lastTimePluv > 0) {
172     //pulsesPluv pulsos pluv
173     cantidad_ml = pulsesPluv * CALIBRATION_FACTOR_PLUVIOMETRO;
174 } else {
175
176     cantidad_ml = 0.0;
177 }
178
179 lastReportTime = currentTime;
180 //}
181
182 //if (millis() - lastUpdate >= 3000) {
183 //    lastUpdate = millis();
184
185     // Lectura de sensores
186     temp = bme.readTemperature();
187     hum = bme.readHumidity();
188     pres = bme.readPressure() / 100.0F;
189
190     int uv_raw = analogRead(UV_SENSOR_PIN);
191     uv = (uv_raw / 1023) * 3.3 * FACTOR_CONVERSION - 1.97;
192     String riesgo_uv;
193     if (uv < 3) {
194         riesgo_uv = "Bajo";
195     } else if (uv >= 3 && uv < 6) {
196         riesgo_uv = "Moderado";
197     } else if (uv >= 6 && uv < 8) {
198         riesgo_uv = "Alto";
199     } else if (uv >= 8 && uv < 11) {
200         riesgo_uv = "Muy Alto";
201     } else {
202         riesgo_uv = "Extremo";
203     }
204
205     int lectura = analogRead(pinVeleta); // Leer se al anal gica
206     (0-800 en Pico) 0/800 norte 0 , 200 este 90 , 400 sur 180 , 600
207     oeste 270 ETIQUETA APUNTA AL NORTE!!!
208     grados = lectura * (360.0 / 800.0);
209
210     // Debug en Serial Monitor
211     Serial.println("\n— Lectura de sensores —");
212     Serial.print("Temperatura: "); Serial.print(temp, 1); Serial.
213     println(" C ");
214     Serial.print("Humedad: "); Serial.print(hum, 1); Serial.println("
215     %");
216     Serial.print("Presi n: "); Serial.print(pres, 1); Serial.println("
217     hPa");
218     Serial.print(" ndice UV: "); Serial.print(uv, 1); Serial.print("
219     UVI | Riesgo "); Serial.println(riesgo_uv);
220     Serial.print("Direccion viento: "); Serial.print(grados, 1);
221     Serial.println(" ");
222     Serial.print("Velocidad viento: "); Serial.print(windSpeedKmh, 2);
223     Serial.println(" km/h");

```



```

217     Serial.print("Precipitaci n: "); Serial.print(cantidad_ml/0.00001
4725, 2); Serial.println(" l/m^2"); //9.5*15.5 cm Area del embudo =
    0.014725 m^2 /1000 para pasar de ml a l
218
219
220
221 // Mostrar en LCD
222 lcd.clear();
223 switch(displayState) {
224     case 0:
225         lcd.print("Temperatura: ");
226         lcd.setCursor(0, 1);
227         lcd.print(temp, 1); lcd.print(" C");
228         break;
229     case 1:
230         lcd.print("Humedad: ");
231         lcd.setCursor(0, 1);
232         lcd.print(hum, 1); lcd.print(" %");
233         break;
234     case 2:
235         lcd.print("Presion: ");
236         lcd.setCursor(0, 1);
237         lcd.print(pres, 1); lcd.print(" hPa");
238         break;
239     case 3:
240         lcd.print("Indice UV:");
241         lcd.setCursor(0, 1);
242         lcd.print(uv, 1); lcd.print(" UVI");
243         break;
244     case 4:
245         lcd.print("Direccion viento:");
246         lcd.setCursor(0, 1);
247         lcd.print(grados, 1); lcd.print(" grados");
248         break;
249     case 5:
250         lcd.print("Velocidad viento:");
251         lcd.setCursor(0, 1);
252         lcd.print(windSpeedKmh/3.6, 1); lcd.print(" km/h");
253         break;
254     case 6:
255         lcd.print("Precipitacion:");
256         lcd.setCursor(0, 1);
257         lcd.print(cantidad_ml, 1); lcd.print(" ml/min");
258         break;
259 }
260 displayState = (displayState + 1) % 7;
261
262 }
263 }
264
265 void hallSensorISRanem() {
266     pulseCountAnem++;
267     lastPulseTimeAnem = micros();
268 }
269
270 void hallSensorISRpluv() {
271     pulseCountPluv++;
272     lastPulseTimePluv = micros();

```

```

273 }
274
275 void setup_wifi() {
276     delay(10);
277     Serial.println("Conectando a WiFi...");
278     WiFi.begin(ssid, password);
279
280     while (WiFi.status() != WL_CONNECTED) {
281         delay(500);
282         Serial.print("."); Serial.print(WiFi.status());
283     }
284
285     Serial.println("\nWiFi conectado");
286     Serial.print("IP: ");
287     Serial.println(WiFi.localIP());
288 }
289
290
291 void reconnect() {
292     // Intenta conectar al broker
293     while (!client.connected()) {
294         Serial.print("Conectando a MQTT...");
295
296         const char* mqtt_user = "TU_USUARIO_MQTT";
297         const char* mqtt_pass = "TU_CONTRASEA_MQTT";
298
299
300         if (client.connect("pico_pub_client", mqtt_user, mqtt_pass)) {
301             Serial.println("conectado");
302         } else {
303             Serial.print("Error, rc=");
304             Serial.print(client.state());
305             Serial.println(" intentando de nuevo en 5 segundos");
306             delay(5000);
307         }
308     }
309 }
310
311 /* =====
312 ESTACION METEOROLGICA – CONEXIONES RASPBERRY PI PICO W
313 =====*/
314
315 // =====
316 // PANTALLA LCD 1602A (4-bit mode)
317 // =====
318 /*
319 VSS —> PIN 38 (GND)           // Tierra
320 VDD —> PIN 36 (3V3)           // 5V para mejor contraste
321 VO  —> Potenci metro central // Ajuste de contraste (conectar
                                extremos a VDD y GND)
322 RS  —> PIN 1 (GP0)             // Registro de selecci n
323 RW  —> PIN 38 (GND)           // Modo escritura (siempre a GND)
324 E   —> PIN 2 (GP1)             // Habilitaci n
325 D4  —> PIN 4 (GP2)             // Bit 4 datos
326 D5  —> PIN 5 (GP3)             // Bit 5 datos
327 D6  —> PIN 6 (GP4)             // Bit 6 datos
328 D7  —> PIN 7 (GP5)             // Bit 7 datos
329 A   —> PIN 40 (VBUS)           // Retroiluminaci n (+)

```

```

330 K    —> PIN 38 (GND)                // Retroiluminaci n (–)
331 */
332
333 // _____
334 // SENSOR BME280 (T/H/P)
335 // _____
336 /*
337 VCC —> PIN 36 (3V3)                // Alimentaci n 3.3V
338 GND —> PIN 38 (GND)                // Tierra
339 SCL —> PIN 12 (GP9)                // Reloj I2C
340 SDA —> PIN 11 (GP8)                // Datos I2C
341 SDO —> GND 38 (GND)                // Direcci n I2C 0x76 (si va a 3V3
    ser a 0x77)
342 CSB —> PIN 36 (3V3)                // Modo I2C (debe estar a 3V3)
343 */
344
345 // _____
346 // SENSOR UV GUA-S12SD
347 // _____
348 /*
349 VCC —> PIN 36 (3V3)                // Alimentaci n 3.3V
350 GND —> PIN 38 (GND)                // Tierra
351 SIG —> PIN 31 (GP26)                // Salida anal gica (ADC0)
352 */
353
354 // _____
355 // ANEMOMETRO/SENSOR HALL-SS49E
356 // _____
357 /*
358 VCC (1)—> PIN 36 (3V3)                // Alimentaci n 3.3V
359 GND (2)—> PIN 38 (GND)                // Tierra
360 VOUT (3) —> PIN 26 (GP20)            // Salida
361 */
362
363 // _____
364 // PLUVIOMETRO/SENSOR HALL-SS49E
365 // _____
366 /*
367 VCC (1)—> PIN 36 (3V3)                // Alimentaci n 3.3V
368 GND (2)—> PIN 38 (GND)                // Tierra
369 VOUT (3) —> PIN 27 (GP21)            // Salida
370 */
371
372 // _____
373 // POTENCIMETRO 3296 (CONTRASTE LCD)
374 // _____
375 /*
376 Pin lateral 1 —> PIN 40 (3V3)        // Voltaje referencia
377 Pin central   —> VO (LCD)            // Ajuste de contraste
378 Pin lateral 2 —> PIN 38 (GND)        // Tierra
379 */
380
381 // _____
382 // VELETA ZTS-3000-FXJT-V05-360 (DIRECCIN)
383 // _____
384 /*
385 NEGRO —> GND OUT Conversor y Patilla (1) Resistencia 270
    // Tierra

```

```

386  MARRON —> VOUT Conversor
      // Alimentaci n 3.3V
387  AMARILLO —> GND OUT Conversor y Patilla (1) Resistencia 270
      // Tierra
388  AZUL —> PIN 32 y Patilla (2) Resistencia 270
      // Datos ADC1
389 */
390
391 // _____
392 // CONVERSION (3.3V —> 10V)
393 // _____
394 /*
395  VIN —> PIN 36 (3V3)                                // Alimentaci n
      3.3V
396  GNDIN —> PIN 38 (GND)                                // Tierra
397  GNDOUT —> NEGRO Y AMARILLO VELETA Y RES1            //
      Alimentaci n 10V
398  VOUT —> MARRON VELETA                                // Tierra
399 */
400
401 // _____
402 // RESISTENCIA (270 )
403 // _____
404 /*
405  RES1 —> NEGRO Y AMARILLO VELETA Y VOUT CONVERSION
406  RES2 —> AZUL Y PIN 32
407 */

```

Listing D.7: Código completo.

Anexo E

Listado de materiales

Bill Of Materials for Estación Meteorológica

Design Title Estación Meteorológica
Author Mario Acevedo
Document Number 1
Revision 2
Design Created martes, 6 de mayo de 2025
Design Last Modified viernes, 20 de junio de 2025
Total Parts In Design 13

Notes

PLA impresión 3D = 12,95 €
 Tornillería utilizada = 16 tornillos de 4ml, 2 perfiles, 44 tuercas y arandelas de 4ml, 15 tornillos en punta pequeños 6,15 €
 Precio PCB = 5,73 €
 Precio rodamiento = 2,13 €
 Precio plancha metraquilato = 12 €
 Precio imanes = 1,29 €

Al precio Totals hay que sumarle 40,25 €

3 Resistors

Quantity	References	Value	Farnell Code	PCB Package	Unit Cost
1	R1	270 ohm	9334254	RESC1608X50N	€0,08
1	R3	10 Kohm	3769675	RESC1608X50N	€0,62
1	R4	220 ohm	2321743	RESC1608X50N	€0,42
Sub-totals:					€1,12

10 Miscellaneous

Quantity	References	Value	Farnell Code	PCB Package	Unit Cost
1	BME280	BME280	AMAZON B0D4VYH3H8	MODULE_BME280	€3,28
1	CONVERSORA 10V	NDUB22TA	AMAZON B0DQY31H96	CONVERSION	€6,58
1	GUVA-S12SD	GUVA-S12SD (Intensidad UV)	AMAZON B07BFNZWR9	MODULE_GUVA	€2,36
2	HALL ANEMOMETRO,HALL PLUVIOMETRO	MLX90217LUACAA000BU	1225624	BORNAS	€1,00
1	PANTALLA LCD 1602A	CEG003400	2281679	MODULE_CEG003400	€2,83
1	POTENCIOMETRO	3296Y1102 - 2Kohm	9353518	TRIM_3296Y1102	€2,41
1	RASPBERRY PI PICO W	RASPBERRY_PI_PICO_W	3996082	MODULE_RASPBERRY PI PICO W	€6,39
1	RESET	VW39	3406898	BOTON	€1,22
1	VELETA	ZTS-3000-FXJT-V05-360	ALIEXPRESS 1005003040677398	VELETA BUENO	€19,65
Sub-totals:					€46,72

Totals: €47,84

viernes, 20 de junio de 2025 9:41:35